San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

FEB 0 9 2018

Mr. Greg Pritchett
Chevron USA, Inc
PO Box 1392
Bakersfield, CA 93302

Re: Notice of Preliminary Decision – Title V Permit Renewal
Facility Number: C-311
Project Number: C-1161895

Dear Mr. Pritchett:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Chevron USA, Inc at Heavy Oil Production Facility at the Coalinga Field in Fresno County, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation
Chevron USA Inc
C-311

TABLE OF CONTENTS

I. PROPOSAL 1
II. FACILITY LOCATION 1
III. EQUIPMENT LISTING 2
IV. GENERAL PERMIT TEMPLATE USAGE 2
V. SCOPE OF EPA AND PUBLIC REVIEW 2
VI. FEDERALLY ENFORCEABLE REQUIREMENTS 2
VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE 6
VIII. PERMIT REQUIREMENTS 7
IX. PERMIT SHIELD 30
X. CALIFORNIA ENVIRONMENTAL QUALITY ACT 31
XI. PERMIT CONDITIONS 32
XII. ATTACHMENTS 32

A. DRAFT RENEWAL TITLE V OPERATING PERMIT
B. PREVIOUS TITLE V OPERATING PERMIT
C. DETAILED SUMMARY LIST OF FACILITY PERMITS

TITLE V PERMIT RENEWAL EVALUATION

Heavy Oil Production

Engineer: Gurpreet Brar
Date: January 17, 2018

Facility Number: C-311
Facility Name: Chevron USA, Inc
Mailing Address: PO Box 1392
Bakersfield, CA 93302
Contact Name: Greg Pritchett,
Phone: (661) 654-7141

Responsible Official: Chris Powers
Title: Area Manager

Project #: C-1161895
Deemed Complete: September 15, 2016

I. PROPOSAL

Chevron USA, Inc was issued their last renewed Title V Permit on January 20, 2012. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V Permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the last renewal of the Title V Permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

Chevron USA, Inc is located at Heavy Oil Production in Fresno County, CA.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant does not propose to use any model general permit templates.

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Renewed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated and Evaluated

- District Rule 2020, Exemptions
  (amended December 20, 2007 ⇒ amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule
  (amended April 21, 2011 ⇒ amended February 18, 2016)
- District Rule 2520, Federally Mandated Operating Permits
  (amended June 21, 2001)

- District Rule 4621, Gasoline Transfer Into Stationary Storage Containers, Delivery Vessels, And Bulk Plants
  (amended December 20, 2007 ⇒ amended December 19, 2013)

- District Rule 4622, Gasoline Transfer into Motor Vehicle Fuel Tanks
  (amended December 20, 2007 ⇒ amended December 19, 2013)

- District Rule 4702, Internal Combustion Engines
  (amended August 18, 2011 ⇒ amended November 14, 2013)

- 40 CFR Part 60 Subpart GG, Standards of Performance for Stationary Gas Turbines
  (amended February 27, 2014)

- 40 CFR Part 60 Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines
  (amended July 7, 2016)

- 40 CFR Part 63 Subpart ZZZZ, National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines
  (amended February 27, 2014)

- 40 CFR Part 64, Compliance Assurance Monitoring
  (adopted October 22, 1997)

- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners
  (amended October 28, 2014)

- 40 CFR Part 82, Subpart F, Recycling and Emissions Reduction
  (amended November 18, 2016)

B. Rules Removed

There are no applicable rules that were removed since the last Title V permit renewal.

C. Rules Added

- District Rule 2410, Prevention of Significant Deterioration
  (adopted June 16, 2011)

D. Rules Not Updated

- District Rule 1070, Inspections
  (amended December 17, 1992)
- District Rule 1080, Stack Monitoring
  (amended December 17, 1992)
- District Rule 1081, Source Sampling
  (amended December 17, 1992)
- District Rule 1100, Equipment Breakdown
  (amended December 17, 1992)
- District Rule 1160, Emission Statements
  (amended November 18, 1992)
- District Rule 2010, Permits Required
  (amended December 17, 1992)
- District Rule 2031, Transfer of Permits
  (amended December 17, 1992)
- District Rule 2040, Applications
  (amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications
  (amended December 17, 1992)
- District Rule 2080, Conditional Approval
  (amended December 17, 1992)
- District Rule 4101, Visible Emissions
  (amended February 17, 2005)
- District Rule 4201, Particulate Matter Concentration
  (amended December 17, 1992)
- District Rule 4202, Particulate Matter - Emission Rate
  (amended December 17, 1992)

- District Rule 4301, Fuel Burning Equipment
(amended December 17, 1992)

- District Rule 4305, Boilers, Steam Generators, and Process Heaters - Phase 2
(amended August 21, 2003)

- District Rule 4306, Boilers, Steam Generators and Process Heaters - Phase 3
(amended October 16, 2008)

- District Rule 4320, Advanced Emissions Reduction Options for Boiler, Steam Generators, and Process Heaters Greater Than 5.0 MMBtu/hr
(amended October 16, 2008)

- District Rule 4401, Steam-Enhanced Crude Oil Production Wells
(amended June 11, 2011)

- District Rule 4601, Architectural Coatings
(amended December 17, 2009)

- District Rule 4623, Storage of Organic Liquids
(amended May 19, 2005)

- District Rule 4624, Transfer of Organic Liquid
(amended December 20, 2007)

- District Rule 4701, Internal Combustion Engines - Phase 1
(amended August 21, 2003)

- District Rule 4703, Stationary Gas Turbines
(amended September 20, 2007)

- District Rule 4801, Sulfur Compounds
(amended December 17, 1992)

- District Rule 8011, Fugitive Dust General Requirements
(amended August 19, 2004)

- District Rule 8021, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Construction, Demolition, Excavation, and Extraction Activities
(amended August 19, 2004)

- District Rule 8031, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Handling and Storage of Bulk Materials (amended August 19, 2004)
- District Rule 8041, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Open Area (amended August 19, 2004)
- District Rule 8061, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Paved and Unpaved Roads (amended August 19, 2004)
- District Rule 8071, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Unpaved Vehicle/Equipment Areas (amended September 16, 2004)
- 40 CFR 60, Subpart A, General Provisions
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos
- 40 CFR Part 68, Chemical Accident Prevention Provisions

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains both the federally enforceable requirements as well as District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V Permit are designated as "Federally Enforceable through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Added/Updated

None

B. Rules Not Updated

- District Rule 4102, Nuisance (as amended December 17, 1992)
- Title 17 California Code of Regulations (CCR), Section 93115, Airborne Toxic Control Measure (ATCM) for Stationary Compression Ignition (CI) Engines
- Title 17 California Code of Regulations (CCR), Section 93116, Airborne Toxic Control Measure (ATCM) for Diesel Particulate Matter from Portable Engines Rated at 50 Horsepower and Greater

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this section will address rules and permit conditions that have been amended or added since the issuance of the initial Title V Permit or most recent renewal of the Title V permit.

Dormant Emission Units:

Permit units C-311-13, -15, -19, -22, -23, -36 to -41, -46 to -51, -114, -117 and -239 are currently out of operation and are designated as dormant emission units by District Permit requirements.

Permit units C-311-13, -15, -47, -114, and -117 are non-compliant dormant emission units and the permit conditions as shown in the following table have been added to these permits requiring that an Authority to Construct (ATC) permit must be acquired before the facility operates the units. In addition, the facility will be required to submit an ATC application to comply with Title V requirements of District Rule 2520 prior to operating. Therefore these permit units will not be evaluated further in this permitting action.

Draft Permits	Permit Condition
C-311-13-14, -15-13, -114-10 and -117-10	1
C-311-47-13	4

All other dormant permit units are compliant with the District Rules will be evaluated further to review changes to the federally enforceable requirements.

A. District Rule 2020, Exemptions

District Rule 2020 lists equipment that is exempt from obtaining permits and specifies recordkeeping requirements to verify such exemptions. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

Condition 4 on draft facility-wide permit C-311-0-4 will serve as a mechanism to enforce compliance.

B. District Rule 2201, New and Modified Stationary Source Review (NSR) Rule

District Rule 2201 has been amended since this facility's initial Title V permit was issued. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit.

C. District Rule 2410, Prevention of Significant Deterioration

District Rule 2410 has been newly adopted since this Title V permit was last renewed. However the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any PSD permit actions have already been incorporated into the current Title V permit.

D. District Rule 2520, Federally Mandated Operating Permits

No changes to this Rule have occurred since issuance of the previous Title V permit; however, greenhouse gas emissions will be addressed under Rule 2520 during this renewal.

Greenhouse Gas Discussion

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

E. District Rule 4621, Gasoline Transfer Into Stationary Storage Containers, Delivery Vessels, and Bulk Plants

The purpose of this rule is to limit VOC emissions from stationary storage containers, delivery vessels, and bulk plants and to provide the administrative requirements for determining compliance with this rule. The rule applies to applies to gasoline storage containers located at bulk plants with capacities greater than 250 gallons and less than 19,800 gallons; to other stationary gasoline storage containers with capacities greater than 250 gallons; to those gasoline storage containers that are not subject to the control requirements of District Rule 4623 (Storage of Organic Liquids); and to gasoline delivery vessels.

This rule was amended on December 19, 2013. The amended rule removed ARB (California Air Resources Board) certification requirements for aviation gasoline bulk loading operations. Instead of ARB certifications, these operations would be required to be equipped with a vapor recovery system that would meet a minimum volumetric control of 90% as required by ARB's Certification Procedure (CP-202) for Vapor Recovery Systems of Bulk Plants (March 17, 1999). The rule was also amended to incorporate these testing requirements and eliminate the ARB certification requirement.

Permit S-311-227 at the facility is currently subject to Rule 4621, but the gasoline storage operation under this permit is not used as aviation gasoline bulk loading operation. Therefore, none of the operations were affected by the rule amendment. Therefore, continued compliance with the rule is expected.

The following conditions on the draft permit will ensure compliance with the requirements of this rule.

Draft Permits	Permit Conditions
C-311-227-4	1, 3, 4, 5, 6, 10, 11, 15, 16, 20 to 23, 27, and 28

F. District Rule 4622, Transfer of Gasoline Into Vehicle Fuel Tanks

The purpose of this rule is to limit emissions of gasoline vapors from the transfer of gasoline into motor vehicle fuel tanks. District Rule 4622 applies to any gasoline storage and dispensing operation or mobile fueler from which gasoline is transferred into motor vehicle fuel tanks, except certain exemptions identified in Section 4.0 of the rule.

The facility maintains one non-retail aboveground gasoline storage tank, permit unit C-311-227. This rule was amended on December 19, 2013. There were new definitions added, provisions added for E85 fuel, revisions to inspection frequency, requirements for liquid condensate traps, requirements for in-station diagnostic systems (ISD), and revised testing requirements.

Section 3.29 of this rule defines a retail gasoline outlet as an establishment at which gasoline is sold or offered for sale to the general public for use in motor vehicles.

Section 5.1 states "a person shall not transfer or permit the transfer of gasoline from any stationary storage container, or from any mobile fueler with a capacity greater than 120 gallons, into a motor vehicle fuel tank with a capacity greater than 5 gallons, unless the gasoline dispensing unit used to transfer the gasoline is equipped with and has in operation an ARB certified Phase II vapor recovery system."

Section 5.1.1 states "all ARB certified Phase II vapor recovery systems shall be maintained according to ARB certifications and the manufacturer specifications applicable to the system." Since the gasoline dispensing unit is equipped with an ARB certified Phase II vapor recovery system, requirements of this section are satisfied and compliance is expected.

In addition, ARB has the additional certification requirements, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification.

Section 5.1.2 states "all ARB certified Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method in Section 6.5.4." Section 6.5.4 states "detection of leaks shall be in accordance with EPA Test Method 21." Section 3.20 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.5.4.

Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

Section 5.2.1 states "any gasoline dispensing system subject to this rule shall comply with the provisions of this rule at the time of installation." Section 5.2.2 states "operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. The operator shall notify the District by telephone or other District-approved method and obtain a confirmation number at least three business days prior to the backfilling."

Per District's policy, the aboveground tanks with balance Phase II vapor recovery system are not allowed to have a remote dispenser. Any dispenser that is more than two feet away from the tank is considered a remote dispenser. It is very unlikely for a non-remote dispenser to have underground vapor pipes and instead most of the aboveground tanks with balance Phase II systems have top or side mounted dispensers. Therefore, no underground piping is involved with the aboveground tank and this section does not apply.

Section 5.2.3 states "installation and maintenance contractors shall, be certified by the ICC for Vapor Recovery System Installation and Repair, renew the ICC certification for Vapor Recovery System Installation and Repair every 24 months, make available onsite proof of ICC certification, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems." Section 5.2.4 states "in lieu of complying with Sections 5.2.3.1 through 5.2.3.4, installation and maintenance contractors may work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available on site current certifications from the ICC, indicating he or she has passed the ICC Vapor Recovery System Installation and Repair exam and all other certifications required by the applicable ARB Executive Order."

Section 5.3.1 states "the owner or operator of an ARB certified Phase II vapor recovery system shall conduct periodic maintenance inspections to ensure that components of the vapor recovery system are in proper operating condition."

Section 5.3.2 states "the frequency of inspections shall be based on the operation's largest monthly gasoline throughput from the previous calendar year as indicated in Table 1."

Section 5.3.3 states "the frequency of vapor path inspections shall be based on the amount of gasoline dispensed by the operation in a calendar month as indicated in Table 1."

Section 5.3.4 states "the person conducting the inspections shall at a minimum, verify that the fueling instructions required by Section 5.5 are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs, that the following nozzle components are in place and in good condition as specified in ARB Executive Orders: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, hold open latch, that the hoses are not torn or crimped, that the vapor path of coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid, or as required by the applicable ARB Executive Order, and that the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit."

Section 5.4.1 states "no person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect, until: The defect has been repaired, replaced, or adjusted as necessary to correct the defect; The District has been notified, and the District has reinspected the system or authorized the system for use. Such authorization shall not include the authority to operate the equipment prior to the correction of the defective components; and all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual."

Section 5.4.2 states "upon identification of any major defects, the owner or operator shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired."

Section 5.4.2.1 states "tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary."

Section 5.4.2.2 states "in the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use."

Section 5.4.4 states "in the event of a separation due to a drive off, the owner or operator shall complete one of the following, unless otherwise specified in the applicable ARB Executive Order, and document the activities in accordance with Section 6.2, before placing the affected equipment back in service:"

> Conduct a visual inspection of the affected equipment, perform qualified repairs on any damaged components, and conduct applicable re-verification tests pursuant to Sections 6.5.1.1 and 6.5.1.4, or"
>
> Conduct a visual inspection of the affected equipment and replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified, before placing affected equipment back in service."

Section 6.2.1 states "operators shall retain the test result verification that each ARB certified Phase II vapor recovery system meets or exceeds the requirements of the tests specified in Section 6.5. These verifications shall be maintained for at least five years. These test results shall be dated and shall contain the names, addresses, and telephone numbers of the companies responsible for system installation and testing."

Section 6.2.2 states "a person who performs repairs on any ARB certified Phase I or Phase II vapor recovery system shall provide to the owner or operator a repair log, which the owner or operator shall maintain on the premises for at least five years and which shall include all of the following:"

Date and time of each repair;
The name and applicable certification numbers of the person(s) who performed the repair, and, if applicable, the name, address and phone number of the person's employer;
Description of service performed;
Each component that was repaired, serviced, or removed;
Each component that was installed as replacement, if applicable;
Receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs.

Section 6.2.3 states "each operator who is required to perform periodic maintenance inspections under Section 5.3 shall maintain monthly gasoline throughput records on the premises for a minimum of five years, make them available on site during normal business hours to the APCO, ARB, or EPA, and submit them to the APCO, ARB, or EPA upon request."

Section 6.3.1 states "the owner or operator of a gasoline dispensing operation shall maintain an O&M Manual in accordance with Section 6.3."

Section 6.3.2 states "the O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request."

Section 6.3.3 states "the O&M manual shall, at a minimum, include the following current information:"

Copies of all vapor recovery performance tests,
All applicable ARB Executive Orders, Approval Letters, and District Permits,
Manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to applicable ARB Certification procedures, and any additional instruction provided by the manufacturer,
System and/or component testing requirements, including test schedules and passing criteria for each of the standard tests listed in Section 6.0. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements, and additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components.

Section 6.3.4 states "owners or operators of gasoline dispensing operations shall document the periodic maintenance inspection program in the O&M manual."

Section 6.4.1 states "operators shall comply with the ARB certified Phase II vapor recovery system performance tests specified in Sections 6.4.1.1 through 6.4.1.4 and shall conduct all applicable performance tests at start up and thereafter (no more than 30 days before or after the required compliance testing date) as required by the applicable ARB Executive Order and installation and operation manuals."

Section 6.4.1.1 states "conduct and pass a Static Leak Test of the ARB certified Phase II vapor recovery system at least once every twelve months."

Section 6.4.1.2 states "conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every five years except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under the applicable ARB Executive Order." All balance Phase II systems require integral dispensers (top or side mounted). Back pressure test is designed to verify if there is any blockage in the vapor return path for Phase II vapor recovery systems with remote dispenser(s). Per District policy, a remote dispenser is defined as more than two feet away from the AST. Since the balance Phase II vapor recovery system for AST involved with this operation has top or side mounted dispenser, this test is not necessary; therefore, no further discussion is required under this section.

Section 6.4.1.3 states "for ARB certified Phase II vapor recovery systems with bellows-less nozzles, conduct and pass, as applicable, an Air-to-Liquid Volume Ratio Test or a Vapor-to-Liquid Ratio Test at least once every six months."

Section 6.4.1.4 states "for ARB certified Phase II vapor recovery systems with a liquid removal device required by ARB Executive Orders, conduct and pass a Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be determined in accordance with the procedure specified in Section 5.3.4.4."

Section 6.4.2 states "the person responsible for conducting the tests specified in Section 6.4 shall use calibrated equipment meeting the calibration range and calibration intervals specified by the manufacturer, ARB Executive Order, or ARB test procedure."

Section 6.4.3 states "Persons responsible for conducting the tests specified in Section 6.5 shall be in full compliance with all provisions of Rule 1177 (Gasoline Dispensing Facility Tester Certification)."

Section 6.4.4 states "each gasoline dispensing operation shall notify the District at least seven days prior to any performance testing."

Section 6.4.5 states "each ARB certified Phase II vapor recovery system shall be tested within 60 days of completion of installation or modification."

Section 6.5.1 states "tests shall be conducted in accordance with the latest version of the following ARB and EPA approved test methods, or their equivalents as approved by the EPA, and the APCO."

Section 6.5.1.2 states "Dynamic Back-Pressure Test, ARB TP-201.4"
Section 6.5.1.3 states "Air-to-Liquid Volume Ratio Test, ARB TP-201.5"
Section 6.5.1.4 states "Liquid Removal Test, ARB TP-201.6C"
Section 6.5.1.5 states "Static Leak Test for Aboveground Tanks, ARB TP-206.3 or TP-201.3B as applicable."

The following conditions on the draft permit will serve as a mechanism to enforce compliance with the requirements of this rule.

Draft Permit	Permit Conditions
C-311-227-4	1, 2, 4, 5, 7 to 10, 12, 13, 15 to 22, and 24 to 28

G. District Rule 4702, Internal Combustion Engines

The purpose of this rule is to limit the emissions of nitrogen oxides (NOx), carbon monoxide (CO), volatile organic compounds (VOC), and sulfur oxides (SOx) from internal combustion (IC) engines. This rule applies to any internal combustion engine rated at 25 brake horsepower or greater. This rule was amended November 14, 2013. The amended involved including a waste gas fueled category of lean-burn engine and associated emissions requirements. All the engines at this facility are diesel-fired IC engines; therefore, no permits at this facility were affected by the rule amendment.

The following conditions on the draft permits will ensure compliance with the requirements of this rule.

Draft Permits	Permit Conditions
C-311-235-3	6, 7, 13, 13 to 19, and 22
C-311-238-4	4, 6, 7, 9, 13, 1,4 and 16
C-311-239-2	10, and 14 to 21
C-311-253-2	3, and 6 to 13

H. 40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

Section 60.4200(a)(2)(i) states that the provisions of this subpart apply to owners and operators of stationary compression ignition (CI) internal combustion engines that commence construction after July 11, 2005, where the engines are:

(i) Manufactured after April 1, 2006, and are not fire pump engines, or
(ii) Manufactured as a certified National Fire Protection Association (NFPA) fire pump engine after July 1, 2006.

The engine permit units C-311-239 and -253 were manufactured after April 1, 2006. Therefore, these units are subject to the requirements of this subpart.

§60.4205(b)(2) states owners and operators of 2007 model year and later emergency stationary CI ICE with a displacement of less than 30 liters per cylinder that are not fire pump engines must comply with the emissions standards for new nonroad CI engines in §60.4202, for all pollutants, for the same model year and maximum engine power for their 2007 model year and later emergency stationary CI ICE.

> §60.4202(a)(2) states that for engines with a maximum engine power greater than or equal to 37 KW (50 HP), the certification emission standards for new nonroad CI engines for the same model year and maximum engine power in 40 CFR 89.112 for all pollutants beginning in model year 2007.
>
> §89.112(a) specified exhaust emission from nonroad engines to which this subpart is applicable shall not exceed the applicable exhaust emission standards contained in Table 1 of this subpart.

The following tables summarizes the emissions limits specified in Table 1 of this regulation for Tier 3 engines power rated in these ranges, the emissions limits of the Tier 3 certified emergency standby engines, and the compliance status.

Pollutant	§89.112(a) Table 1 Emission Limit (g/bhp-hr)	157 hp Engine (C-311-239) Emission Limit (g/bhp-hr)	Compliant?
PM	0.22	0.15	Yes
NO_X + VOC	3.0	2.66	Yes
CO	3.7	1.34	Yes

Pollutant	§89.112(a) Table 1 Emission Limit (g/bhp-hr)	324 hp Engine (C-311-253) Emission Limit (g/bhp-hr)	Compliant?
PM	0.15	0.147	Yes
NO_X + VOC	3.0	3.0	Yes
CO	2.6	2.6	Yes

The following table summarizes the conditions that enforce on-going compliance with these sections:

Draft Permits	**Permit Conditions**
C-311-239-3	13 and 14
C-311-253-2	5

§60.4207(b) requires that owners and operators of stationary CI ICE subject to this subpart with a displacement of less than 30 liters per cylinder that use diesel fuel must purchase diesel fuel that meets the requirements of 40 CFR 80.510(b) for nonroad diesel fuel.

40 FR Part 80 – Regulation of Fuels and Fuel Additives, §80.510(b)(2) requires that all nonroad diesel fuel is subject to the following per-gallon standards.

- Sulfur content - 15 ppm maximum for nonroad diesel fuel
- Cetane index or aromatic content - a minimum cetane index of 40 or a maximum aromatic content of 35 volume percent.

The engines are limited to exclusively use of CARB Diesel Fuel, which has a sulfur content of 15 ppm or less and a maximum aromatic content of 20 percent by volume. Therefore, use of CARB Diesel Fuel satisfies the requirement of this subpart.

The following table summarizes the conditions that enforce on-going compliance with this section:

Draft Permits	Permit Conditions
C-311-239-3	12
C-311-253-2	4

§60.4209(a) states that if you are an owner or operator of an emergency stationary CI internal combustion engine that does not meet the standards applicable to non-emergency engines, you must install a non-resettable hour meter prior to startup of the engine.

The following table summarizes the conditions that enforce on-going compliance with this section:

Draft Permits	Permit Conditions
C-311-239-3	11
C-311-253-2	3

§60.4211(a)(1) requires that the owner or operator must operate and maintain the stationary CI ICE and control device according to the manufacturer's emission-related written instructions.

The following table summarizes the conditions that enforce on-going compliance with this section:

Draft Permits	Permit Conditions
C-311-239-3	15
C-311-253-2	6

§60.4211(f) states that emergency stationary ICE many operated for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Maintenance check and readiness testing or such units is limited to 100 hours per year. There is no time limit on the use of emergency stationary ICE in emergency situations.

However, 17 CCR Section 93115, Airborne Toxic Control Measure for Stationary Compression Ignition Engines limits the non-emergency situation, maintenance and testing purpose, of engine for these sizes to 50 hours per year.

The following table summarizes the conditions that enforce on-going compliance with this section:

Draft Permits	Permit Conditions
C-311-239-2	20
C-311-253-2	11

I. **40 CFR Part 63, Subpart ZZZZ, National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines**

This national emission standard for hazardous air pollutants (NESHAP) is intended to regulate emissions of HAP from stationary reciprocating IC engines. Subpart ZZZZ applies to an existing stationary IC engine, so unit C-311-235 is subject to the requirements of this Subpart.

The February 27, 2014 amendment included revisions to clarify that a heated probe is not necessary when using ASTM D6522 to measure oxygen or carbon dioxide concentrations. The requirement to use Method 1 or 1A for sampling site and sampling point selection in testing gaseous emissions from engines with smaller ducts is deleted, and single or three-point sampling, depending on duct size, is added.

These amendments do not affect the facility's IC engine. The applicable requirements of Subpart ZZZZ are already incorporated in the existing permit. There have been no modifications to the emergency engine to affect compliance with Subpart ZZZZ and continued compliance is expected.

The following conditions on the draft permit C-311-235-3 will serve as a mechanism to enforce compliance with the requirements of this subpart.

Draft Permit	Permit Conditions
C-311-235-3	8 to 16, and 19 to 22

J. 40 CFR Part 60, Subpart GG, Standard of Performance for Stationary Gas Turbines Engines

The provisions of this subpart are applicable to all stationary gas turbines with a heat input at peak load equal to or greater than 10 million Btu per hour. Section 60.335 of this Subpart was amended on February 27, 2014.

The definitions of terms for the ISO correction equation in Section 60.335(b)(1) are revised to allow the reference combustor inlet absolute pressure (P_r) to be measured in millimeters of mercury (mm Hg) or in standard atmosphere. The site barometric pressure is allowed as an alternative to the observed combustor inlet absolute pressure (P_o) for calculating the NO_X emission concentration at 15 percent O_2 and ISO standard ambient conditions.

Since the draft permits have no reference to the ISO correction equation in Section 60.335(b)(1), it does not impact the permit requirements. The amendment to this Subpart does not require any change to the permit conditions.

The following conditions on the draft permits will ensure compliance with the requirements of this subpart.

Draft Permits	Permit Conditions
C-311-88-16	3 to 5, 16, 18, 21, 22, 23, 25, 27, and 31 to 34
C-311-93-14, -95-14 and -97-14	3 to 5, 16, 18, 21, 22, 23, 25, 27, and 31 to 33

K. 40 CFR Part 64, Compliance Assurance Monitoring (CAM)

40 CFR Part 64 requires Compliance Assurance Monitoring for units that meet the following three criteria:

1) the unit must have an emission limit for the pollutant;
2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
NO_X	20,000
SO_X	140,000
PM_{10}	140,000
CO	200,000
VOC	20,000

40 CFR Part 64 defines a control device as equipment, other than inherent process equipment, that is used to destroy or remove air pollutants prior to discharge to the atmosphere.

This subpart defines inherent process equipment as equipment that is necessary for the proper or safe functioning of the process, or material recovery equipment that the owner or operator documents is installed and operated primarily for purposes other than compliance with air pollution regulations. Equipment that must be operated at an efficiency higher than that achieved during normal process operations in order to comply with the applicable emission limitation or standard is not inherent process equipment. For the purposes of this part, inherent process equipment is not considered a control device.

a. C-311-19-25, -20-23, -22-25, -23-22, -25-13, -27-19, -28-22, -30-20, -42-21, -43-19, -45-19, -48-15, -49-15, -50-15, 52-24, -53-21, -76-22, -84-22, and -254-1: Natural Gas-Fired Steam Generators with Low NO_X Burner and FGR

SO_X, PM_{10}, CO, and VOC:

These permit units have emissions limits for SO_X, PM_{10}, CO, and VOC but they do not have add-on controls for these criteria pollutants. Therefore, these permit units are not subject to CAM for SO_X, PM_{10}, CO, and VOC.

NO_X:

These permits may be subject to CAM for NO_X, as there is a NO_X limit, and they do have add-on controls in the form of FGR. The pre-control potential to emit for these units is calculated below.

The control efficiency for FGR was determined using the following AP-42 emission factors from Table 1.4.1 (7/98) for small boilers < 100 MMBtu/hr.

	Emission Factor (lb/10^6 scf)
Uncontrolled	100
Controlled – low NOx burner	50
Controlled Low NOx burner and Flue Gas Recirculation	32

The control efficiency of FGR is,

((50 lb/10^6 scf – 32 lb/10^6 scf) ÷ 50 lb/10^6 scf) x 100 = 36%

The NOx emission factors for these units are limited to 7 ppmv @ 3% O2, 14 ppmv @ 3% O2 or 0.017 lb-MMBtu/hr, or 15 ppmv @ 3% O2 or 0.018 lb-MMBtu/hr (per current permits). These permit units are limited to maximum heat input limits of 434,700 MMBtu/year, 435,000 MMBtu/year, or 457,800 MMBtu/year. The worst-case pre-control emissions will be calculated based on 15 ppmv @ 3% O2 or 0.018 lb-MMBtu/hr, and maximum heat input of 457,800 MMBtu/year.

$\text{Emission Factor}_{\text{Precontrolled}}$ = Controlled EF/(1 – Control Efficiency)
= (0.018 lb-NO_X/MMBtu)/(1 – 0.36)
= 0.028 lb-NO_X/MMBtu

$PE_{\text{Precontrolled}}$ = $\text{Emission Factor}_{\text{Precontrolled}}$ x Heat Input/year
= 0.028 lb-NO_X/MMBtu x 457,800 MMBtu/year
= 12,818 lb-NO_X/year

However, as shown above, the pre-control potential to emit is not greater than the major source threshold of 20,000 pounds NO_X/year. Therefore, these permit units are not subject to CAM for NOx.

b. C-311-21-13: 58.5 MMBtu/hr Natural Gas-Fired Steam Generator with Low NO_X Burner

NOx, SOx, PM_{10}, CO, and VOC:

This permit unit has emissions limits for NOx, SOx, PM_{10}, CO, and VOC but it does not have add-on controls for these criteria pollutants. Therefore, it is not subject to CAM for NOx, SOx, PM_{10}, CO, and VOC.

c. C-311-36-25, -37-30, -38-36, -39-27, -40-27 and -41-26: Maximum Heat Input 62.5 MMBtu/hr Natural Gas-Fired Steam Generator with Low NO_X Burner and FGR Served by a Scrubber (Shared with Units -37, -38, -39, -40, and -41)

PM_{10}, CO, and VOC:

These permit units have emissions limits for PM_{10}, CO, and VOC but they do not have add-on controls for these criteria pollutants. Therefore, these permit units are not subject to CAM for PM_{10}, CO, and VOC.

NOx:

These permits may be subject to CAM for NO_X, as there is a NO_X limit, and they do have add-on controls in the form of FGR. The pre-control potential to emit for these units is calculated below.

The control efficiency for FGR was determined using the following AP-42 emission factors from Table 1.4.1 (7/98) for small boilers < 100 MMBtu/hr.

	Emission Factor (lb/10^6 scf)
Uncontrolled	100
Controlled – low NOx burner	50
Controlled Low NOx burner and Flue Gas Recirculation	32

The control efficiency of FGR is,

((50 lb/10^6 scf – 32 lb/10^6 scf) ÷ 50 lb/10^6 scf) x 100 = 36%

The NOx emission factors for these units are limited to 14 ppmv @ 3% O2 or 0.017 lb-MMBtu/hr (per current permits). The maximum rating of each unit is 62.5 MMBtu/hr. The heat input on current permit is limited to 457,800 MMBtu/year, 434,700 MMBtu/year, or 435, 000 MMBtu/year. The worst-case pre-control emissions will be calculated based on 457,800 MMBtu/year of heat input.

$$\text{Emission Factor}_{\text{Precontrolled}} = \text{Controlled EF}/(1 - \text{Control Efficiency})$$
$$= (0.017 \text{ lb-NO}_X/\text{MMBtu})/(1 - 0.36)$$
$$= 0.027 \text{ lb-NO}_X/\text{MMBtu}$$

$PE_{Precontrolled}$ = Emission $Factor_{Precontrolled}$ x Heat Input/year
= 0.027 lb-NO_X/MMBtu x 457,800 MMBtu/year
= 12,361 lb-NO_X/year

However, as shown above, the pre-control potential to emit is not greater than the major source threshold of 20,000 pounds NO_X/year. Therefore, these permit units are not subject to CAM for NOx.

SO_X:

The engineering evaluation for project C-960342 states that the scrubber was designed for control efficiency of 35.6 percent. The worst case uncontrolled SOx emissions can be calculated based on the maximum annual heat input of 457,800 MMBtu/year and with an emissions factor of 0.052 lb SO_X/MMBtu. The uncontrolled emissions are calculated as follows:

$PE_{Uncontrolled}$ = 0.052 lb SO_X/MMBtu x 457,800 MMBtu/yr ÷ (1 -0.356)
= 36,965 lb SO_X/year

Since 36,965 lb SO_X/year is less that the major source threshold of 140,000 lb SO_X/year, these permit units are not subject to CAM for SOx.

d. C-311-77-8, -78-6, -79-20, -83-22, -111-9, and -112-19: Thermally Enhanced Oil Recovery Operation (TEOR) With Well Vent Vapor Control System

NOx, SOx, PM_{10}, and CO:

These permit units do not have emissions limits for NOx, SOx, PM_{10}, and CO. Therefore, these permit units not subject to CAM for NOx, SOx, PM_{10}, and CO.

VOC:

These permit units have emissions limits for VOC but they do not have add-on controls for this criteria pollutant. The vapor control system serving oil production well is a collection system that meets the criteria for inherent process equipment, and as such is not a control device as defined in this subpart. Therefore, these permit units are not subject to CAM for VOC.

e. C-311-88-16, -93-16, -95-14, and -97-14: 86.4 MMBtu/hr Cogeneration System with a Turbine Engine Served by a Selective Catalytic Reduction (SCR) System with Ammonia Injection and a Continuous Emissions Monitoring System (CEMS)

SOx, PM_{10}, CO, and VOC:

These permit units have emissions limits for SOx, PM_{10}, CO, and VOC but they do not have add-on controls for these criteria pollutants. Therefore, these permit units are not subject to CAM for SOx, PM_{10}, CO, and VOC.

NOx:

These permit units have emissions limits for NOx and have Selective Catalytic Reduction (SCR) system as add-on controls for this criteria pollutant. However, based on 40 CFR Part 64.2(b)(1)(vi), NO_X emissions limits are exempt from CAM since the Part 70 permit already specifies a continuous compliance determination method for NO_X.

f. C-311-105-5, and -106-4: Closed-Vent TEOR Wells and Closed Vent Steam Drive Wells

NOx, PM_{10}, and CO:

These permit units do not have emissions limits for NOx, PM_{10}, and CO. Therefore, it is not subject to CAM for NOx, PM_{10}, and CO.

SOx and VOC:

These permit units have emissions limits for SOx and VOC but they do not have add-on controls for these criteria pollutants. The VOC collection and control systems meets the criteria for inherent process equipment, and as such is not a control devices as defined above under this subpart. Therefore, these permit units are not subject to CAM for SOx and VOC.

g. C-311-122-9, -123-9, -124-9, -125-9, -126-9, -127-9, and -128-9: Fixed Roof Petroleum Storage Tanks Served By Shared Vapor Recovery System

NOx, SOx, PM_{10}, CO, and VOC:

These permit units do not have emissions limits for NOx, SOx, PM_{10}, CO, and VOC. Therefore, these permit units not subject to CAM for any criteria pollutants.

h. C-311-129-11: Fixed Roof Petroleum Storage Tank Served By Shared Vapor Recovery System including Shared Casing Collection System for Permit Unit C-311-112 and Tank Permit Units C-311-122, -123, -124, -125, -126, -127, -128 and -129

NOx, SOx, PM_{10}, and CO:

This permit unit does not have emissions limits for NOx, SOx, PM_{10}, and CO. Therefore, it is not subject to CAM for these criteria pollutants.

VOC:

This permit unit has emissions limits for VOC but does not have add-on controls for this criteria pollutant. The vapor recovery system serving storage tanks and TEOR system is a collection system that meets the criteria for inherent process equipment, and as such is not a control device as defined under this subpart. Therefore, it is not subject to CAM for VOC.

i. C-311-146-24, -147-15, -150-15, -163-15, -164-15, -165-15, -166-15, -167-15, -168-15, -169-15, -170-15, -177-18, -196-15, -197-15, -198-15, -236-9, -266-2, -267-7, -268-3, 269-1, -270-1, and -271-3: Fixed Roof Crude Oil Storage Tanks, Drain Tank, Oil Cleaning Plants Served By Shared Vapor Recovery System

NOx, SOx, PM_{10}, and CO:

These permit units do not have emissions limits for NOx, SOx, PM_{10}, and CO. Therefore, these permit units not subject to CAM for NOx, SOx, PM_{10}, and CO.

VOC:

These permit units have emissions limits for VOC but they do not have add-on controls for this criteria pollutant. The vapor control system serving oil storage tank is a collection system that meets the criteria for inherent process equipment, and as such is not a control devices as defined under this subpart. Therefore, these permit units are not subject to CAM for VOC.

j. C-311-180-4, -181-4, -182-4, -215-4, -216-4, -217-4, -219-4, -220-4, -221-4, -222-7, -223-5, -227-4, -232-3, -233-3, and -234-3: Fixed Roof Petroleum Storage Tanks

NOx, SOx, PM_{10}, and CO:

These permit units do not have emissions limits for NOx, SOx, PM_{10}, and CO. Therefore, these permit units are not subject to CAM for NOx, SOx, PM_{10}, and CO.

VOC:

These permit units have emissions limits for VOC but they do not have add-on controls for this criteria pollutant. Therefore, these permit units are not subject to CAM for VOC.

k. C-311-205-4: Open-Vent Cyclic Wells

NOx, SOx, PM_{10}, CO, and VOC:

This permit unit does not have emissions limits for NOx, SOx, PM_{10}, CO, and VOC. Therefore, it is not subject to CAM for any criteria pollutant.

l. C-311-227-4: Gasoline Dispensing Operation with one 2,000 Gallon Aboveground Storage Tank Served By Phase I and Phase II Vapor Recovery System

NOx, SOx, PM_{10}, CO, and VOC:

These permit units do not have emissions limits for NOx, SOx, PM_{10}, CO, and VOC. Therefore, it is not subject to CAM for these criteria pollutants.

m. C-311-235-3, -238-4, -239-3, and -253-2: Diesel-Fired Emergency IC Engines Powering Electrical Generators

NOx, SOx, PM_{10}, CO, and VOC:

These permit units have emissions limits for NOx, SOx, PM_{10}, CO, and VOC but they do not have add-on controls for these criteria pollutants. Therefore, these permit units are not subject to CAM.

n. C-311-240-4 and -265-2: Pressure Vessels Vented To TEOR Operation C-311-79, or Vapor Control System

NOx, SOx, PM_{10}, and CO:

These permit units do not have emissions limits for NOx, SOx, PM_{10}, and CO. Therefore, these permit units are not subject to CAM.

VOC:

These permit units have emissions limits for VOC but does not have add-on controls for this criteria pollutant. The vapor recovery system serving and TEOR system are collection systems that meet the criteria for inherent process equipment, and as such are not a control device as defined under this subpart. Therefore, these permit units are not subject to CAM for VOC.

L. 40 CFR Part 82, Subpart B - Servicing of Motor Vehicle Air Conditioners

The purpose of 40 CFR Part 82 Subpart B is to implement section 609 of the Clean Air Act, as amended regarding the servicing of motor vehicle air conditioners (MVACs), and to implement section 608 of the Clean Air Act regarding certain servicing, maintenance, repair and disposal of air conditioners in MVACs and MVAC-like appliances.

These regulations apply to any person performing service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner.

The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed further in this evaluation.

Draft Permit	Permit Condition
C-311-0-4	28

M. 40 CFR Part 82, Subpart F - Recycling and Emission Reduction

The purpose of 40 CFR Part 82 Subpart F is to reduce emissions of class I and class II refrigerants and their substitutes to the lowest achievable level by maximizing the recapture and recycling of such refrigerants during the service, maintenance, repair, and disposal of appliances and restricting the sale of refrigerants consisting in whole or in part of a class I and class II ODS in accordance with Title VI of the Clean Air Act.

These regulations apply to any person servicing, maintaining, or repairing appliances. This subpart also applies to persons disposing of appliances, including small appliances and motor vehicle air conditioners. In addition, this subpart applies to refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturer of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Draft Permit	Permit Condition
C-311-0-4	27

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V Permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

The applicant does not propose to use any model general permit templates.

B. Requirements not Addressed by Model General Permit Templates

The applicant is not requesting any new permit shield within this Title V renewal project.

C. Obsolete Permit Shields From Existing Permit Requirements

The permit shield is obsolete for the District Rules that have been amended since the date specified in the permit shield on the current permit.

The existing permits have permit shields for the previous version of District Rules 4403, 4621, 4622, 4623, 4624 and 4661; therefore, permit shields are no longer valid and will be removed from the permit requirements.

The permit conditions with obsolete permit shields have been removed from the draft permits. However, the permit condition has been added to keep the permit shields on existing permits that have dates specifying the latest version of the rules.

Draft Permits	Existing Conditions Removed from Current Permits	New Condition Added to Draft Permits
C-311-122-9, -123-9 and -124-9	40 and 42	41
C-311-125-9, -126-9, -127-9 and -128-9	41 and 43	42
C-311-146-24, -147-15, -150-15, -165-15, -167-15 to -170-15, -196-15 and -198-15	50	50
C-311-163-15, -164-15, -177-18 and -236-9	51	51
C-311-166-15	47	47
C-311-227-4	29 and 30	29

X. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XI. PERMIT CONDITIONS

See Attachment A for the Draft Renewed Title V Operating Permit.

XII. ATTACHMENTS

A. Draft Renewal Title V Operating Permit
B. Previous Title V Operating Permit
C. Detailed Facility List

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley
Air Pollution Control District

FACILITY: C-311-0-4 **EXPIRATION DATE:** 12/31/2016

DRAFT

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit

30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit

31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit

32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit

33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit

35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

42. Facility shall abide by all applicable requirements of 40 CFR Part 68. [40 CFR Part 68] Federally Enforceable Through Title V Permit

43. The reporting period for the Report of Required Monitoring and the Compliance Certification Report begin on October 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-13-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

DRAFT

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT EMISSIONS UNIT CONSISTING OF 86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-105, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A STRUTHERS WASTE HEAT RECOVERY STEAM GENERATOR #SG-205, WITH A 36.4 MMBTU/HR COEN DUCT BURNER

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4703] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4703 and all other applicable District regulations. [District Rule 4703] Federally Enforceable Through Title V Permit
4. {2256} Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
5. The Owner/Operator shall maintain a separate fuel meter to the turbine and a fuel meter to the duct burners. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Natural gas consumption by the cogeneration system (turbine and duct burner) shall not exceed 1,812,000 scf/day. Natural gas consumption by the cogeneration system shall not exceed 654 million scf/year. [District Rule 2201]
7. Emissions from the cogeneration system shall not exceed any of the following limits: 233.7 lb-NOx/day, 3.6 lb-SOx/day, 47.1 lb-PM10/day, 257.3 lb-CO/day, or 47.1 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The owner or operator shall not operate the gas turbine under load conditions, excluding the thermal stabilization period or reduced load period, which results in the measured NOx emissions concentration exceeding 35 ppmv @ 15% O2. [40 CFR 60.332(a)(1), (a)(2) and District Rules 2201 and 4703, 5.1.2.1] Federally Enforceable Through Title V Permit
9. CO emissions from the cogeneration system with the duct burner firing shall not exceed 53 ppmv CO @ 15% O2 or 0.119 lb-CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
10. CO emissions from the cogeneration system without duct burner firing shall not exceed 63 ppmv CO @ 15% O2 or 0.142 lb CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
11. Emissions from the cogeneration system (with or without duct burner firing) shall not exceed any of the following limits: 0.002 lb-SOx/MMBtu, 0.026 lb-PM10/MMBtu, or 0.026 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Reduced Load Period shall be defined as the time during which the gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate, not exceeding one hour. [District Rule 4703, 3.19] Federally Enforceable Through Title V Permit

13. Thermal Stabilization Period shall be defined as the startup or shutdown, as defined in 40 CFR 60.2, time during which the exhaust gas is not within the normal operating temperature range, not to exceed two hours per startup or shutdown event. [District Rule 4703, 3.25] Federally Enforceable Through Title V Permit

14. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit

15. The sulfur fuel content of each fuel source shall be: (i) documented in a valid purchase contract, a supplier certification, a tariff sheet or transportation contract or (ii) monitored weekly using ASTM Methods D4084, D5504, D6228, or Gas Processors Association Standard 2377, or double GC for H2S and mercaptans. If the sulfur fuel content is less than 1.0 gr/100 scf for eight consecutive weeks, then the monitoring frequency shall be every 6 months. If any six-month monitoring tests result in a sulfur fuel content exceedance, weekly monitoring shall resume. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit

16. Performance testing shall be conducted annually to measure NOx and CO emissions concentrations using the following test methods: EPA Methods 7E or 20 for NOx emissions, EPA Methods 10 or 10B for CO emissions, EPA Methods 3, 3A, or 20 for Oxygen content of the exhaust gas. The test will be comprised of three test runs performed at the highest physically achievable load of the gas turbine. The measured NOx concentrations shall be averaged over a three hour period, using consecutive 15-minute sampling periods. [40 CFR60.335(a), (b)(2) and District Rule 4703, 5.1, 6.3.1, 6.3.2, and 6.4] Federally Enforceable Through Title V Permit

17. Any gas turbine with an intermittently operated auxiliary burner shall demonstrate compliance with the auxiliary burner both on and off. Source testing shall not be required with the duct burner on if it has not been in operation during the previous 12 months, i.e. the duct burner need not be started to solely perform source testing. Source testing shall not be required with the duct burner off if it has been in continuous operation during the previous 12 months, i.e. the duct burner need not be shut-down solely to perform source testing. Source testing shall be performed within 60 days of startup or shutdown of the duct burner unless source testing of the duct burner has been performed in the previous 12 months. [40 CFR 60.335(b) and District Rule 4703, 6.3.3] Federally Enforceable Through Title V Permit

18. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

19. The owner or operator shall be required to conform to the sampling facilities and testing procedures described in Rule 1081 (as amended 12/16/93), Sections 3.0 and 6.1. [District Rule1081] Federally Enforceable Through Title V Permit

20. The District must be notified 30 days prior to any performance testing and a test plan shall be submitted for approval 15 days prior to such testing. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Performance testing shall be witnessed or authorized by District personnel. Test results must be submitted to the District within 60 days of performance testing. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The owner or operator shall operate and maintain in calibration a system which continuously measures and records: control system operating parameters, elapsed time of operation, the fuel consumption and the ratio of water to fuel being fired in the turbine. [40 CFR 60.334(a) and District Rule 4703, 6.2.2] Federally Enforceable Through Title V Permit

23. The owner or operator shall develop and keep on-site a parameter monitoring plan which includes the procedures used to document the proper operation of the NOx emissions controls (water injection). This plan shall include the parameter(s) monitored, such as the water-to-fuel ratio, and the acceptable range(s) of the parameter(s) as well as the basis for designating the parameter(s) and acceptable range(s). Any supplemental data such as engineering analyses, design specifications, manufacturers recommendations and other relevant information shall be included in the monitoring plan. [40 CFR 60.334(g)] Federally Enforceable Through Title V Permit

24. The water to fuel ratio shall not be less than 0.45 on a weight basis. [District Rule 4703, 6.2.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The owner or operator shall submit a semi-annual excess NOx emissions and monitor downtime report to the APCO. Excess emissions shall be reported for all periods of operation, including startup, shutdown and malfunction. The report, post marked by the 30th day following the end of every other calendar quarter, shall include the following: Time intervals, average steam or water-to-fuel ratio, turbine load, nature and cause of excess emissions (if known), and corrective actions taken and preventative measures adopted. [40 CFR 60.334(j), (j)(5) and District Rule 2520, 9.3.2)] Federally Enforceable Through Title V Permit

26. Excess emissions shall be defined as any operating hour for which the steam or water to fuel ratio, as measured by the continuous monitoring system, falls below the established steam or water to fuel ratio. Any operating hour in which no steam or water is injected into the turbine shall also be considered as excess emissions. [40 CR 60.334(j)(1)(i)(A)] Federally Enforceable Through Title V Permit

27. Monitor downtime shall be any operating hour in which the water or steam is injected into the turbine, but essential parametric data needed to determine the steam or water to fuel ratio are unavailable or invalid. [40 CFR 60.334(j)(1)(i)(B)] Federally Enforceable Through Title V Permit

28. Fuel consumption and the water-to-fuel ratio shall be monitored continuously with a system that is accurate to within 5 percent. [District Rule 2201] Federally Enforceable Through Title V Permit

29. The cogeneration system shall be equipped with a meter recording the total elapsed operating time. [District Rule 2201] Federally Enforceable Through Title V Permit

30. Permittee shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100] Federally Enforceable Through Title V Permit

31. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100] Federally Enforceable Through Title V Permit

32. If the water injection system is inoperative when the turbine is running, the operator shall follow procedures pursuant to District Rule 1100 (Equipment Breakdown). [District Rule 1100] Federally Enforceable Through Title V Permit

33. {741} The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

34. If the turbine is fired on PUC-regulated natural gas, then the operator shall maintain a log describing the source of natural gas and quantity used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

35. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments and emissions measurements. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

36. The owner or operator shall maintain a record of the cumulative rolling 12 month fuel usage for each turbine. The record shall be updated at the end of each calendar month. [District Rule 2201] Federally Enforceable Through Title V Permit

37. {787} Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis, the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332(a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

38. {2271} The owner or operator of a stationary gas turbine system shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: 40 CFR 60.332(a)(1), (a)(2), 60.333 (b), (g), (h)(3), (j), (j)(1)(i)(A), (j)(1)(i)(b), and (j)(5); 60.335(a), (b)(2), (b)(3); and District Rule 4703 (as amended 4/25/02), Sections 5.1.2.1, 5.2, 6.2.2, 6.4, and 6.2.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 1081(as amended 12/16/93), Section 3.0, 6.0, 7.1, 7.2, 7.3 and Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-15-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT EMISSIONS UNIT CONSISTING OF 86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-106, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A STRUTHERS WASTE HEAT RECOVERY STEAM GENERATOR #SG-206 WITH A 36.4 MMBTU/HR COEN DUCT BURNER

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4703] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4703 and all other applicable District regulations. [District Rule 4703] Federally Enforceable Through Title V Permit
4. {2256} Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
5. The Owner/Operator shall maintain a separate fuel meter to the turbine and a fuel meter to the duct burners. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Natural gas consumption by the cogeneration system (turbine and duct burner) shall not exceed 1,812,000 scf/day. Natural gas consumption by the cogeneration system shall not exceed 654 million scf/year. [District Rule 2201]
7. Emissions from the cogeneration system shall not exceed any of the following limits: 233.7 lb-NOx/day, 3.6 lb-SOx/day, 47.1 lb-PM10/day, 257.3 lb-CO/day, or 47.1 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The owner or operator shall not operate the gas turbine under load conditions, excluding the thermal stabilization period or reduced load period, which results in the measured NOx emissions concentration exceeding 35 ppmv @ 15% O2. [40 CFR 60.332(a)(1), (a)(2) and District Rules 2201 and 4703, 5.1.2.1] Federally Enforceable Through Title V Permit
9. CO emissions from the cogeneration system with the duct burner firing shall not exceed 53 ppmv CO @ 15% O2 or 0.119 lb-CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
10. CO emissions from the cogeneration system without duct burner firing shall not exceed 63 ppmv CO @ 15% O2 or 0.142 lb CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
11. Emissions from the cogeneration system (with or without duct burner firing) shall not exceed any of the following limits: 0.002 lb-SOx/MMBtu, 0.026 lb-PM10/MMBtu, or 0.026 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. Reduced Load Period shall be defined as the time during which the gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate, not exceeding one hour. [District Rule 4703, 3.19] Federally Enforceable Through Title V Permit

13. Thermal Stabilization Period shall be defined as the startup or shutdown, as defined in 40 CFR 60.2, time during which the exhaust gas is not within the normal operating temperature range, not to exceed two hours per startup or shutdown event. [District Rule 4703, 3.25] Federally Enforceable Through Title V Permit

14. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit

15. The sulfur fuel content of each fuel source shall be: (i) documented in a valid purchase contract, a supplier certification, a tariff sheet or transportation contract or (ii) monitored weekly using ASTM Methods D4084, D5504, D6228, or Gas Processors Association Standard 2377, or double GC for H2S and mercaptans. If the sulfur fuel content is less than 1.0 gr/100 scf for eight consecutive weeks, then the monitoring frequency shall be every 6 months. If any six-month monitoring tests result in a sulfur fuel content exceedance, weekly monitoring shall resume. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit

16. Performance testing shall be conducted annually to measure NOx and CO emissions concentrations using the following test methods: EPA Methods 7E or 20 for NOx emissions, EPA Methods 10 or 10B for CO emissions, EPA Methods 3, 3A, or 20 for Oxygen content of the exhaust gas. The test will be comprised of three test runs performed at the highest physically achievable load of the gas turbine. The measured NOx concentrations shall be averaged over a three hour period, using consecutive 15-minute sampling periods. [40 CFR60.335(a), (b)(2) and District Rule 4703, 5.1, 6.3.1, 6.3.2, and 6.4] Federally Enforceable Through Title V Permit

17. Any gas turbine with an intermittently operated auxiliary burner shall demonstrate compliance with the auxiliary burner both on and off. Source testing shall not be required with the duct burner on if it has not been in operation during the previous 12 months, i.e. the duct burner need not be started to solely perform source testing. Source testing shall not be required with the duct burner off if it has been in continuous operation during the previous 12 months, i.e. the duct burner need not be shut-down solely to perform source testing. Source testing shall be performed within 60 days of startup or shutdown of the duct burner unless source testing of the duct burner has been performed in the previous 12 months. [40 CFR 60.335(b) and District Rule 4703, 6.3.3] Federally Enforceable Through Title V Permit

18. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

19. The owner or operator shall be required to conform to the sampling facilities and testing procedures described in Rule 1081 (as amended 12/16/93), Sections 3.0 and 6.1. [District Rule1081] Federally Enforceable Through Title V Permit

20. The District must be notified 30 days prior to any performance testing and a test plan shall be submitted for approval 15 days prior to such testing. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Performance testing shall be witnessed or authorized by District personnel. Test results must be submitted to the District within 60 days of performance testing. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The owner or operator shall operate and maintain in calibration a system which continuously measures and records: control system operating parameters, elapsed time of operation, the fuel consumption and the ratio of water to fuel being fired in the turbine. [40 CFR 60.334(a) and District Rule 4703, 6.2.2] Federally Enforceable Through Title V Permit

23. The owner or operator shall develop and keep on-site a parameter monitoring plan which includes the procedures used to document the proper operation of the NOx emissions controls (water injection). This plan shall include the parameter(s) monitored, such as the water-to-fuel ratio, and the acceptable range(s) of the parameter(s) as well as the basis for designating the parameter(s) and acceptable range(s). Any supplemental data such as engineering analyses, design specifications, manufacturers recommendations and other relevant information shall be included in the monitoring plan. [40 CFR 60.334(g)] Federally Enforceable Through Title V Permit

24. The water to fuel ratio shall not be less than 0.45 on a weight basis. [District Rule 4703, 6.2.5] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The owner or operator shall submit a semi-annual excess NOx emissions and monitor downtime report to the APCO. Excess emissions shall be reported for all periods of operation, including startup, shutdown and malfunction. The report, post marked by the 30th day following the end of every other calendar quarter, shall include the following: Time intervals, average steam or water-to-fuel ratio, turbine load, nature and cause of excess emissions (if known), and corrective actions taken and preventative measures adopted. [40 CFR 60.334(j), (j)(5) and District Rule 2520, 9.3.2)] Federally Enforceable Through Title V Permit

26. Excess emissions shall be defined as any operating hour for which the steam or water to fuel ratio, as measured by the continuous monitoring system, falls below the established steam or water to fuel ratio. Any operating hour in which no steam or water is injected into the turbine shall also be considered as excess emissions. [40 CR 60.334(j)(1)(i)(A)] Federally Enforceable Through Title V Permit

27. Monitor downtime shall be any operating hour in which the water or steam is injected into the turbine, but essential parametric data needed to determine the steam or water to fuel ratio are unavailable or invalid. [40 CFR 60.334(j)(1)(i)(B)] Federally Enforceable Through Title V Permit

28. Fuel consumption and the water-to-fuel ratio shall be monitored continuously with a system that is accurate to within 5 percent. [District Rule 2201] Federally Enforceable Through Title V Permit

29. The cogeneration system shall be equipped with a meter recording the total elapsed operating time. [District Rule 2201] Federally Enforceable Through Title V Permit

30. Permittee shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100] Federally Enforceable Through Title V Permit

31. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100] Federally Enforceable Through Title V Permit

32. If the water injection system is inoperative when the turbine is running, the operator shall follow procedures pursuant to District Rule 1100 (Equipment Breakdown). [District Rule 1100] Federally Enforceable Through Title V Permit

33. {741} The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

34. If the turbine is fired on PUC-regulated natural gas, then the operator shall maintain a log describing the source of natural gas and quantity used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

35. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments and emissions measurements. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

36. The owner or operator shall maintain a record of the cumulative rolling 12 month fuel usage for each turbine. The record shall be updated at the end of each calendar month. [District Rule 2201] Federally Enforceable Through Title V Permit

37. {787} Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis, the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332(a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

38. {2271} The owner or operator of a stationary gas turbine system shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: 40 CFR 60.332(a)(1), (a)(2), 60.333 (b), (g), (h)(3), (j), (j)(1)(i)(A), (j)(1)(i)(b), and (j)(5); 60.335(a), (b)(2), (b)(3); and District Rule 4703 (as amended 4/25/02), Sections 5.1.2.1, 5.2, 6.2.2, 6.4, and 6.2.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 1081(as amended 12/16/93), Section 3.0, 6.0, 7.1, 7.2, 7.3 and Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-19-25 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-03 THERMOTICS STEAM GENERATOR, MODEL 5G-50-NDS-15, WITH NORTH AMERICAN GAS BURNER, MODEL 6131G-LO-NOX WITH FLUE GAS RECIRCULATION AND O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. This unit shall be fired on natural gas, or a blend of natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
7. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201 and 4301] Federally Enforceable Through Title V Permit
10. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301 and 2520] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2, equivalent to 0.017 lb-NOx/MMBtu or 25 ppmvd CO @ 3% O2 equivalent to 0.0185 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520 and 4301] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

26. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel sulfur testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by test methods and procedures outlined in this permit. [District Rules 2520, 4305, and 4351] Federally Enforceable Through Title V Permit

30. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-20-23 **EXPIRATION DATE:** 12/31/2016

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-04 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR WITH A NORTH AMERICAN GLE BURNER WITH FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.004 lb-PM10/MMBtu or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,332 lb-NOx/yr, 51.9 lb-CO/day, or 16,939 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

12. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

13. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. Well casing gas shall be sampled monthly from the gas line down stream from the point where the casing gas from all 4 casing collection systems is connected together and upstream from the point where the well casing gas is fed to the steam generators. The gas sample shall be analyzed by the laboratory for total sulfur and the results shall be given in grain/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Permittee shall maintain monthly records of the total amount of well casing gas consumed by the entire bank of steam generators (in MMscf), along with the date and time of the measurement. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall maintain monthly records of the total amount of PUC grade gas consumed by the entire bank of steam generators (in MMscf), along with the date and time of the measurement. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Natural gas sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source or natural gas shall be tested for sulfur content and higher heating value (hhv) monthly. Casing gas shall be tested for sulfur content and higher heating value (hhv) not less than monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

31. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

32. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-21-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14

DRAFT

EQUIPMENT DESCRIPTION:
58.5 MBTU/HR SG 13-05 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.004 lb-PM10/MMBtu or 0.08 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,332 lb-NOx/yr, 51.9 lb-CO/day, or 16,939 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

12. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

13. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

33. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-22-25 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-06 THERMOTICS STEAM GENERATOR, MODEL 5G-50-NDS-15, WITH A NORTH AMERICAN GLE LOW NOX BURNER, FLUE GAS RECIRCULATION SYSTEM, AND O2 CONTROLLER

DRAFT

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. This unit shall be fired on natural gas, or a blend of natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
7. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201 and 4301] Federally Enforceable Through Title V Permit
10. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301 and 2520] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2, equivalent to 0.017 lb-NOx/MMBtu or 25 ppmvd CO @ 3% O2 equivalent to 0.0185 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520 and 4301] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

26. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel sulfur testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by test methods and procedures outlined in this permit. [District Rules 2520, 4305, and 4351] Federally Enforceable Through Title V Permit

30. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-23-22 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-07 THERMOTICS STEAM GENERATOR, MODEL 5G-50-NDS-15, WITH A NORTH AMERICAN GLE LOW-NOX BURNER WITH FLUE GAS RECIRCULATION AND O2 CONTROLLER

DRAFT

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. This unit shall be fired on natural gas, or a blend of natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
7. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201 and 4301] Federally Enforceable Through Title V Permit
10. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301 and 2520] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2, equivalent to 0.017 lb-NOx/MMBtu or 25 ppmvd CO @ 3% O2 equivalent to 0.0185 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

14. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520 and 4301] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

26. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel sulfur testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by test methods and procedures outlined in this permit. [District Rules 2520, 4305, and 4351] Federally Enforceable Through Title V Permit

30. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-25-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-09 NATURAL/LPG/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Combined natural , well casing, and TVR gas consumption shall not exceed either of the following limits: 1,404 million MMBtu/day or 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. LPG consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed any of the following limits: 0.045 lb-PM10/MMBtu or 0.009 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,912 lb-NOx/yr, 51.9 lb-CO/day, or 16,095 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
14. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit
21. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

32. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

33. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

34. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-27-19 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR STRUTHERS THERMOFLOOD STEAM GENERATOR #13-11, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER, EQUIPPED WITH FLUE GAS RECIRCULATION AND AN OXYGEN CONTROLLER

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, or a blend of PUC-quality natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day nor 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.00285 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.009 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,830 lb-NOx/yr, 51.9 lb-CO/day, and 16,084 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

17. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
27. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-28-22 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-12 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, EQUIPPED WITH A NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.008 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-30-20 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 13-14 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN BURNER, AND A FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-36-25

EXPIRATION DATE: 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG-25-15 STRUTHERS THERMOFLOOD, MODEL OH-50-ND-16XAM STEAM GENERATOR WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE 25D NEPTUNE AIRPOL CAUSTIC SCRUBBER (SHARED WITH UNITS -37, -38, -39, -40, AND -41) WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

DRAFT

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total LPG, casing gas, waste gas, and natural gas consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Scrubber liquor pH shall be maintained between 6.5 and 8.0. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Scrubber tray packing flowrate shall be operated at a minimum of 700 gallons/minute. [District Rule 2201]
16. Quench flowrate shall be operated at 145 to 185 gallons/minute. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Except during start-up and shutdown periods, emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.014 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.0085 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,830 lb-NOx/year, 49.1 lb-CO/day, or 16,095 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
25. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

30. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

31. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
39. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. Daily records of the tray packing flowrate and the quench flowrate shall be maintained, retained on the premises for a period of at least five years, and made available for District inspection upon request. [District Rules 1070 and 2520, 9.5.2] Federally Enforceable Through Title V Permit
41. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
42. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
43. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
45. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
46. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
47. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-37-30 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-16 STRUTHERS THERMOFLOOD MODEL OH-50-ND-16XAM STEAM GENERATOR WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total gas consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Except during start-up and shutdown periods, emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.014 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,240 lb-NOx/year, 85.6 lb-CO/day, or 16,939 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-38-36 **EXPIRATION DATE:** 12/31/2016

SECTION: 25D **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-17 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 14 ppmvd NOx @ 3% O2, or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2, or 0.037 lb-CO/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,332 lb-NOx/yr, 51.9 lb-CO/day, or 16,939 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-39-27 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG-25-18 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total gas consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Except during startup and shutdown, emissions from this unit shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.0520 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu, 0.0520 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, nor 0.008 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

20. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

38. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

42. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-40-27 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-19 NATURAL GAS STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Emissions from this unit shall not exceed any of the following limits: 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

15. Except during startup and shutdown, emissions from this unit shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, nor 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-41-26 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-20 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR), SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total LPG, casing gas, waste gas, and natural gas consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Emissions from this unit shall not exceed any of the following limits: 0.052 lb-SOx/MMBtu, 0.044 lb-PM10/MMBtu, or 0.0085 lb-VOC/MMBtu. [District Rules 2201 and 4320]

15. Except during startup and shutdown, emissions from this unit shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.044 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.0085 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320]

16. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.044 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, nor 0.0085 lb-VOC/MMBtu. [District Rule 2201]

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-42-21

EXPIRATION DATE: 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-21 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

DRAFT

PERMIT UNIT REQUIREMENTS

1. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
5. This unit shall be fired exclusively on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
7. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
11. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day or 7390 lb-NOx/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

17. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C ; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

20. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

33. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-43-19 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-22 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16AXM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

DRAFT

PERMIT UNIT REQUIREMENTS

1. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
5. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
9. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
10. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,825 lb-NOx/yr, 51.9 lb-CO/day, and 16,084 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

16. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C ; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Operator shall provide an annual fuel analysis to the District. [District Rule 4320] Federally Enforceable Through Title V Permit

19. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

32. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

34. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-45-19 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-24 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16AXM, WITH FLUE GAS RECIRCULATION (FGR)

DRAFT

PERMIT UNIT REQUIREMENTS

1. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
5. This unit shall be fired exclusively on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
7. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
11. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,825 lb-NOx/yr, 51.9 lb-CO/day, and 16,084 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

14. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

17. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C ; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

20. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

33. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992) and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-46-19

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 25-25 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN 4131-G-LNX BURNER WITH FLUE GAS

PERMIT UNIT REQUIREMENTS

1. Operation of the unit is not authorized until modifications are made to comply with District Rules as authorized by an Authority to Construct. [District Rule 2010] Federally Enforceable Through Title V Permit
2. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
3. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081] Federally Enforceable Through Title V Permit
5. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of a compliant DEU. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
7. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
8. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
10. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6B; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
13. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
14. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
15. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5; and 2520, 9.4.2] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
18. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
19. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
20. The flue gas recirculation system shall be operated in accordance with the manufacturer's directions whenever the steam generator is operating. [District Rule 2201] Federally Enforceable Through Title V Permit
21. This unit shall be fired exclusively with natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Natural gas or LPG consumption shall not exceed 1404 MMBtu/day nor 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
23. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
24. Emissions shall not exceed any of the following limits: NOx - 0.036 lb/MMBtu, SOx - 0.052 lb/MMBtu, CO - 0.035 lb/MMBtu, and PM-10 - 0.045 lb/MMBtu. [District Rules 2201 and 4305] Federally Enforceable Through Title V Permit
25. Emissions shall not exceed any of the following limits: NOx - 50.5 lb/day, SOx - 72.96 lb/day, CO - 49.0 lb/day, and PM10 - 63.12 lb/day. [District Rules 2201 and 4305] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. This unit shall be tested for compliance with NOx emissions limit not less than once every 12 months. Source testing shall not be required if the unit did not operate during the previous 12 month period. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every 36 months. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

29. The stack concentration of NOx (as NO2), CO, and O2 shall be measured at least on a monthly basis using District approved portable analyzers. Monitoring shall not be required if the unit is not in operation during any given month, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the steam generator unless monitoring has been performed within the last month. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

30. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2, and the O2 concentration. The records must also include a description of any corrective action taken to maintain the emissions within the acceptable range and shall identify the months of non-operation for any unit to validate extended monitoring frequencies. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

31. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the allowable emissions rate, the permittee shall notify the District and take corrective action within one (1) hour after detection. If the portable analyzer readings continue to exceed the allowable emissions rate, the permittee shall conduct an emissions test within 60 days, utilizing District-approved test methods, to demonstrate compliance with the applicable emissions limits. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

32. The portable analyzer shall be calibrated as recommended by the manufacturer. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 6 months prior to the date the stack concentrations are measured and recorded. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

33. Concentration measurements shall not be taken until the sample acquisition probe has been exposed to the stack gas for at least 150% of the response time. Measurements shall be taken in triplicate. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

34. If water vapor is not removed prior to measurement, the absolute humidity in the gas stream must be determined so that the gas concentrations may be reported on a dry basis. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

35. If water vapor creates an interference with the measurement of any component, then the water vapor must be removed from the gas stream prior to concentration measurements. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

36. Permittee shall record daily natural gas and propane consumption. Records shall be provided to the District upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Natural gas or LPG sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source; or natural gas or LPG shall be tested for sulfur content and higher heating value (hhv) monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

39. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Source testing shall be performed for NOx (ppmv) according to EPA method 7E (or ARB Method 100) and EPA Method 10 (or ARB Method 100) for CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

42. Annual test results to the District from unit(s) representing a group of units may be used to measure NOx emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

43. The following conditions must be met for representative unit(s) to be used to test for NOx limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

44. All units in a group for which representative units are source for NOx emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). Records shall be maintained for the each unit of the group including all preventative and corrective maintenance work done. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

45. All units in a group for which representative units are source tested for NOx emissions for this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

46. The number of representative units source tested for NOx emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-47-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 25-26 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16-XAM, WITH A NORTH AMERICAN BURNER, MODEL 4131-G-LNX, AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. This permit unit shall not be operated unless the owner or operator applies to modify the Title V permit to address the requirements of District Rule 2520, section 9.0 for this permit unit. [District Rule 2520, 9.0] Federally Enforceable Through Title V Permit
2. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
3. The emissions shall not exceed 30 ppm NOx (0.036 lb-NOx/MMBtu) @ 3% O2. [District Rule 4305]
4. No modification to this unit shall be performed without an Authority to Construct for that modification(s), except for changes specified in condition 5. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
5. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305] Federally Enforceable Through Title V Permit
6. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081] Federally Enforceable Through Title V Permit
7. Natural gas consumption shall not exceed 1.34 million scf/day or 414 million scf/year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively with natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
9. LPG consumption shall not exceed 1,404 MMBtu/day nor 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The flue gas recirculation system shall be operated whenever the generator is in use. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions shall not exceed the following limits: CO - 0.034 lb/MMBtu, SOx - 0.052 lb/MMBtu, or PM10 - 0.045 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions shall not exceed the following limits: NOx - 50.5 lb/day, SOx - 72.96 lb/day, or PM10 - 63.12 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall record natural gas and propane consumption. Records shall be retained for at least two years and provided to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

14. This unit shall be tested for compliance with NOx emissions limit not less than once every 12 months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. [District Rule 4305] Federally Enforceable Through Title V Permit

15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-48-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-27, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Total fuel consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum NOx emissions from the steam generator, including start-up and shutdown, shall not exceed 46.3 lb-NOx/day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using test methods listed on this permit. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by a third party supplier or tested in accordance with procedures outlined in this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx and CO emissions from this unit shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992) and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-49-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-28, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Total fuel consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum NOx emissions from the steam generator, including start-up and shutdown, shall not exceed 46.3 lb-NOx/day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using test methods listed on this permit. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by a third party supplier or tested in accordance with procedures outlined in this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx and CO emissions from this unit shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-50-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-29, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Total fuel consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum NOx emissions from the steam generator, including start-up and shutdown, shall not exceed 46.3 lb-NOx/day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using test methods listed on this permit. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by a third party supplier or tested in accordance with procedures outlined in this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx and CO emissions from this unit shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-51-21

EXPIRATION DATE: 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 6-31 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN 4131-G-LNX BURNER WITH FLUE GAS RECIRCULATION

DRAFT

PERMIT UNIT REQUIREMENTS

1. {4558} Operation of the unit is not authorized until modifications are made to comply with District Rules as authorized by an Authority to Construct. [District Rule 2010]
2. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
3. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081] Federally Enforceable Through Title V Permit
5. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of a compliant DEU. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
7. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
8. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
10. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6B; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
13. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
14. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
15. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
18. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
19. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
20. The flue gas recirculation system shall be operated in accordance with the manufacturer's directions whenever the steam generator is operating. [District Rule 2201] Federally Enforceable Through Title V Permit
21. This unit shall be fired exclusively with natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Natural gas or LPG consumption shall not exceed 1,404 MMBtu/day nor 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
23. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
24. Emissions shall not exceed any of the following limits: NO2 - 50.5 lb/day, SO2 - 4.56 lb/day, PM10 - 9.48 lb/day, CO - 48.0 lb/day, and VOC (NMHC) - 12.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
25. Emissions shall not exceed any of the following limits: NO2 - 0.036 lb/MMBtu, SO2 - 0.003 lb/MMBtu, VOC - 0.003 lb/MMBtu, and CO - 0.035 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. This unit shall be tested for compliance with NOx emissions limit not less than once every 12 months. Source testing shall not be required if the unit did not operate during the previous 12 month period. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every 36 months. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

29. The stack concentration of NOx (as NO2), CO, and O2 shall be measured at least on a monthly basis using District approved portable analyzers. Monitoring shall not be required if the unit is not in operation during any given month, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the steam generator unless monitoring has been performed within the last month. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

30. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2, and the O2 concentration. The records must also include a description of any corrective action taken to maintain the emissions within the acceptable range and shall identify the months of non-operation for any unit to validate extended monitoring frequencies. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

31. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the allowable emissions rate, the permittee shall notify the District and take corrective action within one (1) hour after detection. If the portable analyzer readings continue to exceed the allowable emissions rate, the permittee shall conduct an emissions test within 60 days, utilizing District-approved test methods, to demonstrate compliance with the applicable emissions limits. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

32. The portable analyzer shall be calibrated as recommended by the manufacturer. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 6 months prior to the date the stack concentrations are measured and recorded. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

33. Concentration measurements shall not be taken until the sample acquisition probe has been exposed to the stack gas for at least 150% of the response time. Measurements shall be taken in triplicate. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

34. If water vapor is not removed prior to measurement, the absolute humidity in the gas stream must be determined so that the gas concentrations may be reported on a dry basis. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

35. If water vapor creates an interference with the measurement of any component, then the water vapor must be removed from the gas stream prior to concentration measurements. [District Rules 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

36. Permittee shall record daily natural gas and propane consumption. Records shall be provided to the District upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Natural gas or LPG sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source; or natural gas or LPG shall be tested for sulfur content and higher heating value (hhv) monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

39. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Source testing shall be performed for NOx (ppmv) according to EPA method 7E (or ARB Method 100) and EPA Method 10 (or ARB Method 100) for CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

42. Annual test results to the District from unit(s) representing a group of units may be used to measure NOx emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

43. The following conditions must be met for representative unit(s) to be used to test for NOx limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.4.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

44. All units in a group for which representative units are source for NOx emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). Records shall be maintained for the each unit of the group including all preventative and corrective maintenance work done. [District Rules, 9.4.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

45. All units in a group for which representative units are source tested for NOx emissions for this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

46. The number of representative units source tested for NOx emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-52-24

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG STRUTHERS THERMOFLOOD STEAM GENERATOR #6-32, MODEL 0H-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
6. Total fuel consumption of this unit shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in the fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801] Federally Enforceable Through Title V Permit
11. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.005 lb-PM10/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,240 lb-NOx/yr, 51.9 lb-CO/day, and 16,939 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.4.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

22. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

25. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

26. {109} Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]

27. {110} The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

29. Sampling facilities for source testing shall be provided in accordance with the provisions of rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

30. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Natural gas sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source or natural gas shall be tested for sulfur content and higher heating value (hhv) monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

35. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320]

37. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

39. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-53-21 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS THERMOFLOOD STEAM GENERATOR MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER, AND FLUE GAS RECIRCULATION (FGR)

DRAFT

PERMIT UNIT REQUIREMENTS

1. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. This unit shall be fired exclusively with natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
6. Total fuel consumption of this unit shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in the fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801] Federally Enforceable Through Title V Permit
11. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.005 lb-PM10/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,240 lb-NOx/yr, 51.9 lb-CO/day, and 16,939 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.4.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

22. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2, 4305, 6.2.1, and 4351, 6.2.1] Federally Enforceable Through Title V Permit

23. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4320] Federally Enforceable Through Title V Permit

24. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

25. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

26. {109} Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]

27. {110} The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

29. Sampling facilities for source testing shall be provided in accordance with the provisions of rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

30. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Natural gas sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source or natural gas shall be tested for sulfur content and higher heating value (hhv) monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

37. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

39. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-76-22

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 6-38 NATURAL/LPG/TEOR GAS-FIRED STRUTHERS THERMOFLOOD MODEL OH-50-ND-16XAM STEAM GENERATOR WITH A NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.00675 lb-PM10/MMBtu or 0.0085 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,825 lb-NOx/yr, 66.4 lb-CO/day, or 16,084 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

12. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

13. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

33. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-77-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 91 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-2-13D WITH LOW PRESSURE SCRUBBER-SEPARATOR, AIR COOLER AND CONDENSATE COLLECTOR (13D NORTHEAST)

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Sections 13, T20S, R14E and Section 18, T20S R15E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the low pressure scrubber-separator and the air cooler is optional. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, or a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. {1667} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. {1311} The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-78-6 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 149 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-4-13D WITH SCRUBBER, FIN-FAN AIR COOLER AND CONDENSATE COLLECTOR (13D NORTHWEST)

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations Sections 12 and 13, T20S, R14E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the fin-fan air cooler is optional. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, or a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. {1667} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. {1311} The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-79-20 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TEOR OPERATION #CC-1-25D WITH 491 STEAM ENHANCED WELLS WITH TWO 100 HP COMPRESSORS, SEPARATOR, CONDENSATE COLLECTOR AND PIPING FROM TEOR OPERATION #6C-CC-1 (C-311-112) AND PRESSURE VESSEL C-311-240

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Sections 24, 25, and 36, T20S, R14E and Sections 19, 30, T20S, R15E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the 100 hp compressor is optional. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, or a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. {1667} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. {1311} The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-83-22 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20 **RANGE:** 14

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 596 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-3-13D WITH SCRUBBER, FIN-FAN AIR COOLER, COMPRESSOR, AND CONDENSATE COLLECTOR, WITH CLOSED CASING VENTS OR VENTING TO A BALANCED PIPING SYSTEM OR STEAM GENERATORS APPROVED BY DISTRICT FOR TEOR GAS INCINERATION OR DOGGR APPROVED VAPOR DISPOSAL WELL(S) (13D SOUTHWEST)

DRAFT

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Sections 13 and 24, T20S, R14E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the fin-fan air cooler is optional. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, or a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. {1667} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. {1311} The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-84-22 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 6-37 STRUTHERS THERMOFLOOD STEAM GENERATOR MODEL OH5O-ND-16XAM WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

DRAFT

PERMIT UNIT REQUIREMENTS

1. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This unit shall be fired on PUC-quality natural gas, LPG, or a blend of PUC-quality natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
6. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.00675 lb-PM10/MMBtu, or 0.00855 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,390 lb-NOx/yr, 66.4 lb-CO/day, and 16,084 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.4.2 and 4320] Federally Enforceable Through Title V Permit

18. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

19. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

20. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

25. {110} The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

27. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2, 4305, 4306, 4320, and 4351, 6.2.1] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. Natural gas or LPG sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source; or natural gas or LPG shall be tested for sulfur content and higher heating value (hhv) monthly. Casing gas shall be tested for sulfur content and higher heating value (hhv) not less than monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-88-16 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-104, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A RENTECH WASTE HEAT RECOVERY STEAM GENERATOR, WITH A 37 MMBTU/HR JOHN ZINC HAMWORTHY COMBUSTION DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. {2256} Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [District Rules 2201 and 4201, and 40 CFR 60.333(b)] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [District Rule 4703 and 40 CFR 60.335(b)] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081] Federally Enforceable Through Title V Permit

13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081] Federally Enforceable Through Title V Permit

16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, and 40 CFR 60.335(a)] Federally Enforceable Through Title V Permit

17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081] Federally Enforceable Through Title V Permit

18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit

19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. The results of each source test shall be submitted to the District within 60 days of the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, and 40 CFR 60.334(b)(1)] Federally Enforceable Through Title V Permit

22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)] Federally Enforceable Through Title V Permit

23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)] Federally Enforceable Through Title V Permit

24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080] Federally Enforceable Through Title V Permit

25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, and 40 CFR 60.334(b)(1)] Federally Enforceable Through Title V Permit

26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080] Federally Enforceable Through Title V Permit

27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)] Federally Enforceable Through Title V Permit

28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080] Federally Enforceable Through Title V Permit

29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080] Federally Enforceable Through Title V Permit

30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201, and 40 CFR 60.8(d)] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)] Federally Enforceable Through Title V Permit
32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)(1)(iii)(B)] Federally Enforceable Through Title V Permit
33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)] Federally Enforceable Through Title V Permit
34. Should the applicant decide to conduct performance evaluation of CEMS with the initial performance test, a minimum of 9 reference method runs, with a minimum time per run of 21 minutes, at a single load level, between 90 and 100 percent of peak (or the highest physically achievable) load shall be performed. The test data obtained during these runs can be used to demonstrate compliance with the applicable NOx emission limit and to provide reference method data for the RATA of the CEMS. The requirement to test at three additional load levels is waived under this option. [40 CFR 60.335(b)(6)] Federally Enforceable Through Title V Permit
35. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
36. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
37. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
38. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703] Federally Enforceable Through Title V Permit
39. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703] Federally Enforceable Through Title V Permit
40. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703] Federally Enforceable Through Title V Permit
41. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit
42. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703] Federally Enforceable Through Title V Permit

44. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703] Federally Enforceable Through Title V Permit

45. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

46. {741} The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: 40 CFR 60.332(a), 60.335 (a), (b) and (c). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

49. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-93-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-101, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-201, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. {2256} Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [District Rules 2201 and 4201, and 40 CFR 60.333(b)] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [District Rule 4703, and 40 CFR 60.335(b)] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703]
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201]
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201]
9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201]

11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201]

12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081]

13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years thereafter. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081]

16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, and 40 CFR 60.335(a)]

17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081]

18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit

19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, and 40 CFR 60.334(b)(1)]
22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)]
23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)]
24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080]
25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, and 40 CFR 60.334(b)(1)]
26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080]
27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)]
28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080]
29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080]
30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201, and 40 CFR 60.8(d)]
31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)1)(iii)(B)]

33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)]

34. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703]

35. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703]

36. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703]

37. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703]

38. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703]

39. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703]

40. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit

41. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703]

42. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703]

43. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703]

44. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

45. {741} The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: 40 CFR 60.332(a), 60.335 (a), (b) and (c). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-95-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-102, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-202, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. {2256} Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [District Rules 2201 and 4201, and 40 CFR 60.333(b)] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [District Rule 4703 and 40 CFR 60.335(b)] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703]
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201]
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201]
9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201]
11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201]
12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081]
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years thereafter. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081]
16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, and 40 CFR 60.335(a)]
17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081]
18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit
19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, and 40 CFR 60.334(b)(1)]

22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)]

23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)]

24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080]

25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, and 40 CFR 60.334(b)(1)]

26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080]

27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)]

28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080]

29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080]

30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201, and 40 CFR 60.8(d)]

31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)(1)(iii)(B)]

33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)]

34. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703]

35. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703]

36. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703]

37. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703]

38. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703]

39. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703]

40. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit

41. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703]

42. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703]

43. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703]

44. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

45. {741} The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: 40 CFR 60.332(a), 60.335 (a), (b) and (c). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-97-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-103, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-203, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. {2256} Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [District Rules 2201 and 4201, and 40 CFR 60.333(b)] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [District Rule 4703 and 40 CFR 60.335(b)] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703]
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201]
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201]
9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201]
11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201]
12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081]
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years thereafter. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081]
16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, and 40 CFR 60.335(a)]
17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081]
18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit
19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, and 40 CFR 60.334(b)(1)]
22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)]
23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)]
24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080]
25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, and 40 CFR 60.334(b)(1)]
26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080]
27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)]
28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080]
29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080]
30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201, and 40 CFR 60.8(d)]
31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)(1)(iii)(B)]

33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)]

34. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703]

35. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703]

36. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703]

37. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703]

38. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703]

39. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703]

40. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit

41. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703]

42. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703]

43. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703]

44. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

45. {741} The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: 40 CFR 60.332(a), 60.335 (a), (b) and (c). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-105-5

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
118 CLOSED-VENT TEOR WELLS

DRAFT

PERMIT UNIT REQUIREMENTS

1. Sulfur compound emissions shall not exceed 2,000 ppmv as SO2. [District Rule 4801, 3.0] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1.1 and 5.1.2] Federally Enforceable Through Title V Permit
4. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
5. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
6. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

7. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

8. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

9. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

10. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

11. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

12. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

13. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

14. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

15. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

16. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

18. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

19. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

20. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

21. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

22. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

23. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

24. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

25. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
27. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit
28. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
29. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
30. Permittee shall maintain a current well roster of all closed vent wells, and such roster shall be made readily available for District inspection upon request. [District Rule 4401] Federally Enforceable Through Title V Permit
31. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-106-4

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
20 CLOSED-VENT TEOR WELLS

DRAFT

PERMIT UNIT REQUIREMENTS

1. Sulfur compound emissions shall not exceed 2,000 ppmv as SO2. [District Rule 4801, 3.0] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1.1 and 5.1.2] Federally Enforceable Through Title V Permit
4. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
5. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
6. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

7. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

8. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

9. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

10. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

11. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

12. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

13. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

14. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

15. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

16. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

18. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

19. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

20. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

21. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

22. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

23. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

24. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

25. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
27. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit
28. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
29. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
30. Permittee shall maintain a current well roster of all closed vent wells, and such roster shall be made readily available for District inspection upon request. [District Rule 4401] Federally Enforceable Through Title V Permit
31. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-111-9

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 70 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-1-13D WITH SEPARATOR, LOW PRESSURE AIR COOLER AND CONDENSATE COLLECTOR (13 D SOUTHEAST)

PERMIT UNIT REQUIREMENTS

1. Operation of the low pressure air cooler is optional. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
3. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
4. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
5. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
9. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
10. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

12. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

13. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

15. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

16. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

17. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

21. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

22. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

23. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

24. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

25. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

26. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

28. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

29. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

30. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

31. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

32. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

34. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

35. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

36. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

37. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

38. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

39. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, or a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

41. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

42. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

43. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

45. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

46. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

47. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

48. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

49. {1667} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. {1311} The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. Permittee shall maintain a current roster of all wells connected to this system. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

52. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

53. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-112-19 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

DRAFT

EQUIPMENT DESCRIPTION:
TEOR OPERATION #6C-CC-1 SERVING 20 AUTOMATIC WELL TESTERS AND 326 STEAM-ENHANCED WELLS WITH LIQUID KNOCK OUT VESSEL (OPTIONAL) WITH DISTRICT-APPROVED VAPOR CONTROL SYSTEM

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Section 6 Township 20S Range 15E; Section 31 Township 19S Range 15E; and Section 36 Township 19S Range 14E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The 6C-CC-1 system may be operated as a vapor balance system and/or an active well vent vapor recovery system. When operated as a vapor balance system, valves associated with the 6C-CC-1 system may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0 and 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, or a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. {1667} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. {1311} The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-114-10 **EXPIRATION DATE:** 12/31/2016

SECTION: 18 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 23 MMBTU/HR HOPPER STEAM GENERATOR, HSG-36, NATURAL GAS FIRED WITH ONE NORTH AMERICAN BURNER, DIS #21013-66

PERMIT UNIT REQUIREMENTS

1. {4558} Operation of the unit is not authorized until modifications are made to comply with District Rules as authorized by an Authority to Construct. [District Rule 2010]
2. This permit unit shall not be operated unless the owner or operator applies to modify the Title V permit to address the requirements of District Rule 2520, section 9.0 for this permit unit. [District Rule 2520, 9.0] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305]
4. The emissions shall not exceed 30 ppmv NOx (0.036 lb-NOx/MMBtu) @ 3% O2. [District Rule 4305]
5. No modification to this unit shall be performed without an Authority to Construct for that modification(s), except for changes specified in condition 5. [District Rule 2201]
6. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305]
7. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081]
8. {15} No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
9. Natural gas consumption shall not exceed 526,000 cubic feet per day or 192 million cubic feet per year. [District Rule 2201]
10. This unit shall be fired exclusively with natural gas. [District Rule 2201]
11. Daily emission limit shall not exceed: PM10 - 2.63 lb/day, SOx - 0.32 lb/day, NOx - 18.9 lb/day, CO - 18.4 lb/day, or VOC (NMHC) - 1.47 lb/day. [District Rule 2201]
12. Fuel consumption shall be recorded on a daily basis. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-117-10 **EXPIRATION DATE:** 12/31/2016

SECTION: 18 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 23 MMBTU/HR HOPPER STEAM GENERATOR, HSG-1, NATURAL GAS FIRED, WITH ONE NORTH AMERICAN BURNER, DIS #5702-66

DRAFT

PERMIT UNIT REQUIREMENTS

1. {4558} Operation of the unit is not authorized until modifications are made to comply with District Rules as authorized by an Authority to Construct. [District Rule 2010]
2. This permit unit shall not be operated unless the owner or operator applies to modify the Title V permit to address the requirements of District Rule 2520, section 9.0 for this permit unit. [District Rule 2520, 9.0] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305]
4. The emissions shall not exceed 30 ppmv NOx (0.036 lb-NOx/MMBtu) @ 3% O2. [District Rule 4305]
5. No modification to this unit shall be performed without an Authority to Construct for that modification(s), except for changes specified in condition 5. [District Rule 2201]
6. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305]
7. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081]
8. {15} No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
9. Natural gas consumption shall not exceed 526,000 cubic feet per day or 192 million cubic feet per year. [District Rule 2201]
10. This unit shall be fired exclusively with natural gas. [District Rule 2201]
11. Daily emission limit shall not exceed: PM10 - 2.63 lb/day, SOx - 0.32 lb/day, NOx - 18.9 lb/day, CO - 18.4 lb/day, or VOC (NMHC) - 1.47 lb/day. [District Rule 2201]
12. Fuel consumption shall be recorded on a daily basis. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-122-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

DRAFT

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED PETROLEUM STORAGE TANK #T-101 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

40. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, permittee may conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rules 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-123-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

DRAFT

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-102 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

40. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, permittee may conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rules 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-124-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-103 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

DRAFT

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak, the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

40. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, permittee may conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rules 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-125-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-400 SERVED BY SHARED VAPOR RECOVERY SYSTEM ON PERMIT UNIT C-311-129

DRAFT

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

51. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rules 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-126-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-300 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

DRAFT

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

51. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rules 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-127-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-200 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. The efficiency of any VOC destruction device shall be measured by EPA Method 18, 25, or 25a. [District Rule 4623, 6.4.7]

40. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

41. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

42. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

52. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rules 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-128-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
3,020 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-201 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

51. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rules 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-129-11 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

DRAFT

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-500 SERVED BY A VAPOR RECOVERY SYSTEM INCLUDING CONDENSER, COMPRESSOR, CONDENSATE COLLECTION VESSEL, TRANSFER PUMP AND BACK-UP/STANDBY ELECTRIC COMPRESSOR SERVED BY SHARED CASING COLLECTION SYSTEM FOR SECTION 6C - PERMIT UNIT C-311-112 AND TANK PERMIT UNITS C-311-122, -123, -124, -125, -126, -127, -128 AND -129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Throughput of liquid to the storage tank shall not exceed 5.88 million gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit

42. VOC emissions from this tank shall not exceed 2.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

43. Vapor pressure of liquids stored shall not exceed 5 psia reid vapor pressure nor 3.6 psia true vapor pressure. [District Rule 2201] Federally Enforceable Through Title V Permit

44. Collected condensed vapors shall be returned to one of the storage tanks served by the vapor recovery system. [District Rule 2201] Federally Enforceable Through Title V Permit

45. Permittee shall record annual liquid throughput and true vapor pressure of the liquids stored. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

46. The vapor recovery system shall control the tanks identified in permit units C-311-122, -123, -124, -125, -126, -127, -128 and -129. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. When storing liquids of TVP equal to or greater than 0.5 psia, prior to opening the tank to allow tank cleaning one of the following procedures must be followed: 1) operate the vapor recovery system for at least 24 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The vapor recovery system may control the recovered well casing vapors from permit unit C-311-112 during operation of the casing collection system as a casing balance system. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

56. The 6C-CC-1 system (C-311-112) may be operated as a vapor balance system and/or an active well vent vapor recovery system. When operated as a vapor balance system valves associated with the 6C-CC-1 system (C-311-112) may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District Rule 2201] Federally Enforceable Through Title V Permit

57. Collected VOC vapors shall be incinerated in steam generators C-311-36, '-37, '-38, '-39, '-40, '-41, '-52, '-53, '-55, '-56, '-76 and -'84, or disposed of in Department of Oil, Gas, and Geothermal Resources (DOGGR) approved vapor disposal well(s). [District Rule 2201] Federally Enforceable Through Title V Permit

58. Operation of the casing collection system as a casing balance system shall not cause gas flow rates at the 6C, 13D and/or 25D Oil Cleaning Plant in excess of the design capacity of the tank vapor recovery compressor. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-146-24 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-23 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-267

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-147-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-22 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-150-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-18 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-267

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-163-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
4,697 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-31 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rules 2520, 9.3.2 and 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2520, 9.3.2 and 4623, 5.6.2] Federally Enforceable Through Title V Permit

15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-164-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
4,697 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-32 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-165-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,592 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-29 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-268

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-166-15

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,592 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-30 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
9. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
12. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
14. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit
15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
16. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
19. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

46. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

52. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-167-15

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
3,579 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-33 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-168-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
3,579 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-34 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers.. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-169-15

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,424 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-60 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-170-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,901 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-37 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-268

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-177-18 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,047 BBL FIXED ROOF FREE WATER KNOCK OUT TANK # 25-42 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-180-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
523 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-3

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-181-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
523 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-4

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-182-4

EXPIRATION DATE: ~~12/31/2016~~

DRAFT

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
269 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-5

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-196-15

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF WASH TANK # 13-29 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.
DRAFT

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-197-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF WASH TANK # 13-30 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
9. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

12. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

13. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

46. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

52. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-198-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
270 BBL FIXED ROOF CRUDE OIL TANK # 13-13 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-205-4

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
20 OPEN-VENT CYCLIC WELLS

PERMIT UNIT REQUIREMENTS

1. There may be no more than 20 open-vent cyclic-driven petroleum production wells at this stationary source, when the well is undergoing pilot testing (and the production zone has not been injected with steam in the preceding two years) or well stimulation; and no more than 5 wells that are not undergoing pilot testing or well stimulation may be operated. [District Rule 4401] Federally Enforceable Through Title V Permit
2. The well is located more than 1,000 feet from an existing well vent vapor control system operated by the company. [District Rule 4401, 4.5.1] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-215-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-1

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-216-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-2

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-217-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-3

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-219-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-5

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-220-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-6

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-221-4

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-7

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-222-7

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
3000 BBL CONE BOTTOM WASH TANK #24-9

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. VOC emissions shall not exceed 1.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-223-5

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-10

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The tank shall be operated at constant level. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. VOC emissions shall not exceed 1.4 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-227-4 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
GASOLINE DISPENSING OPERATION WITH ONE 2,000 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROS EVR PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE(S) SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116-F)

PERMIT UNIT REQUIREMENTS

1. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622, and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit

9. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit

10. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

11. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit

12. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit

13. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit

14. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

16. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
17. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6 Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected once per month if monthly throughput is below 2,500 gallons or once per week otherwise. [District Rule 4622] Federally Enforceable Through Title V Permit
18. If a Liquid Condensate Trap is installed, the permittee shall perform and pass a Liquid Condensate Trap Compliance Test using the test procedure defined in the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rule 4622] Federally Enforceable Through Title V Permit
19. If a Liquid Condensate Trap is installed it shall be (1) maintained without leaks; (2) accessible for inspection upon request; (3) capable of automatic evacuation of liquid; and (4) equipped with an alarm system in case of failure of the evacuation system. [District Rule 4622] Federally Enforceable Through Title V Permit
20. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
23. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
24. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
26. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
27. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
28. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. This permit unit is not equipment used for light crude oil and gas production, natural gas processing, nor organic liquid loading, and is not an internal or external floating roof tank with a capacity of 19,800 gallons or more. Therefore, the requirements of 4623 except section 5.4 (Amended May 19, 2005) do not apply to this permit unit. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. This permit unit is not associated with loading at a bulk gasoline terminal (as defined in 40 CFR 60.501). Therefore, the requirements of 40 CFR 60 Subpart XX do not apply to this permit unit. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-232-3

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 31 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Formerly C-1121-162-2

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-233-3

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 31 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
3. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
5. {2589} For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. {2592} As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. The operator shall keep an accurate daily record of each organic liquid stored in each tank, including its storage temperature, TVP, and API gravity. [District Rules 2520, 9.3.2 and 4623, 6.3.1] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly C-1121-163-2

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-234-3

EXPIRATION DATE: 12/31/2016

SECTION: 31 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Formerly C-1121-164-2

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-235-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 25D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
600 BHP CUMMINS MODEL #KTA19C52 SERIAL #31134968 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [17 CCR 93115]
4. Emissions from this IC engine shall not exceed 1.0 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [17 CCR 93115]
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
8. The engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

14. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

15. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

16. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

17. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit

18. The permittee shall maintain monthly records that include the type of fuel purchased, the amount of fuel purchased, and the date of fuel purchase. [District Rules 4702 and 2520, 9.4 and 17 CCR 93115] Federally Enforceable Through Title V Permit

19. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.), and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4702 and 2520, 9.4, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

20. The permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [District Rules 1070 and 2520, 9.4, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

21. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [District Rules 1070 and 2520, 9.4, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4702 and 2520, 9.4, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

23. This permit unit was formerly number C-311-91.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-236-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,100 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-19 SERVED BY SHARED VAPOR RECOVERY SYSTEM
PTO C-311-267

DRAFT

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (Amended December 18, 2014). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201] Federally Enforceable Through Title V Permit

53. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

56. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

57. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-238-4 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
TRANSPORTABLE TIER 3 CERTIFIED DIESEL-FIRED IC ENGINE UP TO 532 HP FOR MECHANICAL PUMPING, COMPRESSION, OR POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Permittee shall provide written notification to the District within 48 hours of operating an engine under this permit (if an engine is located onsite longer than 24 hours). Such notification shall include the date the unit was brought onsite, the manufacturer, model number, maximum rating, and emissions information that documents that the unit meets the emission limits and requirements specified in the permit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Any engine utilized by this permit shall not be operated within 181 feet of facility boundary. [District Rule 4102]
4. Any engine utilized by this permit shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93116] Federally Enforceable Through Title V Permit
6. Any engine utilized by this permit shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Any engine utilized by this permit shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
8. Any nonroad transportable engine utilized by this permit shall not be operated at one location for more than 12 consecutive months and shall meet all the requirements of a nonroad transportable engine, per CFR Title 40 Part 89. [District Rule 4701 and 17 CCR 93116] Federally Enforceable Through Title V Permit
9. Operation of the engine shall not exceed 200 hours per year, as determined by an operational nonresettable elapsed operating time meter or other APCO approved alternative. The operator shall maintain records of the cumulative hours of operation on a 12 month rolling average. These records shall be updated at least monthly. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
10. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
11. Emissions from any engine utilized by this permit shall not exceed any of the following limits: 2.85 g-NOx/bhp-hr, 2.61 g-CO/bhp-hr, or 0.15 g-VOC/bhp-hr. [District Rule 2201 and 17 CCR 93116] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. The PM10 emissions rate from any engine utilized by this permit shall not exceed 0.15 g/hp-hr based on US EPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
13. During periods of operation, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
14. Permittee shall maintain a permit operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
15. Permittee shall maintain records of each location where the permit unit is operated, including dates and duration of residency at each location, and shall update those records each time any IC engine utilized by this permit is moved. [District Rule 2201 and 17 CCR 93116] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-239-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 19 **TOWNSHIP:** 28S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
157 BHP CATERPILLAR MODEL LC3034B S/N E5M02254 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

DRAFT

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
8. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
9. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102] Federally Enforceable Through Title V Permit
10. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
11. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, 17 CCR 93115, 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. Emissions from this IC engine shall not exceed any of the following limits: 2.53 g-NOx/bhp-hr, 1.34 g-CO/bhp-hr, or 0.13 g-VOC/bhp-hr. [District Rule 2201, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

13. Emissions from this IC engine shall not exceed 0.15 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
14. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
15. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
16. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
17. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
18. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
19. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
20. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-240-4

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
600 BBL PRESSURE VESSEL VENTED TO TEOR OPERATION C-311-79

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission components exclude piping and components handling produced fluids having less than 10% VOC by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operator shall conduct quarterly sampling of tank vapors to qualify for exemption from fugitive component counts for components handling fluids with less than 10% VOC by weight. If 8 consecutive quarterly samplings show compliance, then sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC content of vapor shall be determined by ASTM D1945, ASTM D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All vessel and vapor control system piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated to methane, to ensure compliance with the provisions of this permit. If any of the vessel components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no vessel components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 ft above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
6. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
7. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Permittee shall maintain a written record of the VOC content of the gas sampled. [District Rule 2201] Federally Enforceable Through Title V Permit

10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-248-1 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20s **RANGE:** 14e

EQUIPMENT DESCRIPTION:
85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR SG-13/25-XA WITH NORTH AMERICAN MODEL 4231-85 GLE LOW-NOX BURNER, AND FLUE GAS RECIRCULATION

DRAFT

PERMIT UNIT REQUIREMENTS

1. This steam generator may be operated at the 13D or 25D steam plants. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. The unit shall always operate at least 604 meters away from the nearest property boundary line. [District Rule 4102]
4. This unit shall be fired on PUC quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 1 grain of total sulfur per 100 standard cubic feet or 0.00285 lb/MMBtu. [District Rules 2201, 4320 and 4801] Federally Enforceable Through Title V Permit
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
8. Except during startup and shutdown periods, emissions shall not exceed either of the following limits: 7 ppmvd NOx (as NO2) @ 3% O2 (0.0085 lb/MMBtu), 0.0032 lb PM10/MMBtu, 25 ppmvd CO @ 3% O2 (0.0185 lb/MMBtu) or 12 ppmvd VOC @ 3% O2 (0.0055 lb VOC/MMBtu). [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 5.5.6 and 4306, 5.3] Federally Enforceable Through Title V Permit
11. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25 and 3.22] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. If either the NOx or CO concentrations corrected to 3%, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The NOx, CO, and O2 analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute sample period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. The permittee shall maintain records of: (1) the date and time of NOx, CO and O2 measurements, (2) the O2 concentration in percent by volume and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. For the purposes of permittee-performed alternate monitoring, emissions measurements may be performed at any time after the unit reaches conditions representative of normal operation. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
23. Each fuel source shall be tested semi-annually for sulfur content and higher heating value. If a fuel content test fails to show compliance, weekly testing is required until compliance is demonstrated for 8 consecutive weeks, after which semi-annual testing may resume. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
24. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, 4320, and 40 CFR 60.48c(i)] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-253-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

DRAFT

EQUIPMENT DESCRIPTION:
324 BHP INTERMITTENT CUMMINS MODEL QSB7-G5NR3 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR (13D WATER PLANT)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. Emission rates from this unit shall not exceed any of the following limits: 2.8 g-NOx/hp-hr, 0.0051 g-SOx/hp-hr, 0.147 g-PM10/hp-hr, 2.6 g-CO/hp-hr; 0.2 g-VOC/hp-hr, or a combined 3.0 g-NOx+VOC/hp-hr. [District Rule 2201 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-254-1 **EXPIRATION DATE:** 12/31/2016

SECTION: SW6 **TOWNSHIP:** 20S **RANGE:** 15E

DRAFT

EQUIPMENT DESCRIPTION:
85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR SG-6-36 WITH NORTH AMERICAN MODEL 4231-85 GLE LOW-NOX BURNER AND FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
5. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Emission rates, except during startup and shutdown shall not exceed: NOx (as NOx): 7 ppmvd @ 3% O2 or CO: 25 ppmvd @ 3% O2. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. Emission rates shall not exceed any of the following: SOx: 0.00285 lb/MMBtu; PM10: 0.0032 lb/MMBtu; or VOC: 0.0055 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions rates shall not exceed 48.5 lb-NOx/day or 6,329 lb-NOx/yr; or 60.4 lb-CO/day or 13,775 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of duration of each start-up and shutdown for a period of five years and make such records readily available for District inspection upon request. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10, 10B or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6, 6A, 6B, 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588, VOC (ppmv) - EPA Method 25A or 25B, or ARB Method 100. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

15. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. If the NOx or CO concentrations corrected to 3%, as measured by the portable analyzer, exceed the applicable emission limit, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4102, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

17. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The NOx, CO, and O2 analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute sample period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive minute period. [District Rules 4102, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall maintain records of: (1) the date and time of NOx, CO and O2 measurements, (2) the O2 concentration in percent by volume and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

19. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the PTO, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. For the purposes of permittee-performed alternate monitoring, emissions measurements may be performed at any time after the unit reaches conditions representative of normal operation. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. Shorter time periods for demonstration of compliance after startup or re-ignition may be approved by the APCO by submittal of appropriate technical justification upon implementation of this ATC. [District Rule 2201] Federally Enforceable Through Title V Permit

21. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

22. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, permittee shall demonstrate compliance at least annually. [District Rule 4320] Federally Enforceable Through Title V Permit

24. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit

25. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-265-2 **EXPIRATION DATE:** 12/31/2016

SECTION: NE 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1000 BBL VESSEL SERVED BY VAPOR CONTROL SYSTEM LISTED ON C-311-111

DRAFT

PERMIT UNIT REQUIREMENTS

1. Maximum VOC content of tank/vessel vapors shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operator shall conduct and keep records of quarterly sampling of tank/vessel vapors to qualify for exemption from fugitive component counts for components handling fluids with less than 10% VOC by weight. If fluids sampled are less than 10% VOC by weight for eight consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Vessel shall only store, place, or hold organic liquid with true vapor pressure (TVP) less than 0.5 psia under all storage conditions. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2520] Federally Enforceable Through Title V Permit
5. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2201, 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

11. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. {941} The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-266-2

EXPIRATION DATE: 12/31/2016

SECTION: NE 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
250 BBL CRUDE OIL DRAIN TANK CLAREMONT T-6

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) less than 0.1 psia under all storage conditions. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. VOC emission rate from the tank shall not exceed 0.5 lb/day. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank within 60 days of startup in accordance with the methods described in this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. Operator shall determine the true vapor pressure (TVP) of the petroleum liquid stored in this tank at least once every 24 months in accordance with the methods described in this permit. Determinations shall be made during the months of July - September and whenever there is a change in the source or type of organic liquid entering the tank. Determination can be made using representative sampling as described in Section 6.2.1.1 of District Rule 4623. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of TVP and API gravity testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Permittee shall maintain monthly records of average daily crude oil throughput and shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-267-7 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 120S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
13D OIL CLEANING PLANT VAPOR RECOVERY SYSTEM, SERVING PERMIT UNITS C-311-112, '-146, '-147, '-150, '-196, '-197, '-198, AND '-236, INCLUDING TWO (2) 50 HP COMPRESSORS, REGULATOR, AND VAPOR PIPING TO DISTRICT APPROVED STEAM GENERATORS C-311-20, '-21, '-25, '-28, '-30, '-36, '-37, '-38, '-39, '-40 AND/OR '-41, OR DOGGR APPROVED VAPOR DISPOSAL WELLS

DRAFT

PERMIT UNIT REQUIREMENTS

1. Vapor recovery system shall consist of a closed vent system that collects VOCs from District approved storage tanks and discharges to District approved VOC vapor recovery. The vapor recovery system shall be APCO-approved. The VOC vapor recovery system shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, vapor balance well vent/tank vapor recovery system, DOGGR-approved injection well(s) for disposal of vapors, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method(s) specified in this permit. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Vapor recovery system compressor shall activate before the pressure relief valve vents, on any of the units served by the vapor recovery equipment. The vapor recovery system does not serve tanks while they are disconnected during District authorized cleaning and maintenance events as allowed by those permits. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. The vapor recovery system may control the recovered well casing vapors from permit units C-311-77, -78, -83, and -111 during operation of the casing collection system as a casing balance system. [District Rules 2201and 4623] Federally Enforceable Through Title V Permit
4. The 13D system may be operated as a vapor balance well vent/tank vapor recovery system. When operated as a vapor balance system, valves associated with the 13D system may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Operation of the casing collection system as a casing balance system shall not cause gas flow rates at the 6C, 13D and/or 25D Oil Cleaning Plant in excess of the design capacity of the tank vapor recovery compressor. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, -267, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
7. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

8. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit

9. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Maximum VOC content of vapor in the vapor recovery system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

13. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, ASTM D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 1081] Federally Enforceable Through Title V Permit

14. Except as otherwise provided on this permit, vapor recovery system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

15. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

16. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

23. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201] Federally Enforceable Through Title V Permit

25. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-268-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
25D OIL CLEANING PLANT VAPOR RECOVERY SYSTEM, SERVING PERMIT UNITS C-311-163, '-164, '-165, '-166, '-167, '-168, '-169, '-170 AND '-177, INCLUDING 50 HP COMPRESSOR, TWO VERTICAL SCRUBBERS, FIN FAN COOLER, REGULATOR, AND VAPOR PIPING TO DISTRICT APPROVED STEAM GENERATORS C-311-20, '-21, '-25, '-28, '-30, '-36, '-37, '-38, '-39, '-40 AND/OR '-41, OR DOGGR APPROVED VAPOR DISPOSAL WELLS

PERMIT UNIT REQUIREMENTS

1. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
2. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealants, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Vapor recovery system shall consist of a closed vent system that collects VOCs from District approved storage tanks and discharges to District approved VOC vapor recovery. The vapor recovery system shall be APCO-approved. The VOC vapor recovery system shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, vapor balance well vent/tank vapor recovery system, DOGGR-approved injection well(s) for disposal of vapors, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method(s) specified in this permit. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
7. Vapor recovery system compressor shall activate before the pressure relief valve vents, on any of the units served by the vapor recovery equipment. The vapor recovery system does not serve tanks while they are disconnected during District authorized cleaning and maintenance events as allowed by those permits. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. The vapor recovery system may control the recovered well casing vapors from permit unit C-311-79 during operation of the casing collection system as a casing balance system. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

9. The 25D system may be operated as a vapor balance well vent/tank vapor recovery system. When operated as a vapor balance system valves associated with the 25D system may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Operation of the system as a balance system shall not cause gas flow rates at the 6C, 13D and/or 25D Oil Cleaning Plant in excess of the design capacity of the tank vapor recovery compressor. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Maximum VOC content of vapor in the vapor recovery system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Operator shall test VOC content of the vapors representative of 25D tank vapor recovery gas annually. [District Rule 2201] Federally Enforceable Through Title V Permit

13. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

14. Except as otherwise provided on this permit, vapor recovery system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

15. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

16. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

23. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-269-1 **EXPIRATION DATE:** 12/31/2016

SECTION: 36 **TOWNSHIP:** 19S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TANK #CO-T-57: 10,584 GALLON FIXED ROOF CRUDE OIL STORAGE TANK, 15'D X 8'H, CAPACITY: 252 BBLS

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Formerly #C-8517-4-0

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-270-1 **EXPIRATION DATE:** 12/31/2016

SECTION: 36 **TOWNSHIP:** 19S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TANK #CO-T-58: 10,584 GALLON FIXED ROOF CRUDE OIL STORAGE TANK, 15'D X 8'H, CAPACITY: 252 BBLS

DRAFT

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1 of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. Formerly #C-8415-5-0

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-311-271-3 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK (OR DISTRICT APPROVED EQUIVALENT), #13-13A SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Tank shall not be required to be served by vapor control system C-311-267 during vapor recovery system (tanks to disposal devices, inclusive) maintenance/repairs/upset conditions for up to 600 hours per year. Approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, inspection, monitoring, and repair if necessary of fugitive emissions components at job site within 30 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
7. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

12. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

13. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

28. {983} The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

29. {984} The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201] Federally Enforceable Through Title V Permit

31. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

34. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

DRAFT

ATTACHMENT B

Previous Title V Operating Permit

FACILITY: C-311-0-3 **EXPIRATION DATE:** 12/31/2016

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit

30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit

31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit

32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit

33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit

35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

42. Facility shall comply with all applicable requirements regarding preparation and implementation of a risk management plan (RMP) by August 31, 1999, and shall abide by all applicable sections of 40 CFR Part 68. [40 CFR Part 68] Federally Enforceable Through Title V Permit

43. On September 30, 2001, the initial Title V permit was issued. The reporting period of the Report of Required Monitoring and the Compliance Certification Report begin October 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of reporting period. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-13-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT EMISSIONS UNIT CONSISTING OF 86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-105, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A STRUTHERS WASTE HEAT RECOVERY STEAM GENERATOR #SG-205, WITH A 36.4 MMBTU/HR COEN DUCT BURNER

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4703] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4703 and all other applicable District regulations. [District Rule 4703] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
5. The Owner/Operator shall maintain a separate fuel meter to the turbine and a fuel meter to the duct burners. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Natural gas consumption by the cogeneration system (turbine and duct burner) shall not exceed 1,812,000 scf/day. Natural gas consumption by the cogeneration system shall not exceed 654 million scf/year. [District Rule 2201]
7. Emissions from the cogeneration system shall not exceed any of the following limits: 233.7 lb-NOx/day, 3.6 lb-SOx/day, 47.1 lb-PM10/day, 257.3 lb-CO/day, or 47.1 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The owner or operator shall not operate the gas turbine under load conditions, excluding the thermal stabilization period or reduced load period, which results in the measured NOx emissions concentration exceeding 35 ppmv @ 15% O2. [40 CFR 60.332(a)(1), (a)(2) and District Rules 2201 and 4703, 5.1.2.1] Federally Enforceable Through Title V Permit
9. CO emissions from the cogeneration system with the duct burner firing shall not exceed 53 ppmv CO @ 15% O2 or 0.119 lb-CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
10. CO emissions from the cogeneration system without duct burner firing shall not exceed 63 ppmv CO @ 15% O2 or 0.142 lb CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
11. Emissions from the cogeneration system (with or without duct burner firing) shall not exceed any of the following limits: 0.002 lb-SOx/MMBtu, 0.026 lb-PM10/MMBtu, or 0.026 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Reduced Load Period shall be defined as the time during which the gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate, not exceeding one hour. [District Rule 4703, 3.19] Federally Enforceable Through Title V Permit

13. Thermal Stabilization Period shall be defined as the startup or shutdown, as defined in 40 CFR 60.2, time during which the exhaust gas is not within the normal operating temperature range, not to exceed two hours per startup or shutdown event. [District Rule 4703, 3.25] Federally Enforceable Through Title V Permit

14. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit

15. The sulfur fuel content of each fuel source shall be: (i) documented in a valid purchase contract, a supplier certification, a tariff sheet or transportation contract or (ii) monitored weekly using ASTM Methods D4084, D5504, D6228, or Gas Processors Association Standard 2377, or double GC for H2S and mercaptans. If the sulfur fuel content is less than 1.0 gr/100 scf for eight consecutive weeks, then the monitoring frequency shall be every 6 months. If any six-month monitoring tests result in a sulfur fuel content exceedance, weekly monitoring shall resume. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit

16. Performance testing shall be conducted annually to measure NOx and CO emissions concentrations using the following test methods: EPA Methods 7E or 20 for NOx emissions, EPA Methods 10 or 10B for CO emissions, EPA Methods 3, 3A, or 20 for Oxygen content of the exhaust gas. The test will be comprised of three test runs performed at the highest physically achievable load of the gas turbine. The measured NOx concentrations shall be averaged over a three hour period, using consecutive 15-minute sampling periods. [40 CFR60.335(a), (b)(2) and District Rule 4703, 5.1, 6.3.1, 6.3.2, and 6.4] Federally Enforceable Through Title V Permit

17. Any gas turbine with an intermittently operated auxiliary burner shall demonstrate compliance with the auxiliary burner both on and off. Source testing shall not be required with the duct burner on if it has not been in operation during the previous 12 months, i.e. the duct burner need not be started to solely perform source testing. Source testing shall not be required with the duct burner off if it has been in continuous operation during the previous 12 months, i.e. the duct burner need not be shut-down solely to perform source testing. Source testing shall be performed within 60 days of startup or shutdown of the duct burner unless source testing of the duct burner has been performed in the previous 12 months. [40 CFR 60.335(b) and District Rule 4703, 6.3.3] Federally Enforceable Through Title V Permit

18. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

19. The owner or operator shall be required to conform to the sampling facilities and testing procedures described in Rule 1081 (as amended 12/16/93), Sections 3.0 and 6.1. [District Rule1081] Federally Enforceable Through Title V Permit

20. The District must be notified 30 days prior to any performance testing and a test plan shall be submitted for approval 15 days prior to such testing. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Performance testing shall be witnessed or authorized by District personnel. Test results must be submitted to the District within 60 days of performance testing. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The owner or operator shall operate and maintain in calibration a system which continuously measures and records: control system operating parameters, elapsed time of operation, the fuel consumption and the ratio of water to fuel being fired in the turbine. [40 CFR 60.334(a) and District Rule 4703, 6.2.2] Federally Enforceable Through Title V Permit

23. The owner or operator shall develop and keep on-site a parameter monitoring plan which includes the procedures used to document the proper operation of the NOx emissions controls (water injection). This plan shall include the parameter(s) monitored, such as the water-to-fuel ratio, and the acceptable range(s) of the parameter(s) as well as the basis for designating the parameter(s) and acceptable range(s). Any supplemental data such as engineering analyses, design specifications, manufacturers recommendations and other relevant information shall be included in the monitoring plan. [40 CFR 60.334(g)] Federally Enforceable Through Title V Permit

24. The water to fuel ratio shall not be less than 0.45 on a weight basis. [District Rule 4703, 6.2.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The owner or operator shall submit a semi-annual excess NOx emissions and monitor downtime report to the APCO. Excess emissions shall be reported for all periods of operation, including startup, shutdown and malfunction. The report, post marked by the 30th day following the end of every other calendar quarter, shall include the following: Time intervals, average steam or water-to-fuel ratio, turbine load, nature and cause of excess emissions (if known), and corrective actions taken and preventative measures adopted. [40 CFR 60.334(j), (j)(5) and District Rule 2520, 9.3.2)] Federally Enforceable Through Title V Permit

26. Excess emissions shall be defined as any operating hour for which the steam or water to fuel ratio, as measured by the continuous monitoring system, falls below the established steam or water to fuel ratio. Any operating hour in which no steam or water is injected into the turbine shall also be considered as excess emissions. [40 CR 60.334(j)(1)(i)(A)] Federally Enforceable Through Title V Permit

27. Monitor downtime shall be any operating hour in which the water or steam is injected into the turbine, but essential parametric data needed to determine the steam or water to fuel ratio are unavailable or invalid. [40 CFR 60.334(j)(1)(i)(B)] Federally Enforceable Through Title V Permit

28. Fuel consumption and the water-to-fuel ratio shall be monitored continuously with a system that is accurate to within 5 percent. [District Rule 2201] Federally Enforceable Through Title V Permit

29. The cogeneration system shall be equipped with a meter recording the total elapsed operating time. [District NSR Rule] Federally Enforceable Through Title V Permit

30. Permittee shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100] Federally Enforceable Through Title V Permit

31. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100] Federally Enforceable Through Title V Permit

32. If the water injection system is inoperative when the turbine is running, the operator shall follow procedures pursuant to District Rule 1100 (Equipment Breakdown). [District Rule 1100] Federally Enforceable Through Title V Permit

33. The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

34. If the turbine is fired on PUC-regulated natural gas, then the operator shall maintain a log describing the source of natural gas and quantity used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

35. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments and emissions measurements. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

36. The owner or operator shall maintain a record of the cumulative rolling 12 month fuel usage for each turbine. The record shall be updated at the end of each calendar month. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis, the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332(a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

38. The owner or operator of a stationary gas turbine system shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: 40 CFR 60.332(a)(1), (a)(2), 60.333 (b), (g), (h)(3), (j), (j)(1)(i)(A), (j)(1)(i)(b), and (j)(5); 60.335(a), (b)(2), (b)(3); and District Rule 4703 (as amended 4/25/02), Sections 5.1.2.1, 5.2, 6.2.2, 6.4, and 6.2.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 1081(as amended 12/16/93), Section 3.0, 6.0, 7.1, 7.2, 7.3 and Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-15-12 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT EMISSIONS UNIT CONSISTING OF 86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-106, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A STRUTHERS WASTE HEAT RECOVERY STEAM GENERATOR #SG-206 WITH A 36.4 MMBTU/HR COEN DUCT BURNER

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4703] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4703 and all other applicable District regulations. [District Rule 4703] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
5. The Owner/Operator shall maintain a separate fuel meter to the turbine and a fuel meter to the duct burners. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Natural gas consumption by the cogeneration system (turbine and duct burner) shall not exceed 1,812,000 scf/day. Natural gas consumption by the cogeneration system shall not exceed 654 million scf/year. [District Rule 2201]
7. Emissions from the cogeneration system shall not exceed any of the following limits: 233.7 lb-NOx/day, 3.6 lb-SOx/day, 47.1 lb-PM10/day, 257.3 lb-CO/day, or 47.1 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The owner or operator shall not operate the gas turbine under load conditions, excluding the thermal stabilization period or reduced load period, which results in the measured NOx emissions concentration exceeding 35 ppmv @ 15% O2. [40 CFR 60.332(a)(1), (a)(2) and District Rules 2201 and 4703, 5.1.2.1] Federally Enforceable Through Title V Permit
9. CO emissions from the cogeneration system with the duct burner firing shall not exceed 53 ppmv CO @ 15% O2 or 0.119 lb-CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
10. CO emissions from the cogeneration system without duct burner firing shall not exceed 63 ppmv CO @ 15% O2 or 0.142 lb CO/MMBtu, excluding thermal stabilization periods or reduced load periods. [District Rule 4703, 5.2] Federally Enforceable Through Title V Permit
11. Emissions from the cogeneration system (with or without duct burner firing) shall not exceed any of the following limits: 0.002 lb-SOx/MMBtu, 0.026 lb-PM10/MMBtu, or 0.026 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Reduced Load Period shall be defined as the time during which the gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate, not exceeding one hour. [District Rule 4703, 3.19] Federally Enforceable Through Title V Permit

13. Thermal Stabilization Period shall be defined as the startup or shutdown, as defined in 40 CFR 60.2, time during which the exhaust gas is not within the normal operating temperature range, not to exceed two hours per startup or shutdown event. [District Rule 4703, 3.25] Federally Enforceable Through Title V Permit

14. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit

15. The sulfur fuel content of each fuel source shall be: (i) documented in a valid purchase contract, a supplier certification, a tariff sheet or transportation contract or (ii) monitored weekly using ASTM Methods D4084, D5504, D6228, or Gas Processors Association Standard 2377, or double GC for H2S and mercaptans. If the sulfur fuel content is less than 1.0 gr/100 scf for eight consecutive weeks, then the monitoring frequency shall be every 6 months. If any six-month monitoring tests result in a sulfur fuel content exceedance, weekly monitoring shall resume. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit

16. Performance testing shall be conducted annually to measure NOx and CO emissions concentrations using the following test methods: EPA Methods 7E or 20 for NOx emissions, EPA Methods 10 or 10B for CO emissions, EPA Methods 3, 3A, or 20 for Oxygen content of the exhaust gas. The test will be comprised of three test runs performed at the highest physically achievable load of the gas turbine. The measured NOx concentrations shall be averaged over a three hour period, using consecutive 15-minute sampling periods. [40 CFR60.335(a), (b)(2) and District Rule 4703, 5.1, 6.3.1, 6.3.2, and 6.4] Federally Enforceable Through Title V Permit

17. Any gas turbine with an intermittently operated auxiliary burner shall demonstrate compliance with the auxiliary burner both on and off. Source testing shall not be required with the duct burner on if it has not been in operation during the previous 12 months, i.e. the duct burner need not be started to solely perform source testing. Source testing shall not be required with the duct burner off if it has been in continuous operation during the previous 12 months, i.e. the duct burner need not be shut-down solely to perform source testing. Source testing shall be performed within 60 days of startup or shutdown of the duct burner unless source testing of the duct burner has been performed in the previous 12 months. [40 CFR 60.335(b) and District Rule 4703, 6.3.3] Federally Enforceable Through Title V Permit

18. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

19. The owner or operator shall be required to conform to the sampling facilities and testing procedures described in Rule 1081 (as amended 12/16/93), Sections 3.0 and 6.1. [District Rule1081] Federally Enforceable Through Title V Permit

20. The District must be notified 30 days prior to any performance testing and a test plan shall be submitted for approval 15 days prior to such testing. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Performance testing shall be witnessed or authorized by District personnel. Test results must be submitted to the District within 60 days of performance testing. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The owner or operator shall operate and maintain in calibration a system which continuously measures and records: control system operating parameters, elapsed time of operation, the fuel consumption and the ratio of water to fuel being fired in the turbine. [40 CFR 60.334(a) and District Rule 4703, 6.2.2] Federally Enforceable Through Title V Permit

23. The owner or operator shall develop and keep on-site a parameter monitoring plan which includes the procedures used to document the proper operation of the NOx emissions controls (water injection). This plan shall include the parameter(s) monitored, such as the water-to-fuel ratio, and the acceptable range(s) of the parameter(s) as well as the basis for designating the parameter(s) and acceptable range(s). Any supplemental data such as engineering analyses, design specifications, manufacturers recommendations and other relevant information shall be included in the monitoring plan. [40 CFR 60.334(g)] Federally Enforceable Through Title V Permit

24. The water to fuel ratio shall not be less than 0.45 on a weight basis. [District Rule 4703, 6.2.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The owner or operator shall submit a semi-annual excess NOx emissions and monitor downtime report to the APCO. Excess emissions shall be reported for all periods of operation, including startup, shutdown and malfunction. The report, post marked by the 30th day following the end of every other calendar quarter, shall include the following: Time intervals, average steam or water-to-fuel ratio, turbine load, nature and cause of excess emissions (if known), and corrective actions taken and preventative measures adopted. [40 CFR 60.334(j), (j)(5) and District Rule 2520, 9.3.2)] Federally Enforceable Through Title V Permit

26. Excess emissions shall be defined as any operating hour for which the steam or water to fuel ratio, as measured by the continuous monitoring system, falls below the established steam or water to fuel ratio. Any operating hour in which no steam or water is injected into the turbine shall also be considered as excess emissions. [40 CR 60.334(j)(1)(i)(A)] Federally Enforceable Through Title V Permit

27. Monitor downtime shall be any operating hour in which the water or steam is injected into the turbine, but essential parametric data needed to determine the steam or water to fuel ratio are unavailable or invalid. [40 CFR 60.334(j)(1)(i)(B)] Federally Enforceable Through Title V Permit

28. Fuel consumption and the water-to-fuel ratio shall be monitored continuously with a system that is accurate to within 5 percent. [District Rule 2201] Federally Enforceable Through Title V Permit

29. The cogeneration system shall be equipped with a meter recording the total elapsed operating time. [District NSR Rule] Federally Enforceable Through Title V Permit

30. Permittee shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100] Federally Enforceable Through Title V Permit

31. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100] Federally Enforceable Through Title V Permit

32. If the water injection system is inoperative when the turbine is running, the operator shall follow procedures pursuant to District Rule 1100 (Equipment Breakdown). [District Rule 1100] Federally Enforceable Through Title V Permit

33. The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

34. If the turbine is fired on PUC-regulated natural gas, then the operator shall maintain a log describing the source of natural gas and quantity used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

35. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments and emissions measurements. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

36. The owner or operator shall maintain a record of the cumulative rolling 12 month fuel usage for each turbine. The record shall be updated at the end of each calendar month. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis, the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332(a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

38. The owner or operator of a stationary gas turbine system shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: 40 CFR 60.332(a)(1), (a)(2), 60.333 (b), (g), (h)(3), (j), (j)(1)(i)(A), (j)(1)(i)(b), and (j)(5); 60.335(a), (b)(2), (b)(3); and District Rule 4703 (as amended 4/25/02), Sections 5.1.2.1, 5.2, 6.2.2, 6.4, and 6.2.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 1081(as amended 12/16/93), Section 3.0, 6.0, 7.1, 7.2, 7.3 and Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-19-24 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED, MODEL 5G-50-NDS-15, THERMOTICS STEAM GENERATOR SG 13-03, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. This unit shall be fired on natural gas, or a blend of natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
7. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201 and 4301] Federally Enforceable Through Title V Permit
10. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301 and 2520] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2, equivalent to 0.017 lb-NOx/MMBtu or 25 ppmvd CO @ 3% O2 equivalent to 0.0185 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520 and 4301] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

26. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel sulfur testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by test methods and procedures outlined in this permit. [District Rules 2520, 4305, and 4351] Federally Enforceable Through Title V Permit

30. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-20-22 **EXPIRATION DATE:** 12/31/2016

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-04 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR WITH A NORTH AMERICAN GLE BURNER WITH FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.004 lb-PM10/MMBtu or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,332 lb-NOx/yr, 51.9 lb-CO/day, or 16,939 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

12. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

13. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. Well casing gas shall be sampled monthly from the gas line down stream from the point where the casing gas from all 4 casing collection systems is connected together and upstream from the point where the well casing gas is fed to the steam generators. The gas sample shall be analyzed by the laboratory for total sulfur and the results shall be given in grain/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Permittee shall maintain monthly records of the total amount of well casing gas consumed by the entire bank of steam generators (in MMscf), along with the date and time of the measurement. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall maintain monthly records of the total amount of PUC grade gas consumed by the entire bank of steam generators (in MMscf), along with the date and time of the measurement. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Natural gas sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source or natural gas shall be tested for sulfur content and higher heating value (hhv) monthly. Casing gas shall be tested for sulfur content and higher heating value (hhv) not less than monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

31. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

32. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-21-11 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14

EQUIPMENT DESCRIPTION:
58.5 MBTU/HR SG 13-05 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.004 lb-PM10/MMBtu or 0.08 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,332 lb-NOx/yr, 51.9 lb-CO/day, or 16,939 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

12. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

13. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

33. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-22-24 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED, MODEL 5G-50-NDS-15, THERMOTICS STEAM GENERATOR SG 13-06, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. This unit shall be fired on natural gas, or a blend of natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
7. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201 and 4301] Federally Enforceable Through Title V Permit
10. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301 and 2520] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2, equivalent to 0.017 lb-NOx/MMBtu or 25 ppmvd CO @ 3% O2 equivalent to 0.0185 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520 and 4301] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

26. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel sulfur testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by test methods and procedures outlined in this permit. [District Rules 2520, 4305, and 4351] Federally Enforceable Through Title V Permit

30. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-23-21 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED, MODEL 5G-50-NDS-15, THERMOTICS STEAM GENERATOR SG 13-06, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. This unit shall be fired on natural gas, or a blend of natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
7. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201 and 4301] Federally Enforceable Through Title V Permit
10. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301 and 2520] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2, equivalent to 0.017 lb-NOx/MMBtu or 25 ppmvd CO @ 3% O2 equivalent to 0.0185 lb-CO/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520 and 4301] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

26. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520] Federally Enforceable Through Title V Permit

28. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel sulfur testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520 and 4320] Federally Enforceable Through Title V Permit

29. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by test methods and procedures outlined in this permit. [District Rules 2520, 4305, and 4351] Federally Enforceable Through Title V Permit

30. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2520, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-25-10 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-09 NATURAL/LPG/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Combined natural , well casing, and TVR gas consumption shall not exceed either of the following limits: 1,404 million MMBtu/day or 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. LPG consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed any of the following limits: 0.045 lb-PM10/MMBtu or 0.009 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,912 lb-NOx/yr, 51.9 lb-CO/day, or 16,095 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
14. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit
21. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

32. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

33. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

34. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-27-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR STRUTHERS THERMOFLOOD STEAM GENERATOR #13-11, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER, EQUIPPED WITH FLUE GAS RECIRCULATION AND AN OXYGEN CONTROLLER

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, or a blend of PUC-quality natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day nor 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.00285 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.009 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 15 ppmvd NOx @ 3% O2 or 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rules 2201, 4305; 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,830 lb-NOx/yr, 51.9 lb-CO/day, and 16,084 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

17. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-28-20 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 13-12 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, EQUIPPED WITH A NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.008 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-30-19 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 13-14 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN BURNER, AND A FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.005 lb-PM10/MMBtu or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

12. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-36-24 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG-25-15 STRUTHERS THERMOFLOOD, MODEL OH-50-ND-16XAM STEAM GENERATOR WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE 25D NEPTUNE AIRPOL CAUSTIC SCRUBBER (SHARED WITH UNITS -37, -38, -39, -40, AND -41) WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total LPG, casing gas, waste gas, and natural gas consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Scrubber liquor pH shall be maintained between 6.5 and 8.0. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Scrubber tray packing flowrate shall be operated at a minimum of 700 gallons/minute. [District Rule 2201]
16. Quench flowrate shall be operated at 145 to 185 gallons/minute. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Except during start-up and shutdown periods, emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.014 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.0085 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,830 lb-NOx/year, 49.1 lb-CO/day, or 16,095 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
24. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
25. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

30. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

31. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
39. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. Daily records of the tray packing flowrate and the quench flowrate shall be maintained, retained on the premises for a period of at least five years, and made available for District inspection upon request. [District Rule 1070 and 2520, 9.5.2] Federally Enforceable Through Title V Permit
41. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
42. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
43. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
45. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
46. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
47. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-37-29 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-16 STRUTHERS THERMOFLOOD MODEL OH-50-ND-16XAM STEAM GENERATOR WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total gas consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Except during start-up and shutdown periods, emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.014 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,240 lb-NOx/year, 85.6 lb-CO/day, or 16,939 lb-CO/year. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-38-34 **EXPIRATION DATE:** 12/31/2016

SECTION: 25D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-17 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total fuel consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 14 ppmvd NOx @ 3% O2, or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2, or 0.037 lb-CO/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,332 lb-NOx/yr, 51.9 lb-CO/day, or 16,939 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-39-26 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG-25-18 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total gas consumption shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Except during startup and shutdown, emissions from this unit shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.0520 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu, 0.0520 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, nor 0.008 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

20. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

38. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

42. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-40-25 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-19 NATURAL GAS STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Emissions from this unit shall not exceed any of the following limits: 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

15. Except during startup and shutdown, emissions from this unit shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District NSR Rule and District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, nor 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-41-25 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-20 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR), SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total LPG, casing gas, waste gas, and natural gas consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Whenever well casing vapors and/or tank vapor recovery gas are being burned in this unit, the SO2 scrubber shall operate and shall reduce SO2 emissions by 95% by weight, or shall limit exhaust SO2 to less than or equal to 9 ppmv corrected to 3.0% oxygen. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. PUC quality gas with sulfur content shall not exceeding 1 gr S/100 scf shall be combusted in this unit whenever the scrubber is not being operated. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Emissions from this unit shall not exceed any of the following limits: 0.052 lb-SOx/MMBtu, 0.044 lb-PM10/MMBtu, or 0.0085 lb-VOC/MMBtu. [District Rules 2201 and 4320]

15. Except during startup and shutdown, emissions from this unit shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.044 lb-PM10/MMBtu, 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu, or 0.0085 lb-VOC/MMBtu. [District NSR Rule and District Rules 4305, 4306, and 4320]

16. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu, 0.052 lb-SOx/MMBtu, 0.044 lb-PM10/MMBtu, 0.084 lb-CO/MMBtu, nor 0.0085 lb-VOC/MMBtu. [District Rule 2201]

17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

21. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

22. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Permittee shall measure and record the BTU content of the gas burned at the time of NOx testing, except for natural gas purchased from a PUC regulated utility. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

43. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-42-20 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-21 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
5. This unit shall be fired exclusively on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
7. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
11. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day or 7390 lb-NOx/yr. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

17. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C ; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

20. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

33. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-43-18 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-22 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16AXM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
5. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
9. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
10. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,825 lb-NOx/yr, 51.9 lb-CO/day, and 16,084 lb-CO/yr. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

16. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C ; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Operator shall provide an annual fuel analysis to the District. [District Rule 4320] Federally Enforceable Through Title V Permit

19. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

32. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-45-18 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 25-24 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16AXM, WITH FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
5. This unit shall be fired exclusively on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
7. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.045 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
11. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,825 lb-NOx/yr, 51.9 lb-CO/day, and 16,084 lb-CO/yr. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

17. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C ; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

20. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

33. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

37. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-46-18 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 25-25 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN 4131-G-LNX BURNER WITH FLUE GAS

PERMIT UNIT REQUIREMENTS

1. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
2. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305] Federally Enforceable Through Title V Permit
3. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081] Federally Enforceable Through Title V Permit
4. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of a compliant DEU. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
10. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6B; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
12. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
13. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
14. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
15. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
17. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
18. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
19. The flue gas recirculation system shall be operated in accordance with the manufacturer's directions whenever the steam generator is operating. [District NSR Rule] Federally Enforceable Through Title V Permit
20. This unit shall be fired exclusively with natural gas or LPG. [District NSR Rule] Federally Enforceable Through Title V Permit
21. Natural gas or LPG consumption shall not exceed 1404 MMBtu/day nor 434,700 MMBtu/year. [District NSR Rule] Federally Enforceable Through Title V Permit
22. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the boiler. [District NSR Rule] Federally Enforceable Through Title V Permit
23. Emissions shall not exceed any of the following limits: NOx - 0.036 lb/MMBtu, SOx - 0.052 lb/MMBtu, CO - 0.035 lb/MMBtu, and PM-10 - 0.045 lb/MMBtu. [District NSR Rule and 4305] Federally Enforceable Through Title V Permit
24. Emissions shall not exceed any of the following limits: NOx - 50.5 lb/day, SOx - 72.96 lb/day, CO - 49.0 lb/day, and PM10 - 63.12 lb/day. [District NSR Rule and 4305] Federally Enforceable Through Title V Permit
25. This unit shall be tested for compliance with NOx emissions limit not less than once every 12 months. Source testing shall not be required if the unit did not operate during the previous 12 month period. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every 36 months. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
27. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
28. The stack concentration of NOx (as NO2), CO, and O2 shall be measured at least on a monthly basis using District approved portable analyzers. Monitoring shall not be required if the unit is not in operation during any given month, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the steam generator unless monitoring has been performed within the last month. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
29. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2, and the O2 concentration. The records must also include a description of any corrective action taken to maintain the emissions within the acceptable range and shall identify the months of non-operation for any unit to validate extended monitoring frequencies. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
30. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the allowable emissions rate, the permittee shall notify the District and take corrective action within one (1) hour after detection. If the portable analyzer readings continue to exceed the allowable emissions rate, the permittee shall conduct an emissions test within 60 days, utilizing District-approved test methods, to demonstrate compliance with the applicable emissions limits. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
31. The portable analyzer shall be calibrated as recommended by the manufacturer. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 6 months prior to the date the stack concentrations are measured and recorded. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
32. Concentration measurements shall not be taken until the sample acquisition probe has been exposed to the stack gas for at least 150% of the response time. Measurements shall be taken in triplicate. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
33. If water vapor is not removed prior to measurement, the absolute humidity in the gas stream must be determined so that the gas concentrations may be reported on a dry basis. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
34. If water vapor creates an interference with the measurement of any component, then the water vapor must be removed from the gas stream prior to concentration measurements. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit
35. Permittee shall record daily natural gas and propane consumption. Records shall be provided to the District upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
36. Natural gas or LPG sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source; or natural gas or LPG shall be tested for sulfur content and higher heating value (hhv) monthly. [District NSR Rule] Federally Enforceable Through Title V Permit
37. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District NSR Rule] Federally Enforceable Through Title V Permit
38. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
39. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
40. Source testing shall be performed for NOx (ppmv) according to EPA method 7E (or ARB Method 100) and EPA Method 10 (or ARB Method 100) for CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Annual test results to the District from unit(s) representing a group of units may be used to measure NOx emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. [District Rule 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

42. The following conditions must be met for representative unit(s) to be used to test for NOx limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.4.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

43. All units in a group for which representative units are source for NOx emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). Records shall be maintained for the each unit of the group including all preventative and corrective maintenance work done. [District Rule, 9.4.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

44. All units in a group for which representative units are source tested for NOx emissions for this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

45. The number of representative units source tested for NOx emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-47-12 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 25-26 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16-XAM, WITH A NORTH AMERICAN BURNER, MODEL 4131-G-LNX, AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. This permit unit shall not be operated unless the owner or operator applies to modify the Title V permit to address the requirements of District Rule 2520, section 9.0 for this permit unit. [District Rule 2520, 9.0] Federally Enforceable Through Title V Permit
2. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
3. The emissions shall not exceed 30 ppm NOx (0.036 lb-NOx/MMBtu) @ 3% O2. [District Rule 4305]
4. No modification to this unit shall be performed without an Authority to Construct for that modification(s), except for changes specified in condition 5. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
5. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305] Federally Enforceable Through Title V Permit
6. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081] Federally Enforceable Through Title V Permit
7. Natural gas consumption shall not exceed 1.34 million scf/day or 414 million scf/year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively with natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
9. LPG consumption shall not exceed 1,404 MMBtu/day nor 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The flue gas recirculation system shall be operated whenever the generator is in use. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions shall not exceed the following limits: CO - 0.034 lb/MMBtu, SOx - 0.052 lb/MMBtu, or PM-10 - 0.045 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions shall not exceed the following limits: NOx - 50.5 lb/day, SOx - 72.96 lb/day, or PM10 - 63.12 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall record natural gas and propane consumption. Records shall be retained for at least two years and provided to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. This unit shall be tested for compliance with NOx emissions limit not less than once every 12 months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. [District Rule 4305] Federally Enforceable Through Title V Permit
15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
16. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-48-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-27, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Total fuel consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum NOx emissions from the steam generator, including start-up and shutdown, shall not exceed 46.3 lb-NOx/day. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using test methods listed on this permit. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by a third party supplier or tested in accordance with procedures outlined in this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx and CO emissions from this unit shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-49-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-28, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Total fuel consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum NOx emissions from the steam generator, including start-up and shutdown, shall not exceed 46.3 lb-NOx/day. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using test methods listed on this permit. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by a third party supplier or tested in accordance with procedures outlined in this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx and CO emissions from this unit shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-50-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-29, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
8. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Total fuel consumption shall not exceed 435,000 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.004 lb-PM10/MMBtu, or 0.003 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum NOx emissions from the steam generator, including start-up and shutdown, shall not exceed 46.3 lb-NOx/day. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using test methods listed on this permit. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by a third party supplier or tested in accordance with procedures outlined in this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. NOx and CO emissions from this unit shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

24. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

38. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

40. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-51-20 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 6-31 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN 4131-G-LNX BURNER WITH FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
2. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305] Federally Enforceable Through Title V Permit
3. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081] Federally Enforceable Through Title V Permit
4. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of a compliant DEU. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
10. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6B; or Method 8 or ARB Method 1-100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
12. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
13. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
14. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
15. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
17. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
18. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
19. The flue gas recirculation system shall be operated in accordance with the manufacturer's directions whenever the steam generator is operating. [District NSR Rule] Federally Enforceable Through Title V Permit
20. This unit shall be fired exclusively with natural gas or LPG. [District NSR Rule] Federally Enforceable Through Title V Permit
21. Natural gas or LPG consumption shall not exceed 1404 MMBtu/day nor 434700 MMBtu/year. [District NSR Rule] Federally Enforceable Through Title V Permit
22. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the boiler. [District NSR Rule] Federally Enforceable Through Title V Permit
23. Emissions shall not exceed any of the following limits: NO2 - 50.5 lb/day, SO2 - 4.56 lb/day, PM10 - 9.48 lb/day, CO - 48.0 lb/day, and VOC (NMHC) - 12.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
24. Emissions shall not exceed any of the following limits: NO2 - 0.036 lb/MMBtu, SO2 - 0.003 lb/MMBtu, VOC - 0.003 lb/MMBtu, and CO - 0.035 lb/MMBtu. [District NSR Rule] Federally Enforceable Through Title V Permit
25. This unit shall be tested for compliance with NOx emissions limit not less than once every 12 months. Source testing shall not be required if the unit did not operate during the previous 12 month period. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every 36 months. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

27. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The stack concentration of NOx (as NO2), CO, and O2 shall be measured at least on a monthly basis using District approved portable analyzers. Monitoring shall not be required if the unit is not in operation during any given month, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the steam generator unless monitoring has been performed within the last month. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of the date and time of NOx, CO, and O2 measurements, the measured NO2 and CO concentrations corrected to 3% O2, and the O2 concentration. The records must also include a description of any corrective action taken to maintain the emissions within the acceptable range and shall identify the months of non-operation for any unit to validate extended monitoring frequencies. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

30. If the NOx or CO concentrations, as measured by the portable analyzer, exceed the allowable emissions rate, the permittee shall notify the District and take corrective action within one (1) hour after detection. If the portable analyzer readings continue to exceed the allowable emissions rate, the permittee shall conduct an emissions test within 60 days, utilizing District-approved test methods, to demonstrate compliance with the applicable emissions limits. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

31. The portable analyzer shall be calibrated as recommended by the manufacturer. All instrument calibration data shall be kept on file including the date of calibration. The calibration date shall not exceed 6 months prior to the date the stack concentrations are measured and recorded. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

32. Concentration measurements shall not be taken until the sample acquisition probe has been exposed to the stack gas for at least 150% of the response time. Measurements shall be taken in triplicate. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

33. If water vapor is not removed prior to measurement, the absolute humidity in the gas stream must be determined so that the gas concentrations may be reported on a dry basis. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

34. If water vapor creates an interference with the measurement of any component, then the water vapor must be removed from the gas stream prior to concentration measurements. [District Rule 2520, 9.4.2 and 4305] Federally Enforceable Through Title V Permit

35. Permittee shall record daily natural gas and propane consumption. Records shall be provided to the District upon request. [District NSR Rule] Federally Enforceable Through Title V Permit

36. Natural gas or LPG sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source; or natural gas or LPG shall be tested for sulfur content and higher heating value (hhv) monthly. [District NSR Rule] Federally Enforceable Through Title V Permit

37. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District NSR Rule] Federally Enforceable Through Title V Permit

38. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

39. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

40. Source testing shall be performed for NOx (ppmv) according to EPA method 7E (or ARB Method 100) and EPA Method 10 (or ARB Method 100) for CO. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Annual test results to the District from unit(s) representing a group of units may be used to measure NOx emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. [District Rule 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

42. The following conditions must be met for representative unit(s) to be used to test for NOx limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.4.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

43. All units in a group for which representative units are source for NOx emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). Records shall be maintained for the each unit of the group including all preventative and corrective maintenance work done. [District Rule, 9.4.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

44. All units in a group for which representative units are source tested for NOx emissions for this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.4.2, and 4305, 6.3.2] Federally Enforceable Through Title V Permit

45. The number of representative units source tested for NOx emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-52-19 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG STRUTHERS THERMOFLOOD STEAM GENERATOR #6-32, MODEL 0H-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. This unit shall be fired exclusively on PUC-quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
6. Total fuel consumption of this unit shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in the fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801] Federally Enforceable Through Title V Permit
11. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.005 lb-PM10/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,240 lb-NOx/yr, 51.9 lb-CO/day, and 16,939 lb-CO/yr. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.4.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

22. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

25. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]

27. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

29. Sampling facilities for source testing shall be provided in accordance with the provisions of rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

30. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Natural gas sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source or natural gas shall be tested for sulfur content and higher heating value (hhv) monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

35. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320]
37. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit
39. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-53-20 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS THERMOFLOOD STEAM GENERATOR MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER, AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. This unit shall be fired exclusively with natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
6. Total fuel consumption of this unit shall not exceed 457,800 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in the fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801] Federally Enforceable Through Title V Permit
11. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
12. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.005 lb-PM10/MMBtu, or 0.008 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 8,240 lb-NOx/yr, 51.9 lb-CO/day, and 16,939 lb-CO/yr. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.4.2 and 4320] Federally Enforceable Through Title V Permit

19. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

20. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

22. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

23. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4320] Federally Enforceable Through Title V Permit

24. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

26. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]

27. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

29. Sampling facilities for source testing shall be provided in accordance with the provisions of rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit

30. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

33. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

34. Natural gas sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source or natural gas shall be tested for sulfur content and higher heating value (hhv) monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

37. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

38. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

39. Copies of all , gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-76-18 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
58.5 MMBTU/HR SG 6-38 NATURAL/LPG/TEOR GAS-FIRED STRUTHERS THERMOFLOOD MODEL OH-50-ND-16XAM STEAM GENERATOR WITH A NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit shall be fired on PUC-quality natural gas, LPG, well casing gas, tank vapor recovery (TVR) gas, or any mixture of these fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total fuel consumption shall not exceed either of the following limits: 1,404 MMBtu/day or 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the steam generator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rules 4320 and 4801] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.00675 lb-PM10/MMBtu or 0.0085 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. Except during start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 15 ppmvd NOx @ 3% O2, equivalent to 0.018 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2, equivalent to 0.037 lb-CO/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,825 lb-NOx/yr, 66.4 lb-CO/day, or 16,084 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Fuel sulfur content and higher heating value (hhv) of each fuel source shall be certified by third party fuel supplier or tested in accordance with procedures outlined on this permit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

12. If the unit is fired on noncertified gaseous fuel, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

13. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. Source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The results of each source test shall be submitted to the District within 60 days after the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

24. All instrument calibration data shall be kept on file including the date of calibration . The calibration date shall not exceed 3 months prior to the date the stack concentrations are measured and recorded. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Copies of all gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

33. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-77-7 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 91 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-2-13D WITH LOW PRESSURE SCRUBBER-SEPARATOR, AIR COOLER AND CONDENSATE COLLECTOR (13D NORTHEAST)

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Sections 13, T20S, R14E and Section 18, T20S R15E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the low pressure scrubber-separator and the air cooler is optional. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

45. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

46. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

47. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

48. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

49. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. Permittee shall maintain a current roster of all wells connected to this system. [District NSR Rule and 4401] Federally Enforceable Through Title V Permit

52. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

53. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-78-5 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 149 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-4-13D WITH SCRUBBER, FIN-FAN AIR COOLER AND CONDENSATE COLLECTOR (13D NORTHWEST)

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations Sections 12 and 13, T20S, R14E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the fin-fan air cooler is optional. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit
23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit
24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit
25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit
26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit
29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit
30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit
31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit
32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit
33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District NSR Rule and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-79-19 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TEOR OPERATION #CC-1-25D WITH 491 STEAM ENHANCED WELLS WITH TWO 100 HP COMPRESSORS, SEPARATOR, CONDENSATE COLLECTOR AND PIPING FROM TEOR OPERATION #6C-CC-1 (C-311-112) AND PRESSURE VESSEL C-311-240

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Sections 24, 25, and 36, T20S, R14E and Sections 19, 30, T20S, R15E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the 100 hp compressor is optional. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit
23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit
24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit
25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit
26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit
29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit
30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit
31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit
32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit
33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by the APCO, a VOC collection and control system is not subject to Section 6.2.1 if all uncondensed VOC emissions collected by the system are controlled by a device meeting one of the following requirements: 1) An internal combustion engine subject to District Rule 4702 (Internal Combustion Engines - Phase 2); 2) A combustion device subject to District Rule 4320 (Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr); District Rule 4307 (Boilers, Steam Generators, and Process Heaters - 2.0 MMBtu/hr to 5.0 MMBtu/hr); or District Rule 4308 (Boilers, Steam Generators, and Process Heaters - 0.075 MMBtu/hr to 2.0 MMBtu/hr); or 3) A unit subject to District Rule 4311 (Flares). [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District NSR Rule and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-83-21 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20 **RANGE:** 14

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 596 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-3-13D WITH SCRUBBER, FIN-FAN AIR COOLER, COMPRESSOR, AND CONDENSATE COLLECTOR, WITH CLOSED CASING VENTS OR VENTING TO A BALANCED PIPING SYSTEM OR STEAM GENERATORS APPROVED BY DISTRICT FOR TEOR GAS INCINERATION OR DOGGR APPROVED VAPOR DISPOSAL WELL(S) (13D SOUTHWEST)

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Sections 13 and 24, T20S, R14E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation of the fin-fan air cooler is optional. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR. approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by the APCO, a VOC collection and control system is not subject to Section 6.2.1 if all uncondensed VOC emissions collected by the system are controlled by a device meeting one of the following requirements: 1) An internal combustion engine subject to District Rule 4702 (Internal Combustion Engines - Phase 2); 2) A combustion device subject to District Rule 4320 (Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr); District Rule 4307 (Boilers, Steam Generators, and Process Heaters - 2.0 MMBtu/hr to 5.0 MMBtu/hr); or District Rule 4308 (Boilers, Steam Generators, and Process Heaters - 0.075 MMBtu/hr to 2.0 MMBtu/hr); or 3) A unit subject to District Rule 4311 (Flares). [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

50. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District NSR Rule and 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-84-18 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR SG 6-37 STRUTHERS THERMOFLOOD STEAM GENERATOR MODEL OH5O-ND-16XAM WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. The permittee shall install and maintain a non-resettable, totalizing mass or volumetric flow meter in each fuel line to the boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This unit shall be fired on PUC-quality natural gas, LPG, or a blend of PUC-quality natural gas and well casing and tank vapor recovery (TVR) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas shall not contain more than 5 grains of total sulfur per 100 standard cubic feet. [District Rule 4320]
6. Fuel gas sulfur content shall not exceed 1 gr S/100 scf unless SOx is reduced by 95% or to 9 ppmv SOx @ 3% O2 in exhaust with scrubber. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Total fuel consumption shall not exceed 434,700 MMBtu/year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grain/dscf, 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
9. Nitrogen oxide (NOx) emissions shall not exceed 140 lb/hr, calculated as NO2. [District Rules 4301, 5.2.2, 5.3, and 5.5 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. Emissions of sulfur compounds from this unit shall not exceed 200 lb/hr, calculated as SO2. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas or by testing the sulfur content of each fuel and determining the maximum hourly emissions of sulfur compounds by multiplying the sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by source testing in combination with fuel analysis. [District Rules 2520, 9.4.2 and 4301, 5.2.1] Federally Enforceable Through Title V Permit
11. Emissions from the steam generator shall not exceed any of the following limits: 0.0143 lb-SOx/MMBtu, 0.00675 lb-PM10/MMBtu, or 0.00855 lb-VOC/MMBtu. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
12. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 14 ppmvd NOx @ 3% O2 or 0.017 lb-NOx/MMBtu or 50 ppmvd CO @ 3% O2 or 0.037 lb-CO/MMBtu. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. During start-up and shutdown periods emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 50.5 lb-NOx/day, 7,390 lb-NOx/yr, 66.4 lb-CO/day, and 16,084 lb-CO/yr. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2520, 9.4.2 and 4320] Federally Enforceable Through Title V Permit

18. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 and EPA Method 6C; or ARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or a grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months, however annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

19. Operator shall provide an annual fuel analysis to the District. [District Rule 4320]

20. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

22. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

23. NOx, and CO emissions shall be measured with source testing conducted by independent testing laboratory and shall be witnessed or authorized by the District [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

27. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by: D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 4306, 4320, and 4351, 6.2.1] Federally Enforceable Through Title V Permit

28. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

31. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. Natural gas or LPG sulfur content and higher heating value (hhv) shall be certified by a third party fuel supplier of each fuel source; or natural gas or LPG shall be tested for sulfur content and higher heating value (hhv) monthly. Casing gas shall be tested for sulfur content and higher heating value (hhv) not less than monthly. [District Rule 2201] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

35. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

36. Permittee shall maintain records of higher heating value (hhv), in MMBtu/scf, for each gaseous fuel used in this operation. [District Rule 2201] Federally Enforceable Through Title V Permit

37. Copies of all, gas purchase contracts, supplier certifications, and test results to determine compliance with the conditions of this permit shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted, fuel source, and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of District Rules 1081 (Amended December 16, 1993), 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-88-15 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-104, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A RENTECH WASTE HEAT RECOVERY STEAM GENERATOR, WITH A 37 MMBTU/HR JOHN ZINC HAMWORTHY COMBUSTION DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b), District Rule 4703] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201] Federally Enforceable Through Title V Permit

12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081] Federally Enforceable Through Title V Permit

13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081] Federally Enforceable Through Title V Permit

16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, CFR 60.335(a)] Federally Enforceable Through Title V Permit

17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081] Federally Enforceable Through Title V Permit

18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit

19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rule 2201 and 4703] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. The results of each source test shall be submitted to the District within 60 days of the source test. [District Rule 1081] Federally Enforceable Through Title V Permit

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, 40 CFR 60.334(b)(1)] Federally Enforceable Through Title V Permit

22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)] Federally Enforceable Through Title V Permit

23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)] Federally Enforceable Through Title V Permit

24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080] Federally Enforceable Through Title V Permit

25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, 40 CFR 60.334(b)(1)] Federally Enforceable Through Title V Permit

26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080] Federally Enforceable Through Title V Permit

27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)] Federally Enforceable Through Title V Permit

28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080] Federally Enforceable Through Title V Permit

29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080] Federally Enforceable Through Title V Permit

30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201 and 40 CFR 60.8(d)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)] Federally Enforceable Through Title V Permit

32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)1)(iii)(B)] Federally Enforceable Through Title V Permit

33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)] Federally Enforceable Through Title V Permit

34. Should the applicant decide to conduct performance evaluation of CEMS with the initial performance test, a minimum of 9 reference method runs, with a minimum time per run of 21 minutes, at a single load level, between 90 and 100 percent of peak (or the highest physically achievable) load shall be performed. The test data obtained during these runs can be used to demonstrate compliance with the applicable NOx emission limit and to provide reference method data for the RATA of the CEMS. The requirement to test at three additional load levels is waived under this option. [40 CFR 60.335(b)(6)] Federally Enforceable Through Title V Permit

35. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

36. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

37. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

38. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703] Federally Enforceable Through Title V Permit

39. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703] Federally Enforceable Through Title V Permit

40. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703] Federally Enforceable Through Title V Permit

41. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit

42. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

43. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703] Federally Enforceable Through Title V Permit

45. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

46. The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirement: 40 CFR 60.332(a), 60.335 (a), (b) and (c) . A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

49. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-93-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-101, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-201, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b), District Rule 4703] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703]
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201]
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201]
9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201]
11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201]
12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081]
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years thereafter. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081]
16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, CFR 60.335(a)]
17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081]
18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit
19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rule 2201 and 4703] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, 40 CFR 60.334(b)(1)]
22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)]
23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)]
24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080]
25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, 40 CFR 60.334(b)(1)]
26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080]
27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)]
28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080]
29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080]
30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201 and 40 CFR 60.8(d)]
31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)1)(iii)(B)]

33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)]

34. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703]

35. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703]

36. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703]

37. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703]

38. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703]

39. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703]

40. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit

41. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703]

42. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703]

43. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703]

44. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

45. The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirement: 40 CFR 60.332(a), 60.335 (a), (b) and (c) . A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-95-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-102, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-202, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b), District Rule 4703] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703]
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201]
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201]
9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201]
11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201]
12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081]
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years thereafter. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081]
16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, CFR 60.335(a)]
17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081]
18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit
19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rule 2201 and 4703] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, 40 CFR 60.334(b)(1)]
22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)]
23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)]
24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080]
25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, 40 CFR 60.334(b)(1)]
26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080]
27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)]
28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080]
29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080]
30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201 and 40 CFR 60.8(d)]
31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)1)(iii)(B)]

33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)]

34. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703]

35. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703]

36. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703]

37. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703]

38. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703]

39. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703]

40. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit

41. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703]

42. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703]

43. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703]

44. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

45. The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirement: 40 CFR 60.332(a), 60.335 (a), (b) and (c) . A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-97-13 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-103, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-203, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. If the gas turbine system is fired on PUC-regulated or FERC regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on natural gas as defined in 40 CFR 60.331(u) and the natural gas shall have a total sulfur content less than or equal to 1.0 gr/100 scf. [40 CFR 60.333(b) and District Rules 2201 and 4201] Federally Enforceable Through Title V Permit
4. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334(h)(3)] Federally Enforceable Through Title V Permit
5. HHV and LHV of the fuel shall be determined by using ASTM D3588, ASTM 1826, or ASTM 1945. [40 CFR 60.335(b), District Rule 4703] Federally Enforceable Through Title V Permit
6. Emissions from the gas turbine system, when startup or shutdown or black start do not occur, shall not exceed any of the following limits: 9 ppmvd NOx @ 15% O2 referenced as NO2; 53 ppmvd CO @ 15% O2 when firing both gas turbine and duct burner simultaneously; 63 ppmvd CO @ 15% O2 when firing gas turbine only; 0.026 lb-PM10/MMBtu; 0.026 lb-VOC/MMBtu referenced as methane; and 0.002 lb-SOx/MMBtu referenced as SO2. NOx and CO emission limits are based on 3-hour rolling average period. If unit is in either startup, shutdown, or black start mode during any portion of a clock hour, the unit will not be subject to the ppmvd limits for NOx and CO during that clock hour. [District Rules 2201 and 4703]
7. Emissions from the gas turbine system, on days when startup, shutdown, or black start occurs, shall not exceed any of the following limits: 67.4 lb-NOx/day referenced as NO2; 1199.5 lb-CO/day; 3.7 lb-SOx/day; 48.2 lb-PM10/day; 99.6 lb-VOC/day referenced as methane; and 52.7 lb-NH3/day. [District Rule 2201]
8. Emissions from the gas turbine system shall not exceed any of the following limits: 22,343 lb-NOx/year; 84,878 lb-CO/year; 1,354 lb-SOx/year; 17,606 lb-PM10/year; 17,863 lb-VOC/year; 19,239 lb-NH3/year. All annual emission limits are based on 12 consecutive month rolling emissions totals. [District Rule 2201]
9. Ammonia (NH3) emissions shall not exceed 21 ppmvd @ 15% O2 over a 24-hour average period. [District Rule 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Each three hour rolling average will be compiled from the three most recent one hour periods. Each one hour period shall commence on the hour. Each one hour period in a twenty-four hour average for ammonia slip will commence on the hour. The twenty-four hour average will be calculated starting and ending at twelve-midnight. [District Rule 2201]

11. Daily emissions shall be compiled for a twenty-four hour period starting and ending at twelve-midnight. Each calendar month in a twelve consecutive month rolling emissions total shall commence at the beginning of the first day of the month. The twelve consecutive month rolling emissions totals used to determine compliance with annual emission limits shall be compiled from the twelve most recent calendar months. [District Rule 2201]

12. The exhaust stack shall be equipped with permanent provisions to allow collection of stack gas samples consistent with EPA test methods and shall be equipped with safe permanent provisions to sample stack gases with a portable NOx, CO, and O2 analyzer during District inspections. The sampling ports shall be located in accordance with the CARB regulation titled California Air Resources Board Air Monitoring Quality Assurance Volume VI, Standard Operating Procedures for Stationary Emission Monitoring and Testing. [District Rule 1081]

13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

14. Source testing shall be witnessed or authorized by District personnel and samples shall be collected by a California Air Resources Board (CARB) certified testing laboratory or a CARB certified source testing firm. [District Rule 1081] Federally Enforceable Through Title V Permit

15. Source testing to measure start-up mass emission rates of NOx, CO, and VOC shall be conducted for one of the gas turbine engines (C-311-88, -93, -95 or -97) at least once every seven years thereafter. CEMS relative accuracy shall be determined during source testing in accordance with the procedure listed in 40 CFR Part 60, Appendix F with any necessary changes approved by the District. [District Rule 1081]

16. Source testing to determine compliance with the NOx, CO and NH3 emission rates (ppmvd @ 15% O2) during normal operation shall be conducted annually. [District Rules 2201 and 4703, CFR 60.335(a)]

17. For the purpose of determining compliance with the emissions limits (ppmvd @ 15% O2) during normal operation in this permit, the arithmetic mean of three test runs shall apply, unless two of the three results are above an applicable limit. If two of three runs are above the applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 1081]

18. The following test methods shall be used: NOx - EPA Method 7E or 20 or CARB Method 100; CO - EPA Method 10 or 10B or CARB Method 100; VOC - EPA Method 18 or 25; PM10 - EPA Method 5 (front half and back half) or 201 and 202a; ammonia - BAAQMD ST-1B; and O2 - EPA Method 3, 3A, or 20 or CARB Method 100. EPA approved alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rules 1081 and 4703, 40 CFR 60.335(a), and 40 CFR 60.335(b)(1)] Federally Enforceable Through Title V Permit

19. Source test to demonstrate compliance with NOx and CO emission limits shall be conducted with duct burner "on" and "off" configurations. An annual demonstration of compliance with the duct burner in operation is not required in any year in which the duct burner is not operated at all in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of resumption of operation of the duct burner. An annual demonstration of compliance with the duct burner not in operation is not required in any year in which the duct burner operated continuously in conjunction with the turbine in the preceding 12 months, in such case, the unit shall be compliance source tested within 60 days of shutdown of operation of the duct burner. [District Rule 2201 and 4703] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The owner or operator shall install, certify, maintain, operate, and quality-assure a continuous emission monitor system (CEMS) which continuously measures and records the exhaust gas NOx, CO, and O2 concentrations. Continuous emissions monitors shall be capable of monitoring emissions during normal operating conditions and during startups and shutdowns, provided that CEMS passes the relative accuracy requirements of 40 CFR Part 60, Appendix B, Performance Specification 2 (PS-2) and District approved protocol for startups. If relative accuracy of CEMS cannot be demonstrated during the startup, CEMS results during startup and shutdown events shall be replaced with startup emission rates obtained from the source test conducted by the facility to determine compliance with emission limits contained in this document. [District Rules 1080, 2201 and 4703, 40 CFR 60.334(b)(1)]
22. The CEMS shall complete a minimum of one cycle of operation (sampling, analyzing, and data recording) for each 15-minute quadrant of the hour or shall meet equivalent specifications established by mutual agreement of the District, the CARB and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(2)]
23. The NOx, CO and O2 CEMS shall meet the requirements in 40 CFR 60, Appendix F Procedure 1 and Part 60, Appendix B Performance Specification 2 (PS 2), District approved protocol for startups, or shall meet equivalent specifications established by mutual agreement of the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(1)]
24. In accordance with 40 CFR Part 60, Appendix F, 5.1, the CEMS must be audited at least once each calendar quarter. The District shall be notified prior to completion of the audits. Audit reports shall be submitted along with quarterly compliance reports to the District. [District Rule 1080]
25. The requirements in 40 CFR 60, Appendix F, shall be met through the following EPA and District approved modified procedures: 1) annual RATA testing of at least one gas turbine engine (C-311-88, -93, -95 or -97), and rotate the unit tested so that all four units are tested over four years, 2) annual RAA testing for the three gas turbine engines for which the annual RATA testing is not performed, 3) if any of the gas turbine engines fail the RAA testing, they must have a RATA test within 60 days, and 4) for every quarter that RATA or RAA testing is not performed, a CGA is to be performed for each gas turbine engine. [District Rules 1080 and 4703, 40 CFR 60.334(b)(1)]
26. APCO or an authorized representative shall be allowed to inspect, as determined to be necessary, the required monitoring devices to ensure that such devices are functioning properly. [District Rule 1080]
27. The CEMS data shall be reduced to hourly averages as specified in 40 CFR 60.13(h), or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [District Rule 1080 and 40 CFR 60.334(b)(3)]
28. Upon written notice from the District, the owner or operator shall provide a summary of the data obtained from the CEMS. This summary shall be in the form and the manner prescribed by the District. [District Rule 1080]
29. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEMS data polling software system, or a District approved alternative polling method, and shall make CEMS data available to the District on a daily basis. Upon notice by the District that the facility's CEMS is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEMS data is sent to the District by a District-approved alternative method. [District Rule 1080]
30. The permittee shall maintain the following records: the date, time and duration of any malfunction of the continuous monitoring equipment; dates of performance testing; dates of evaluations, calibrations, checks, and adjustments of the continuous monitoring equipment; date and time period which a continuous monitoring system or monitoring device was inoperative. [District Rules 1080 and 2201 and 40 CFR 60.8(d)]
31. The owner or operator shall submit a written report of CEM operations for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter and shall include the following: Time intervals, data and magnitude of excess NOx emissions, nature and the cause of excess (if known), corrective actions taken and preventive measures adopted; Averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; Applicable time and date of each period during which the CEM was inoperative, except for zero and span checks, and the nature of system repairs and adjustments; A negative declaration when no excess emissions occurred. [District Rule 1080 and 40 CFR 60.334(j)(5)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Monitor downtime for NOx shall be any unit operating hour in which sufficient data are not obtained to validate the hour for either NOx concentration or diluent O2 (or both). [40 CFR 60.334(j)1)(iii)(B)]

33. If the gas turbine system is not fired on PUC-regulated or FERC regulated natural gas, then a fuel sample shall be collected during the source test to determine sulfur content of the fuel combusted in the turbine. The fuel sample shall be analyzed for the total sulfur content using ASTM D1072; D3031; D3246; D4084; D4468; D6228; or D6667; or double GC for H2S and mercaptans. The applicable ranges of some ASTM methods are not adequate to measure the levels of sulfur in some fuel gases. Dilution of samples before analysis (with verification of dilution ratio) may be used after getting a prior approval from the District. [40 CFR 60.335(b)(10)]

34. A totalizing mass or volumetric fuel flow computer shall be utilized and maintained to calculate the amount of natural gas combusted based on measured flow meter parameters (fuel pressure and temperature) and gas composition. [District Rules 2201 and 4703]

35. Except during black start, each startup shall not exceed two hours per event. [District Rules 2201 and 4703]

36. Each shutdown shall not exceed two hours per event. [District Rules 2201 and 4703]

37. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup (black start) and shutdown. [District Rule 4703]

38. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rule 4703]

39. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4703]

40. Reduced load period is defined as the time during which a gas turbine is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. Each reduced load period shall not exceed one hour. [District Rule 4703] Federally Enforceable Through Title V Permit

41. A black start event is defined as the startup of a unit while the cogen plant is electrically separated from the utility grid. A black start event shall not exceed 4.0 hours. [District Rules 2201 and 4703]

42. The owner or operator shall submit to the District information correlating the NOx control system operating parameters to the associated measured NOx output. The information must be sufficient to allow the District to determine compliance with the NOx emission limits of this permit when the CEMS is not operating properly. [District Rule 4703]

43. The owner or operator shall maintain a stationary gas turbine system operating log that includes, on a daily basis, the actual local startup and stop time, length and reason for reduced load periods, total hours of operation, the type and quantity of fuel used, duration of each start-up (or black start) and each shutdown time period. [District Rule 4703]

44. The owner or operator shall maintain all records of required monitoring data and support information for a period of five years from the date of data entry and shall make such records available to the District upon request. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

45. The requirements of 40 CFR 72.6 (b) do not apply to this source because only non-Title IV sources can qualify to use the applicable template. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirement: 40 CFR 60.332(a), 60.335 (a), (b) and (c) . A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with the permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rule 4703, 6.2.4, 6.3, 6.4.1, 6.4.3 and 6.4.5. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4201 (as amended 12/17/92). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-105-4 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
118 CLOSED-VENT TEOR WELLS

PERMIT UNIT REQUIREMENTS

1. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801, 3.0] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1.1 and 5.1.2] Federally Enforceable Through Title V Permit
4. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
5. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
6. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

7. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

8. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

9. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

10. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

11. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

12. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

13. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

14. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

15. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

16. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

18. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

19. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

20. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

21. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

22. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

23. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

24. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

25. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed:. The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
27. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit
28. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
29. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
30. Permittee shall maintain a current well roster of all closed vent wells, and such roster shall be made readily available for District inspection upon request. [District 4401 Rule] Federally Enforceable Through Title V Permit
31. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-106-3 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
20 CLOSED-VENT TEOR WELLS

PERMIT UNIT REQUIREMENTS

1. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801, 3.0] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1.1 and 5.1.2] Federally Enforceable Through Title V Permit
4. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
5. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
6. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

7. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

8. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

9. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

10. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

11. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

12. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

13. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

14. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

15. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

16. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

18. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

19. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

20. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

21. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

22. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

23. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

24. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

25. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit
27. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit
28. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
29. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit
30. Permittee shall maintain a current well roster of all closed vent wells, and such roster shall be made readily available for District inspection upon request. [District 4401 Rule] Federally Enforceable Through Title V Permit
31. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-111-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TEOR OPERATION WITH 70 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-1-13D WITH SEPARATOR, LOW PRESSURE AIR COOLER AND CONDENSATE COLLECTOR (13 D SOUTHEAST)

PERMIT UNIT REQUIREMENTS

1. Operation of the low pressure air cooler is optional. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
3. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
4. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
5. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit
8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
9. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
10. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401, 4.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

12. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

13. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

15. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit

16. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.6] Federally Enforceable Through Title V Permit

17. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401, 4.0, 5.2.2] Federally Enforceable Through Title V Permit

19. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
21. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit
22. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit
23. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.5.2] Federally Enforceable Through Title V Permit
24. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit
25. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
26. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
27. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit
28. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit
29. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit
30. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit
31. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit
32. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

34. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

35. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401, 6.1.7] Federally Enforceable Through Title V Permit

36. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit

37. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401, 6.1.9] Federally Enforceable Through Title V Permit

38. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.10] Federally Enforceable Through Title V Permit

39. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

41. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

42. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

43. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

45. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

46. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

47. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

48. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

49. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. Permittee shall maintain a current roster of all wells connected to this system. [District NSR Rule and 4401] Federally Enforceable Through Title V Permit

52. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

53. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-112-16 **EXPIRATION DATE:** 12/31/2016

SECTION: 6C **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
TEOR OPERATION #6C-CC-1 SERVING 20 AUTOMATIC WELL TESTERS AND 326 STEAM-ENHANCED WELLS WITH LIQUID KNOCK OUT VESSEL (OPTIONAL) WITH DISTRICT-APPROVED VAPOR CONTROL SYSTEM

PERMIT UNIT REQUIREMENTS

1. TEOR wells are authorized to operate at the following locations: Section 6 Township 20S Range 15E; Section 31 Township 19S Range 15E; and Section 36 Township 19S Range 14E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The 6C-CC-1 system may be operated as a vapor balance system and/or an active well vent vapor recovery system. When operated as a vapor balance system, valves associated with the 6C-CC-1 system may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Maximum VOC content of the gas in the casing gas collection system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: (1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or (2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
5. Collected vapors shall be piped to 1) District steam generators approved by the District for TEOR gas incineration, or 2) DOGGR-approved vapor disposal well(s), or 3) balanced piping network. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
6. Permittee shall provide District with a copy of DOGGR approval for each vapor disposal well prior to use for vapor injection. [District Rule 1070 and 2520] Federally Enforceable Through Title V Permit
7. Operator shall test the VOC content of the TEOR vapors no less than annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

11. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

12. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401] Federally Enforceable Through Title V Permit

13. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

14. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

15. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401] Federally Enforceable Through Title V Permit

16. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401] Federally Enforceable Through Title V Permit

17. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401] Federally Enforceable Through Title V Permit

19. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. Notwithstanding the above, wells that are not operating are exempt from these requirements while undergoing service or repair. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
21. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401] Federally Enforceable Through Title V Permit
22. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401] Federally Enforceable Through Title V Permit
23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401] Federally Enforceable Through Title V Permit
24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit
25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401] Federally Enforceable Through Title V Permit
26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401] Federally Enforceable Through Title V Permit
27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401] Federally Enforceable Through Title V Permit
28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
29. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401] Federally Enforceable Through Title V Permit
31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401] Federally Enforceable Through Title V Permit
32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401] Federally Enforceable Through Title V Permit

35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401] Federally Enforceable Through Title V Permit

37. Operator shall keep a list of all gauge tanks, as defined in Section 3.17 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401] Federally Enforceable Through Title V Permit

38. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401] Federally Enforceable Through Title V Permit

40. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401] Federally Enforceable Through Title V Permit

42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401] Federally Enforceable Through Title V Permit

46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401] Federally Enforceable Through Title V Permit

47. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401] Federally Enforceable Through Title V Permit

48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

49. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401] Federally Enforceable Through Title V Permit

50. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit

52. Permittee shall maintain a current roster of all wells connected to this system. [District Rule 4401] Federally Enforceable Through Title V Permit

53. Records of the VOC content of the gas shall be maintained and made readily available for District inspection upon request for a period of 5 years. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

54. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-114-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 18 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 23 MMBTU/HR HOPPER STEAM GENERATOR, HSG-36, NATURAL GAS FIRED WITH ONE NORTH AMERICAN BURNER, DIS #21013-66

PERMIT UNIT REQUIREMENTS

1. This permit unit shall not be operated unless the owner or operator applies to modify the Title V permit to address the requirements of District Rule 2520, section 9.0 for this permit unit. [District Rule 2520, 9.0] Federally Enforceable Through Title V Permit
2. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305]
3. The emissions shall not exceed 30 ppm NOx (0.036 lb-NOx/MMBtu) @ 3% O2. [District Rule 4305]
4. No modification to this unit shall be performed without an Authority to Construct for that modification(s), except for changes specified in condition 5. [District Rule 2201]
5. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305]
6. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081]
7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. Natural gas consumption shall not exceed 526,000 cubic feet per day nor 192 million cubic feet per year. [District Rule 2201]
9. Fuel consumption shall be recorded on a daily basis. Records shall be retained for at least two years and made available to the District upon request. [District Rule 1070]
10. This unit shall be fired exclusively with natural gas. [District Rule 2201]
11. Daily emission limit shall not exceed: PM10 - 2.63 lb/day, SOx - 0.32 lb/day, NOx - 18.9 lb/day, CO - 18.4 lb/day, or VOC (NMHC) - 1.47 lb/day. [District Rule 2201]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-117-9 **EXPIRATION DATE:** 12/31/2016

SECTION: 18 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
NON-COMPLIANT DORMANT 23 MMBTU/HR HOPPER STEAM GENERATOR, HSG-1, NATURAL GAS FIRED, WITH ONE NORTH AMERICAN BURNER, DIS #5702-66

PERMIT UNIT REQUIREMENTS

1. This permit unit shall not be operated unless the owner or operator applies to modify the Title V permit to address the requirements of District Rule 2520, section 9.0 for this permit unit. [District Rule 2520, 9.0] Federally Enforceable Through Title V Permit
2. This equipment shall not be operated for any reason until necessary retrofits are made to comply with the applicable requirements of District Rule 4305. [District Rule 4305]
3. The emissions shall not exceed 30 ppm NOx (0.036 lb-NOx/MMBtu) @ 3% O2. [District Rule 4305]
4. No modification to this unit shall be performed without an Authority to Construct for that modification(s), except for changes specified in condition 5. [District Rule 2201]
5. The fuel supply line, water line and the electrical power output connection shall be physically disconnected from the unit. [District Rule 4305]
6. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 1081]
7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
8. Natural gas consumption shall not exceed 526,000 cubic feet per day nor 192 million cubic feet per year. [District Rule 2201]
9. Fuel consumption shall be recorded on a daily basis. Records shall be retained for at least two years and made available to the District upon request. [District Rule 1070]
10. This unit shall be fired exclusively with natural gas. [District Rule 2201]
11. Daily emission limit shall not exceed: PM10 - 2.63 lb/day, SOx - 0.32 lb/day, NOx - 18.9 lb/day, CO - 18.4 lb/day, or VOC (NMHC) - 1.47 lb/day. [District Rule 2201]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-122-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED PETROLEUM STORAGE TANK #T-101 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4623 (Amended December 17, 1992). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee may conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

51. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rule 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-123-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-102 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4623 (Amended December 17, 1992). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

51. Records of annual throughput of crude oil shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-124-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-103 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4623 (Amended December 17, 1992). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

52. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rule 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-125-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-400 SERVED BY SHARED VAPOR RECOVERY SYSTEM ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4623 (Amended December 17, 1992). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

52. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rule 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-126-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-300 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4623 (Amended December 17, 1992). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

52. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rule 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-127-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-200 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. The efficiency of any VOC destruction device shall be measured by EPA Method 18, 25, or 25a. [District Rule 4623, 6.4.7] Federally Enforceable Through Title V Permit

40. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

42. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4623 (Amended December 17, 1992). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

44. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

53. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rule 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-128-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
3,020 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-201 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4623 (Amended December 17, 1992). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

42. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

43. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

52. Records of annual throughput of crude oil shall be maintained, retained for a period of at least 5 years, and made available for District inspection upon request. [District Rule 1070, and 2520, 9.3.2, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-129-10 **EXPIRATION DATE:** 12/31/2016

SECTION: 6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-500 SERVED BY A VAPOR RECOVERY SYSTEM INCLUDING CONDENSER, COMPRESSOR, CONDENSATE COLLECTION VESSEL, TRANSFER PUMP AND BACK-UP/STANDBY ELECTRIC COMPRESSOR SERVED BY SHARED CASING COLLECTION SYSTEM FOR SECTION 6C - PERMIT UNIT C-311-112 AND TANK PERMIT UNITS C-311-122, -123, -124, -125, -126, -127, -128 AND -129

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District NSR Rule and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

9. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

10. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

11. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, after a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7]

31. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Identification and location of essential process units found leaking that cannot be repaired unit the next process unit turnaround; and 5) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. Except during tank cleaning and maintenance operations, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

41. Throughput of liquid to the storage tank shall not exceed 5.88 million gallons per year. [District NSR Rule] Federally Enforceable Through Title V Permit

42. VOC emissions from this tank shall not exceed 2.7 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

43. Vapor pressure of liquids stored shall not exceed 5 psia reid vapor pressure nor 3.6 psia true vapor pressure. [District NSR Rule] Federally Enforceable Through Title V Permit

44. Collected condensed vapors shall be returned to one of the storage tanks served by the vapor recovery system. [District NSR Rule] Federally Enforceable Through Title V Permit

45. Permittee shall record annual liquid throughput and true vapor pressure of the liquids stored. [District NSR Rule and 4623] Federally Enforceable Through Title V Permit

46. The vapor recovery system shall control the tanks identified in permit units C-311-122, -123, -124, -125, -126, -127, -128 and -129. [District NSR Rule and 4623] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 48 hours before tank cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. When storing liquids of TVP equal to or greater than 0.5 psia, prior to opening the tank to allow tank cleaning one of the following procedures must be followed: 1) operate the vapor recovery system for at least 24 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: t = 2.3 V / Q, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP less than 0.5 psia, prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, within 48 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The vapor recovery system may control the recovered well casing vapors from permit unit C-311-112 during operation of the casing collection system as a casing balance system. [District NSR Rule and 4623] Federally Enforceable Through Title V Permit

56. The 6C-CC-1 system (C-311-112) may be operated as a vapor balance system and/or an active well vent vapor recovery system. When operated as a vapor balance system valves associated with the 6C-CC-1 system (C-311-112) may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District NSR Rule] Federally Enforceable Through Title V Permit

57. Collected VOC vapors shall be incinerated in steam generators C-311-36, '-37, '-38, '-39, '-40, '-41, '-52, '-53, '-55, '-56, '-76 and -'84, or disposed of in Department of Oil, Gas, and Geothermal Resources (DOGGR) approved vapor disposal well(s). [District NSR Rule] Federally Enforceable Through Title V Permit

58. Operation of the casing collection system as a casing balance system shall not cause gas flow rates at the 6C, 13D and/or 25D Oil Cleaning Plant in excess of the design capacity of the tank vapor recovery compressor. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-146-23 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-23 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers.. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit.

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-147-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,013 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-22 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers.. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-150-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14

EQUIPMENT DESCRIPTION:
5,103 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-18 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers.. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-163-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
4,697 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-31 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rules 2520, 9.3.2 and 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2520, 9.3.2 and 4623, 5.6.2] Federally Enforceable Through Title V Permit

15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-164-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
4,697 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-32 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit
19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-165-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,592 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-29 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-166-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,592 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-30 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
9. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

12. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

13. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

46. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

52. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-167-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
3,579 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-33 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-168-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
3,579 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-34 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers.. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-169-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,424 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-60 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-170-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,901 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-37 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers.. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP.of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-177-17 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,047 BBL FIXED ROOF FREE WATER KNOCK OUT TANK # 25-42 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-268, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

56. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-180-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
523 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-3

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-181-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
523 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-4

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-182-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
269 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-5

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-196-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF WASH TANK # 13-29 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-197-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF WASH TANK # 13-30 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
9. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
12. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
14. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit
15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
16. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
18. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
19. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

42. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

46. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

50. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

51. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

52. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-198-14 **EXPIRATION DATE:** 12/31/2016

SECTION: 13D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
270 BBL FIXED ROOF CRUDE OIL TANK # 13-13 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
8. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
11. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

14. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

17. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

31. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

49. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

52. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

53. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

55. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-205-3

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
20 OPEN-VENT CYCLIC WELLS

PERMIT UNIT REQUIREMENTS

1. There may be no more than 20 open-vent cyclic-driven petroleum production wells at this stationary source, when the well is undergoing pilot testing (and the production zone has not been injected with steam in the preceding two years) or well stimulation; and no more than 5 wells that are not undergoing pilot testing or well stimulation may be operated. [District Rule 4401] Federally Enforceable Through Title V Permit
2. The well is located more than 1000 feet from an existing well vent vapor control system operated by the company. [District Rule 4401, 4.5.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-215-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-1

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-216-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-2

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-217-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-3

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-219-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-5

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-220-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-6

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-221-3 **EXPIRATION DATE:** 12/31/2016

SECTION: 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-7

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-222-6 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
3000 BBL CONE BOTTOM WASH TANK #24-9

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. VOC emissions shall not exceed 1.5 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-223-4 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-10

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The tank shall be operated at constant level. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. VOC emissions shall not exceed 1.4 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-227-3 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
GASOLINE DISPENSING OPERATION WITH ONE 2,000 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROS EVR PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE(S) SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116-F)

PERMIT UNIT REQUIREMENTS

1. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit

9. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit

10. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

11. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit

12. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit

13. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit

14. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

16. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
17. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6 Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected once per month if monthly throughput is below 2,500 gallons or once per week otherwise. [District Rule 4622] Federally Enforceable Through Title V Permit
18. If a Liquid Condensate Trap is installed, the permittee shall perform and pass a Liquid Condensate Trap Compliance Test using the test procedure defined in the Executive Order specified in this permit for the Phase II Vapor Recovery System at least once every 12 months. [District Rule 4622] Federally Enforceable Through Title V Permit
19. If a Liquid Condensate Trap is installed it shall be (1) maintained without leaks; (2) accessible for inspection upon request; (3) capable of automatic evacuation of liquid; and (4) equipped with an alarm system in case of failure of the evacuation system. [District Rule 4622] Federally Enforceable Through Title V Permit
20. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
23. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
24. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
26. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
27. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
28. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVAPCD Rules 4621 except section 5.2.2 (as amended June 18, 1998), 4622 (as amended September 19, 2002), and 4623, section 5.4 (as amended May 19, 2005). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. This permit unit is not equipment used for light crude oil and gas production, natural gas processing, nor organic liquid loading, and is not an internal or external floating roof tank with a capacity of 19,800 gallons or more. Therefore, the requirements of District Rule 4403 (as amended April 20, 2005), 4623 except section 5.4 (as amended May 19, 2005), and 4624 (as amended December 17, 1992) do not apply to this permit unit. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

31. This permit unit is not associated with loading at a bulk gasoline terminal (as defined in 40 CFR 60.501). Therefore, the requirements of 40 CFR 60 Subpart XX do not apply to this permit unit. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-232-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 31 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Formerly C-1121-162-2

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-233-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 31 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
3. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
5. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
6. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. The operator shall keep an accurate daily record of each organic liquid stored in each tank, including its storage temperature, TVP, and API gravity. [District Rules 2520, 9.3.2 & 4623, 6.3.1] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly C-1121-163-2

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-234-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 31 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
1000 BBL FIXED ROOF PETROLEUM STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Formerly C-1121-164-2

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-235-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 25D **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
600 BHP CUMMINGS MODEL #KTA19C52 (SERIAL #31134968) DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101, 5.1]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Emissions from this IC engine shall not exceed any of the following limits: 14.1 g-NOx/bhp-hr, 3.03 g-CO/bhp-hr, or 1.14 g-VOC/bhp-hr. [17 CCR 93115]
4. Emissions from this IC engine shall not exceed 1.0 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [17 CCR 93115]
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
8. On and after May 3, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. On and after May 3, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. On and after May 3, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. On and after May 3, 2013, the engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. On and after May 3, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

14. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

15. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

16. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit

17. The permittee shall maintain monthly records that include the type of fuel purchased, the amount of fuel purchased, and the date of fuel purchase. [District Rules 4702 and 2520, 9.4 and 17 CCR 93115] Federally Enforceable Through Title V Permit

18. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.), and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4702 and 2520, 9.4, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

19. On and after May 3, 2013, the permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [District Rule 1070, 2520, 9.4 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

20. On and after May 3, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [District Rule 1070, 2520, 9.4 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4702, 2520, 9.4, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

22. This permit unit was formerly number C-311-91.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-236-8 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
5,100 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-19 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to vapor control when receiving production from TEOR wells operated with closed casing vents. [District Rule 2201]
2. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, and -271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
9. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit

12. Except as otherwise provided on this permit, this tank shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit

13. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit

14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

15. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit

16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

18. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

19. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

20. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

21. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

23. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

24. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

25. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

26. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

27. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

29. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

30. When storing organic liquids of TVP of equal to or greater than 0.5 psia, to facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. When storing organic liquids of TVP of equal to or greater than 0.5 psia, this tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

32. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 or greater is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

33. When storing organic liquids of TVP of equal to or greater than 0.5 psia, while performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

34. When storing organic liquids of TVP of equal to or greater than 0.5 psia, steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

35. When storing organic liquids of TVP of equal to or greater than 0.5 psia, during sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

36. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

37. When storing organic liquids of TVP of equal to or greater than 0.5 psia, permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

38. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit

39. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080] Federally Enforceable Through Title V Permit

40. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit

41. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080] Federally Enforceable Through Title V Permit

43. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

44. When storing organic liquids of TVP less than 0.5 psia, permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedure as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

45. When storing organic liquids of TVP less than 0.5 psia, tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

46. When storing organic liquids of TVP less than 0.5 psia, permittee shall notify the District Compliance division at least 72 hours prior to tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit

47. When storing organic liquids of TVP less than 0.5 psia, the tank shall be cleaned using water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment shall be used for road mix as allowed by Section 6.17 of District Rule 2020 (amended 12/19/02). [District Rule 2080] Federally Enforceable Through Title V Permit

48. When storing organic liquids of TVP less than 0.5 psia, steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

49. When storing organic liquids of TVP less than 0.5 psia, within 96 hours after refilling the tank, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA Method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

50. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

51. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201] Federally Enforceable Through Title V Permit

53. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

55. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

56. When storing organic liquids of TVP less than 0.5 psia, permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

57. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-238-3 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
TRANSPORTABLE TIER 3 CERTIFIED DIESEL-FIRED IC ENGINE UP TO 532 HP FOR MECHANICAL PUMPING, COMPRESSION, OR POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Permittee shall provide written notification to the District within 48 hours of operating an engine under this permit (if an engine is located onsite longer than 24 hours). Such notification shall include the date the unit was brought onsite, the manufacturer, model number, maximum rating, and emissions information that documents that the unit meets the emission limits and requirements specified in the permit. [District Rule 1070]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Any engine utilized by this permit shall not be operated within 181 feet of facility boundary. [District Rule 4102]
4. Any engine utilized by this permit shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801and 17 CCR 93116] Federally Enforceable Through Title V Permit
6. Any engine utilized by this permit shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Any engine utilized by this permit shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
8. Any nonroad transportable engine utilized by this permit shall not be operated at one location for more than 12 consecutive months and shall meet all the requirements of a nonroad transportable engine, per CFR Title 40 Part 89. [CCR, Title 17 and District Rule 4701] Federally Enforceable Through Title V Permit
9. Operation of the engine shall not exceed 200 hours per year, as determined by an operational nonresettable elapsed operating time meter or other APCO approved alternative. The operator shall maintain records of the cumulative hours of operation on a 12 month rolling average. These records shall be updated at least monthly. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
10. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
11. Emissions from any engine utilized by this permit shall not exceed any of the following limits: 2.85 g-NOx/bhp-hr, 2.61 g-CO/bhp-hr, or 0.15 g-VOC/bhp-hr. [District Rule 220117 CCR 93116] Federally Enforceable Through Title V Permit
12. The PM10 emissions rate from any engine utilized by this permit shall not exceed 0.15 g/hp-hr based on US EPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. During periods of operation, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
14. Permittee shall maintain a permit operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
15. Permittee shall maintain records of each location where the permit unit is operated, including dates and duration of residency at each location, and shall update those records each time any IC engine utilized by this permit is moved. [District Rule 2201 and 17 CCR 93116] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-239-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 19 **TOWNSHIP:** 28S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
157 BHP CATERPILLAR MODEL LC3034B S/N E5M02254 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR:

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
3. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
8. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
9. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102] Federally Enforceable Through Title V Permit
10. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102] Federally Enforceable Through Title V Permit
11. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, 17 CCR 93115, 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Emissions from this IC engine shall not exceed any of the following limits: 2.53 g-NOx/bhp-hr, 1.34 g-CO/bhp-hr, or 0.13 g-VOC/bhp-hr. [District Rule 2201, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII]] Federally Enforceable Through Title V Permit
14. Emissions from this IC engine shall not exceed 0.15 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
15. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
16. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
17. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
18. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
19. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
20. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115 and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
21. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-240-3 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
600 BBL PRESSURE VESSEL VENTED TO TEOR OPERATION C-311-79

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emission components exclude piping and components handling produced fluids having less than 10% VOC by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operator shall conduct quarterly sampling of tank vapors to qualify for exemption from fugitive component counts for components handling fluids with less than 10% VOC by weight. If 8 consecutive quarterly samplings show compliance, then sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC content of vapor shall be determined by ASTM D1945, ASTM D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All vessel and vapor control system piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated to methane, to ensure compliance with the provisions of this permit. If any of the vessel components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no vessel components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 ft above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
6. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
7. During a District inspection, any tank, gauge hatch, sampling device, or other component that is not leak free will not be a violation of this permit provided the facility records, tags, and repairs the leak in accordance with the requirements of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Permittee shall maintain a written record of the VOC content of the gas sampled. [District Rule 2201] Federally Enforceable Through Title V Permit

10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-248-0 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20s **RANGE:** 14e

EQUIPMENT DESCRIPTION:
85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR SG-13/25-XA WITH NORTH AMERICAN MODEL 4231-85 GLE LOW-NOX BURNER, OR EQUIVALENT, AND FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. This steam generator may be operated at the 13D or 25D steam plants. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This Authority to Construct authorizes the installation of an 85 MMBtu/hr North American GLE burner or a 69 MMBtu/hr North American GLE burner, or equivalent. Approval of any other equivalent burner shall be made only after the District's determination that the submitted design and performance of the proposed alternate equipment is equivalent to the specifically authorized equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The permittee's request for approval of equivalent equipment shall include the make, model, manufacturer's maximum rating, manufacturer's guaranteed emission rates, equipment drawing(s), and other relevant operational characteristics. [District Rule 2201] Federally Enforceable Through Title V Permit
6. A burner is not equivalent if any of the emission factors or the maximum heat input rating is greater than those authorized in this Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. The unit shall always operate at least 604 meters away from the nearest property boundary line. [District Rule 4102]
9. This unit shall be fired on PUC quality natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Fuel gas shall not contain more than 1 grain of total sulfur per 100 standard cubic feet or 0.00285 lb/MMBtu. [District Rule 2201, 4320 and 4801] Federally Enforceable Through Title V Permit
11. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
12. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
13. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. During the 60-day shakedown period, the operator shall operate the burner with the maximum FGR setting that can be accommodated by the specific commissioning activity being undertaken, perform expeditious completion of commissioning activities, and shall use good work practice standards to minimize emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Except during startup and shutdown periods, and the 60-day shakedown period, emissions shall not exceed either of the following limits: 7 ppmvd NOx (as NO2) @ 3% O2 (0.0085 lb/MMBtu), 0.0032 lb PM10/MMBtu, 25 ppmvd CO @ 3% O2 (0.0185 lb/MMBtu) or 12 ppmvd VOC @ 3% O2 (0.0055 lb VOC/MMBtu). [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. During the 60-day shakedown period, emissions shall not exceed any of the following limits: 15 ppmvd NOx (as NO2) @ 3% O2 (0.018 lb/MMBtu), 0.0032 lb PM10/MMBtu, 50 ppmvd CO @ 3% O2 (0.037 lb/MMBtu) or 12 ppmvd VOC @ 3% O2 (0.0055 lb VOC/MMBtu). [District Rule 2201] Federally Enforceable Through Title V Permit

17. During start-up and shutdown periods, emissions from the steam generator shall not exceed either of the following limits: 0.1 lb-NOx/MMBtu or 0.084 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

18. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 5.5.6 and 4306, 5.3] Federally Enforceable Through Title V Permit

19. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25 and 3.22] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3%, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

22. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The NOx, CO, and O2 analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute sample period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The permittee shall maintain records of: (1) the date and time of NOx, CO and O2 measurements, (2) the O2 concentration in percent by volume and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. A source test to demonstrate compliance with NOx and CO emission limits shall be performed within 60 days of startup of this unit. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

25. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

26. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. For the purposes of permittee-performed alternate monitoring, emissions measurements may be performed at any time after the unit reaches conditions representative of normal operation. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

27. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

28. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

29. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

30. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, Stack Gas Oxygen - EPA Method 3 or 3A or ARB Method 100, Stack Gas Velocity (ft/min) - EPA Method 2, Stack Gas Moisture Content (%) - EPA Method 4, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6, 6A, 6B, 6C or fuel gas sulfur content analysis and EPA Method 19, Fuel Gas Sulfur Content - EPA Method 11 or 15, ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588, PM10 - EPA Methods 5, 201A, and/or 202, CARB Method 5, or any combination of these PM10 methods with both filterable and condensable PM10 measured. [District Rules 1081, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

31. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

32. Each fuel source shall be tested semi-annually for sulfur content and higher heating value. If a fuel content test fails to show compliance, weekly testing is required until compliance is demonstrated for 8 consecutive weeks, after which semi-annual testing may resume. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

33. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, 4320 and 40 CFR 60.48c(i)] Federally Enforceable Through Title V Permit

35. Prior to operating equipment under this Authority to Construct with an 85 MMBtu/hr burner, permittee shall surrender emission reduction credits for the following quantities of emissions: NOx: 2,373 lb/qtr; SOx: 796 lb/qtr; PM10: 894 lb/qtr, and VOC: 1,536 lb/qtr. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 4/21/11) for the ERCs specified below. [District Rule 2201 and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

36. Prior to operating equipment under this Authority to Construct with a 69 MMBtu/hr burner, permittee shall surrender emission reduction credits for the following quantities of emissions: NOx: 1,927 lb/qtr; SOx: 646 lb/qtr; PM10: 725 lb/qtr, and VOC: 1,247 lb/qtr. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 4/21/11) for the ERCs specified below. [District Rule 2201 and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

37. ERC Certificate Numbers S-3735-2 (NOx), S-2934-5 (SOx), S-3598-4 (PM10) and S-3722-1 (VOC) (or certificates split from these certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201 and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-253-1 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
324 BHP INTERMITTENT CUMMINS MODEL QSB7-G5NR3 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR. (13D WATER PLANT)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. Emission rates from this unit shall not exceed any of the following limits: 2.8 g-NOx/hp-hr; 0.0051 g-SOx/hp-hr; 0.147 g-PM10/hp-hr; 2.6 g-CO/hp-hr; 0.2 g-VOC/hp-hr; or a combined 3.0 g-NOx+VOC/hp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-254-0 **EXPIRATION DATE:** 12/31/2016

SECTION: SW6 **TOWNSHIP:** 20S **RANGE:** 15E

EQUIPMENT DESCRIPTION:
85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR SG-6-36 WITH NORTH AMERICAN MODEL 4231-85 GLE LOW-NOX BURNER AND FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
5. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Emission rates, except during startup and shutdown shall not exceed: NOx (as NOx): 7 ppmvd @ 3% O2 or CO: 25 ppmvd @ 3% O2 [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. Emission rates shall not exceed any of the following: SOx:0.00285 lb/MMBtu; PM10: 0.0032 lb/MMBtu; or VOC: 0.0055 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions rates shall not exceed 48.5 lb-NOx/day or 6,329 lb-NOx/yr; or 60.4 lb-CO/day or 13,775 lb-CO/yr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of duration of each start-up and shutdown for a period of five years and make such records readily available for District inspection upon request. [District Rule 4320] Federally Enforceable Through Title V Permit
10. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 2201, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

13. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10, 10B or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6, 6A, 6B, 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; ASTM D1072, D3031, D4084 D3246 or grab sample analysis by GC-FPD/TCD or double GC for H2S and mercaptans performed in a laboratory and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588, VOC (ppmv) - EPA Method 25A or 25B, or ARB Method 100. [District Rule 2201, 4305, 4306, 4320] Federally Enforceable Through Title V Permit

14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

15. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. If the NOx or CO concentrations corrected to 3%, as measured by the portable analyzer, exceed the applicable emission limit, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4102, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

17. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The NOx, CO, and O2 analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute sample period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive minute period. [District Rules 4102, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

18. The permittee shall maintain records of: (1) the date and time of NOx, CO and O2 measurements, (2) the O2 concentration in percent by volume and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

19. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the PTO, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. For the purposes of permittee-performed alternate monitoring, emissions measurements may be performed at any time after the unit reaches conditions representative of normal operation. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. Shorter time periods for demonstration of compliance after startup or re-ignition may be approved by the APCO by submittal of appropriate technical justification upon implementation of this ATC. [District Rule 2201] Federally Enforceable Through Title V Permit

21. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

22. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

23. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, permittee shall demonstrate compliance at least annually. [District Rule 4320] Federally Enforceable Through Title V Permit

24. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit

25. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-265-1 **EXPIRATION DATE:** 12/31/2016

SECTION: NE 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
1000 BBL VESSEL SERVED BY VAPOR CONTROL SYSTEM LISTED ON C-311-111

PERMIT UNIT REQUIREMENTS

1. Maximum VOC content of tank/vessel vapors shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operator shall conduct and keep records of quarterly sampling of tank/vessel vapors to qualify for exemption from fugitive component counts for components handling fluids with less than 10% VOC by weight. If fluids sampled are less than 10% VOC by weight for eight consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Vessel shall only store, place, or hold organic liquid with true vapor pressure (TVP) less than 0.5 psia under all storage conditions. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2520] Federally Enforceable Through Title V Permit
5. Except as otherwise provided on this permit, this tank and vapor control system shall be maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rule 2201and District Rules 2520, 9.3.2 and 4623, 5.7] Federally Enforceable Through Title V Permit
9. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit

11. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

12. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-266-1 **EXPIRATION DATE:** 12/31/2016

SECTION: NE 24 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
250 BBL CRUDE OIL DRAIN TANK CLAREMONT T-6

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) less than 0.1 psia under all storage conditions. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. VOC emission rate from the tank shall not exceed 0.5 lb/day. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank within 60 days of startup in accordance with the methods described in this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. Operator shall determine the true vapor pressure (TVP) of the petroleum liquid stored in this tank at least once every 24 months in accordance with the methods described in this permit. Determinations shall be made during the months of July - September and whenever there is a change in the source or type of organic liquid entering the tank. Determination can be made using representative sampling as described in Section 6.2.1.1 of District Rule 4623. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of TVP and API gravity testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Permittee shall maintain monthly records of average daily crude oil throughput and shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-267-5 **EXPIRATION DATE:** 12/31/2016

SECTION: 13 **TOWNSHIP:** 120S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
13D OIL CLEANING PLANT VAPOR RECOVERY SYSTEM, SERVING PERMIT UNITS C-311-146, '-147, '-150, '-196, '-197, '-198, '-236, AND '-271, INCLUDING TWO (2) 50 HP COMPRESSORS, REGULATOR, AND VAPOR PIPING TO DISTRICT APPROVED STEAM GENERATORS C-311-20, '-21, '-25, '-28, '-30, '-36, '-37, '-38, '-39, '-40 AND/OR '-41, OR DOGGR APPROVED VAPOR DISPOSAL WELLS

PERMIT UNIT REQUIREMENTS

1. Vapor recovery system shall consist of a closed vent system that collects VOCs from District approved storage tanks and discharges to District approved VOC vapor recovery. The vapor recovery system shall be APCO-approved. The VOC vapor recovery system shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, vapor balance well vent/tank vapor recovery system, DOGGR-approved injection well(s) for disposal of vapors, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method(s) specified in this permit. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
2. Vapor recovery system compressor shall activate before the pressure relief valve vents, on any of the units served by the vapor recovery equipment. The vapor recovery system does not serve tanks while they are disconnected during District authorized cleaning and maintenance events as allowed by those permits. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. The vapor recovery system may control the recovered well casing vapors from permit units C-311-77, '-78, '-83, and '-111 during operation of the casing collection system as a casing balance system. [District District Rule 2201and 4623] Federally Enforceable Through Title V Permit
4. The 13D system may be operated as a vapor balance well vent/tank vapor recovery system. When operated as a vapor balance system, valves associated with the 13D system may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Operation of the casing collection system as a casing balance system shall not cause gas flow rates at the 6C, 13D and/or 25D Oil Cleaning Plant in excess of the design capacity of the tank vapor recovery compressor. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-146, -147, -150, -196, -197, -198, -236, -267, and '-271 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
7. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Maximum VOC content of vapor in the vapor recovery system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
13. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, ASTM D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Except as otherwise provided on this permit, vapor recovery system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
15. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
16. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201] Federally Enforceable Through Title V Permit

25. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-268-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 25 **TOWNSHIP:** 20S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
25D OIL CLEANING PLANT VAPOR RECOVERY SYSTEM, SERVING PERMIT UNITS C-311-163, '-164, '-165, '-166, '-167, '-168, '-169, '-170 AND '-177, INCLUDING 50 HP COMPRESSOR, TWO VERTICAL SCRUBBERS, FIN FAN COOLER, REGULATOR, AND VAPOR PIPING TO DISTRICT APPROVED STEAM GENERATORS C-311-20, '-21, '-25, '-28, '-30, '-36, '-37, '-38, '-39, '-40 AND/OR '-41, OR DOGGR APPROVED VAPOR DISPOSAL WELLS

PERMIT UNIT REQUIREMENTS

1. Vapor control system may be inoperable during maintenance/repairs/upset conditions of tanks C-311-163, -164, -165, -166, -167, -168, -169, -170, and -177 for up to 600 hours per rolling 12-month period. District-approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201] Federally Enforceable Through Title V Permit
2. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, storage of coatings, adhesives, sealents, and organic solvents in closed containers.. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Inspection, monitoring, and repair if necessary of fugitive emissions components installed when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be done within 7 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Records of the dates, hr/day, and hr/yr when vapor control system is inoperable for tank maintenance/repairs/upset conditions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Tank shall not receive production from wells operated with closed casing vents when vapor control system is inoperable for tank maintenance/repairs/upset conditions. For TEOR wells producing to tank, records of dates well casing valves are open or closed shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Vapor recovery system shall consist of a closed vent system that collects VOCs from District approved storage tanks and discharges to District approved VOC vapor recovery. The vapor recovery system shall be APCO-approved. The VOC vapor recovery system shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, vapor balance well vent/tank vapor recovery system, DOGGR-approved injection well(s) for disposal of vapors, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method(s) specified in this permit. [District Rule 4623, 5.1.1 and 5.6] Federally Enforceable Through Title V Permit
7. Vapor recovery system compressor shall activate before the pressure relief valve vents, on any of the units served by the vapor recovery equipment. The vapor recovery system does not serve tanks while they are disconnected during District authorized cleaning and maintenance events as allowed by those permits. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. The vapor recovery system may control the recovered well casing vapors from permit unit C-311-79 during operation of the casing collection system as a casing balance system. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
9. The 25D system may be operated as a vapor balance well vent/tank vapor recovery system. When operated as a vapor balance system valves associated with the 25D system may be closed to allow condensate and noncondensable gas to be displaced to the reservoir through wells served by the system. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operation of the system as a balance system shall not cause gas flow rates at the 6C, 13D and/or 25D Oil Cleaning Plant in excess of the design capacity of the tank vapor recovery compressor. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Maximum VOC content of vapor in the vapor recovery system shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Operator shall test VOC content of the vapors representative of 25D tank vapor recovery gas annually. [District Rule 2201] Federally Enforceable Through Title V Permit
13. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
14. Except as otherwise provided on this permit, vapor recovery system shall be maintained in a leak-free condition. [District Rule 4623, 5.1.3 and 5.6] Federally Enforceable Through Title V Permit
15. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17] Federally Enforceable Through Title V Permit
16. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623, 6.4.6] Federally Enforceable Through Title V Permit

23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-269-0 **EXPIRATION DATE:** 12/31/2016

SECTION: 36 **TOWNSHIP:** 19S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TANK #CO-T-57: 10,584 GALLON FIXED ROOF CRUDE OIL STORAGE TANK, 15'D X 8'H, CAPACITY: 252 BBLS.

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623]
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623]
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623]
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623]
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623]
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623]
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2]
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623]
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623]
11. Formerly #C-8517-4-0

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-270-0 **EXPIRATION DATE:** 12/31/2016

SECTION: 36 **TOWNSHIP:** 19S **RANGE:** 14E

EQUIPMENT DESCRIPTION:
TANK #CO-T-58: 10,584 GALLON FIXED ROOF CRUDE OIL STORAGE TANK, 15'D X 8'H, CAPACITY: 252 BBLS.

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623]
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank, or a representative tank as provided in Section 6.2.1.1. of District Rule 4623, at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623]
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623]
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623]
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623]
6. Instead of testing each uncontrolled fixed roof tank, the permittee may conduct a TVP test of the organic liquid stored in a representative tank provided the requirements of Sections 6.2.1.1.1. through 6.2.1.1.5 of Rule 4623 are met. [District Rule 4623]
7. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
8. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of the API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 2520, 9.4.2]
9. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623]
10. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 4623]
11. Formerly #C-8415-5-0

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-311-271-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK (OR DISTRICT APPROVED EQUIVALENT), #13-13A SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-267

PERMIT UNIT REQUIREMENTS

1. Tank shall only vent to vapor recovery system, permit C-311-267, except during District approved cleaning and during maintenance procedures. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
2. Tank shall not be required to be served by vapor control system C-311-267 during vapor recovery system (tanks to disposal devices, inclusive) maintenance/repairs/upset conditions for up to 600 hours per year. Approved breakdowns and relief periods granted by variance and supported by the District shall not be included in this limit. [District Rule 2201]
3. During temporary periods of maintenance/repair/upsets covered by this permit, operator shall use work practices to minimize VOC emissions including: constant level tank operation, use of operational P/V valve where possible, work completed expeditiously with pre-staging of equipment and material and pre-fabrication of parts, minimization of tank openings and liquid drainage from disconnects, inspection, monitoring, and repair if necessary of fugitive emissions components at job site within 30 days of completion of work. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When disconnected from the vapor control system for maintenance/repairs/upset conditions, tank will store organic liquid with a true vapor pressure less than 0.5 psia. [District Rule 4623]
5. Maximum VOC content of vapor in the tank vapor space shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Operator shall conduct quarterly gas sampling of gas handled by TVR system. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201] Federally Enforceable Through Title V Permit
7. VOC content of vapor by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945, D1946, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. [District Rule 4623, 3.11 and 3.17]
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall determine the true vapor pressure of the petroleum liquid stored in the tank at least once per year in accordance with methods described in this permit and District Rule 4623. Determinations shall be made annually during the summer and whenever there is a change in the source or type of petroleum entering the tank. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. This determination is to be done so that proper inspection, maintenance and tank cleaning procedures can be made per District Rule 4623, Section 5.7, prior to storing liquids in any permitted tank with a TVP equal to or greater than 0.5 psia. Determination can be made using representative sampling of common sources in the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. [District Rules 2520, 9.3.2 and 4623, 5.7]
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623]
12. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2]
13. For crude oil with an API gravity greater than 26 degrees, the TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D 323-94 (Test Method for Vapor Pressure for Petroleum Products), and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures in District Rule 4623, Appendix B. As an alternative to using ASTM D 323-94, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and US EPA. [District Rule 4623, 6.4.3]
14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4]
15. When storing organic liquids of TVP equal to or greater than 0.5 psia, operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3]
16. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3]
17. When storing organic liquids of TVP equal to or greater than 0.5 psia, upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3]
18. When storing organic liquids of TVP equal to or greater than 0.5 psia, components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. When storing organic liquids of TVP equal to or greater than 0.5 psia, leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3]
20. When storing organic liquids of TVP equal to or greater than 0.5 psia, if a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3]
21. When storing organic liquids of TVP equal to or greater than 0.5 psia, any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3]
22. When storing organic liquids of TVP less than 0.5 psia, all piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080]
23. When storing organic liquids of TVP less than 0.5 psia, a facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in a leak free condition. [District Rule 2080]
24. When storing organic liquids of TVP less than 0.5 psia, an operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2080]
25. When storing organic liquids of TVP less than 0.5 psia, emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080]
26. When storing organic liquids of TVP less than 0.5 psia, any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 18 or 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 18 or 25 at least annually. [District Rule 2080]
27. When storing organic liquids of TVP less than 0.5 psia, if the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080]
28. The requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
29. The requirements of SJVUAPCD Rule 4661 (Amended December 17, 1992) and Rule 4801 (Amended December 17, 1992) do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. Permittee shall maintain records of the number and type of components installed, % VOC content of gas handled, and the calculated fugitive emissions. Permittee shall update such records when new components are installed or removed. [District Rule 2201]

31. An operator whose tanks are subject to the requirements of District Rule 4623, shall keep an accurate record of each organic liquid stored in each tank, including its storage temperature, Reid/TVP as appropriate and API gravity of petroleum liquids stored in this unit to determine which oils are from the Heavy Oil source. [District Rule 4623, 6.3.1]

32. When storing organic liquids of TVP equal to or greater than 0.5, operator shall maintain an inspection log containing the following: 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 1070 and 4623]

33. When storing organic liquids of TVP less than 0.5 psia, operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080]

34. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3]

ATTACHMENT C

Detailed Facility List

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

CHEVRON USA INC
HEAVY OIL PRODUCTION
UTM 10S 734,027E 4,007,848N COALINGA
FRESNO COUNTY, CA 93210

FAC # C 311
STATUS: A
TELEPHONE: 2099350831

TYPE: TitleV
TOXIC ID: 40034

EXPIRE ON: 12/31/2016
AREA: 5 / 308
INSP. DATE: 03/18

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-13-13	2.7 MW TURBINE COGENERATOR	3020-08A C	1	1,678.00	1,678.00	A	NON-COMPLIANT DORMANT EMISSIONS UNIT CONSISTING OF 86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-105, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A STRUTHERS WASTE HEAT RECOVERY STEAM GENERATOR #SG-205, WITH A 36.4 MMBTU/HR COEN DUCT BURNER
C-311-15-12	2.7 MW TURBINE COGENERATOR	3020-08A C	1	1,678.00	1,678.00	A	NON-COMPLIANT DORMANT EMISSIONS UNIT CONSISTING OF 86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-106, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A STRUTHERS WASTE HEAT RECOVERY STEAM GENERATOR #SG-206 WITH A 36.4 MMBTU/HR COEN DUCT BURNER
C-311-19-24	62.5 MMBtu/hr steam generator	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED, MODEL 5G-50-NDS-15, THERMOTICS STEAM GENERATOR SG 13-03, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-20-22	58.5 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	58.5 MMBTU/HR SG 13-04 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR WITH A NORTH AMERICAN GLE BURNER WITH FLUE GAS RECIRCULATION
C-311-21-11	58.5 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	58.5 MBTU/HR SG 13-05 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER
C-311-22-24	62.5 MMBtu/hr steam generator	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED, MODEL 5G-50-NDS-15, THERMOTICS STEAM GENERATOR SG 13-06, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-23-21	62.5 MMBtu/hr steam generator	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED, MODEL 5G-50-NDS-15, THERMOTICS STEAM GENERATOR SG 13-06, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-25-10	58.5 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	58.5 MMBTU/HR SG 13-09 NATURAL/LPG/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM
C-311-27-15	58.5 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	58.5 MMBTU/HR STRUTHERS THERMOFLOOD STEAM GENERATOR #13-11, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN GLE BURNER, EQUIPPED WITH FLUE GAS RECIRCULATION AND AN OXYGEN CONTROLLER

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-28-20	58.5 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	58.5 MMBTU/HR SG 13-12 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, EQUIPPED WITH A NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM
C-311-30-19	62.5 MMBTU/HR SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 13-14 NATURAL/TANK VAPOR RECOVERY/CASING GAS-FIRED STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN BURNER, AND A FLUE GAS RECIRCULATION (FGR) SYSTEM
C-311-36-24	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG-25-15 STRUTHERS THERMOFLOOD, MODEL OH-50-ND-16XAM STEAM GENERATOR WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE 25D NEPTUNE AIRPOL CAUSTIC SCRUBBER (SHARED WITH UNITS -37, -38, -39, -40, AND -41) WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS
C-311-37-29	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 25-16 STRUTHERS THERMOFLOOD MODEL OH-50-ND-16XAM STEAM GENERATOR WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS
C-311-38-34	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 25-17 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS
C-311-39-26	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG-25-18 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS
C-311-40-25	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 25-19 NATURAL GAS STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS
C-311-41-25	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 25-20 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR), SERVED BY THE SCRUBBER LISTED ON UNIT C-311-36 WHEN FIRING WELL CASING AND/OR TANK VAPOR RECOVERY GAS
C-311-42-20	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 25-21 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-43-18	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 25-22 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16AXM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-45-18	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 25-24 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16AXM, WITH FLUE GAS RECIRCULATION (FGR)
C-311-46-18	58.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 25-25 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN 4131-G-LNX BURNER WITH FLUE GAS
C-311-47-12	58.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 25-26 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16-XAM, WITH A NORTH AMERICAN BURNER, MODEL 4131-G-LNX, AND A FLUE GAS RECIRCULATION SYSTEM
C-311-48-14	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-27, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-49-14	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-28, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-50-14	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS MODEL OH-50-ND-16XAM THERMOFLOOD STEAM GENERATOR SG 25-29, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-51-20	58.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	NON-COMPLIANT DORMANT 58.5 MMBTU/HR SG 6-31 STRUTHERS THERMOFLOOD STEAM GENERATOR, MODEL OH-50-ND-16XAM, WITH A NORTH AMERICAN 4131-G-LNX BURNER WITH FLUE GAS RECIRCULATION
C-311-52-19	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG STRUTHERS THERMOFLOOD STEAM GENERATOR #6-32, MODEL 0H-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-53-20	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR STRUTHERS THERMOFLOOD STEAM GENERATOR MODEL OH-50-ND-16XAM, WITH NORTH AMERICAN GLE BURNER, AND FLUE GAS RECIRCULATION (FGR)
C-311-76-18	58.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	58.5 MMBTU/HR SG 6-38 NATURAL/LPG/TEOR GAS-FIRED STRUTHERS THERMOFLOOD MODEL OH-50-ND-16XAM STEAM GENERATOR WITH A NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR) SYSTEM
C-311-77-7	91 WELLS	3020-09 A	91	10.23	930.93	A	TEOR OPERATION WITH 91 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-2-13D WITH LOW PRESSURE SCRUBBER-SEPARATOR, AIR COOLER AND CONDENSATE COLLECTOR (13D NORTHEAST)
C-311-78-5	149 WELLS	3020-09 A	149	10.23	1,524.27	A	TEOR OPERATION WITH 149 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-4-13D WITH SCRUBBER, FIN-FAN AIR COOLER AND CONDENSATE COLLECTOR (13D NORTHWEST)

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-79-19	491 wells	3020-09 A	491	10.23	5,022.93	A	TEOR OPERATION #CC-1-25D WITH 491 STEAM ENHANCED WELLS WITH TWO 100 HP COMPRESSORS, SEPARATOR, CONDENSATE COLLECTOR AND PIPING FROM TEOR OPERATION #6C-CC-1 (C-311-112) AND PRESSURE VESSEL C-311-240
C-311-83-21	596 WELLS	3020-09 A	596	10.23	6,097.08	A	TEOR OPERATION WITH 596 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-3-13D WITH SCRUBBER, FIN-FAN AIR COOLER, COMPRESSOR, AND CONDENSATE COLLECTOR, WITH CLOSED CASING VENTS OR VENTING TO A BALANCED PIPING SYSTEM OR STEAM GENERATORS APPROVED BY DISTRICT FOR TEOR GAS INCINERATION OR DOGGR APPROVED VAPOR DISPOSAL WELL(S) (13D SOUTHWEST)
C-311-84-18	62.5 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	62.5 MMBTU/HR SG 6-37 STRUTHERS THERMOFLOOD STEAM GENERATOR MODEL OH5O-ND-16XAM WITH NORTH AMERICAN MODEL GLE BURNER AND FLUE GAS RECIRCULATION (FGR)
C-311-88-15	2.7 MW TURBINE COGENERATOR	3020-08A C	1	1,678.00	1,678.00	A	86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-104, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A RENTECH WASTE HEAT RECOVERY STEAM GENERATOR, WITH A 37 MMBTU/HR JOHN ZINC HAMWORTHY COMBUSTION DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)
C-311-93-13	2.7 MW TURBINE COGENERATOR	3020-08A C	1	1,678.00	1,678.00	A	86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-101, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-201, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)
C-311-95-13	2.7 MW TURBINE COGENERATOR	3020-08A C	1	1,678.00	1,678.00	A	86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-102, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-202, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)
C-311-97-13	2.7 MW TURBINE COGENERATOR	3020-08A C	1	1,678.00	1,678.00	A	86.4 MMBTU/HR COGENERATION SYSTEM WITH A NOMINAL RATED 40.9 MMBTU/HR SOLAR MODEL CENTAUR 40-4500 TURBINE ENGINE #TG-103, DRIVING A 2.7 MW ELECTRICAL GENERATOR AND INCLUDING A WASTE HEAT RECOVERY STEAM GENERATOR #SG-203, WITH A 36.4 MMBTU/HR COEN DUCT BURNER SERVED BY A SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM WITH AMMONIA INJECTION AND A CONTINUOUS EMISSIONS MONITORING SYSTEM (CEMS)
C-311-105-4	118 CLOSED-VENT CYCLIC WELLS	3020-09 A	118	10.23	1,207.14	A	118 CLOSED-VENT TEOR WELLS

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-106-3	20 CLOSED VENT STEAM DRIVE WEL	3020-09 A	20	10.23	204.60	A	20 CLOSED-VENT TEOR WELLS
C-311-111-8	70 WELLS	3020-09 A	70	10.23	716.10	A	TEOR OPERATION WITH 70 STEAM ENHANCED WELLS SERVED BY WELL VENT VAPOR CONTROL SYSTEM #CC-1-13D WITH SEPARATOR, LOW PRESSURE AIR COOLER AND CONDENSATE COLLECTOR (13 D SOUTHEAST)
C-311-112-16	326 wells with vapor recovery	3020-09 A	326	10.23	3,334.98	A	TEOR OPERATION #6C-CC-1 SERVING 20 AUTOMATIC WELL TESTERS AND 326 STEAM-ENHANCED WELLS WITH LIQUID KNOCK OUT VESSEL (OPTIONAL) WITH DISTRICT-APPROVED VAPOR CONTROL SYSTEM
C-311-114-9	23.0 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	NON-COMPLIANT DORMANT 23 MMBTU/HR HOPPER STEAM GENERATOR, HSG-36, NATURAL GAS FIRED WITH ONE NORTH AMERICAN BURNER, DIS #21013-66
C-311-117-9	23.0 MMBtu/hr SG	3020-02 H	1	1,128.00	1,128.00	A	NON-COMPLIANT DORMANT 23 MMBTU/HR HOPPER STEAM GENERATOR, HSG-1, NATURAL GAS FIRED, WITH ONE NORTH AMERICAN BURNER, DIS #5702-66
C-311-122-8	214,326 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,103 BBL FIXED PETROLEUM STORAGE TANK #T-101 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129
C-311-123-8	214,326 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-102 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129
C-311-124-8	214,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-103 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129
C-311-125-8	84,500 GALLON TANK	3020-05 D	1	203.00	203.00	A	2,013 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-400 SERVED BY SHARED VAPOR RECOVERY SYSTEM ON PERMIT UNIT C-311-129
C-311-126-8	214,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-300 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129
C-311-127-8	214,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,103 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-200 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129
C-311-128-8	127,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	3,020 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-201 SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-129
C-311-129-10	216,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	2,013 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-500 SERVED BY A VAPOR RECOVERY SYSTEM INCLUDING CONDENSER, COMPRESSOR, CONDENSATE COLLECTION VESSEL, TRANSFER PUMP AND BACK-UP/STANDBY ELECTRIC COMPRESSOR SERVED BY SHARED CASING COLLECTION SYSTEM FOR SECTION 6C - PERMIT UNIT C-311-112 AND TANK PERMIT UNITS C-311-122, -123, -124, -125, -126, -127, -128 AND -129

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-146-23	84,546 GALLON TANK	3020-05 D	1	203.00	203.00	A	2,013 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-23 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267
C-311-147-14	84,500 GALLON TANK	3020-05 D	1	203.00	203.00	A	2,013 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-22 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267
C-311-150-14	214,326 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,103 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-18 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267
C-311-163-14	197,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	4,697 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-31 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-164-14	197,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	4,697 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-32 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-165-14	235,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,592 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-29 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-166-14	235,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,592 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-30 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-167-14	150,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	3,579 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-33 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-168-14	150,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	3,579 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-34 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-169-14	60,000 GALLON TANK	3020-05 D	1	203.00	203.00	A	1,424 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-60 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-170-14	80,000 GALLON TANK	3020-05 D	1	203.00	203.00	A	1,901 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 25-37 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-177-17	210,000 gallon	3020-05 E	1	270.00	270.00	A	5,047 BBL FIXED ROOF FREE WATER KNOCK OUT TANK # 25-42 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-268
C-311-180-3	19.7 KGAL STORAGE TANK #T-3	3020-05 B	1	103.00	103.00	A	523 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-3
C-311-181-3	19.7 KGAL STORAGE TANK #T-4	3020-05 B	1	103.00	103.00	A	523 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-4
C-311-182-3	11.3 KGAL STORAGE TANK #T-5	3020-05 B	1	103.00	103.00	A	269 BBL FIXED ROOF PETROLEUM STORAGE TANK #T-5
C-311-196-14	210,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,000 BBL FIXED ROOF WASH TANK # 13-29 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267
C-311-197-14	210,000 GALLON TANK	3020-05 E	1	270.00	270.00	A	5,000 BBL FIXED ROOF WASH TANK # 13-30 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267
C-311-198-14	11,300 GALLON TANK	3020-05 B	1	103.00	103.00	A	270 BBL FIXED ROOF CRUDE OIL TANK # 13-13 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267
C-311-205-3	20 OPEN-VENT CYCLIC WELLS.	3020-09 A	20	10.23	204.60	A	20 OPEN-VENT CYCLIC WELLS
C-311-215-3	42 KGAL TANK #24-1	3020-05 C	1	149.00	149.00	A	1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-1

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-216-3	42 KGAL TANK #24-2	3020-05 C	1	149.00	149.00	A	1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-2
C-311-217-3	84 KGAL TANK #24-3	3020-05 D	1	203.00	203.00	A	2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-3
C-311-219-3	42 KGAL TANK #24-5	3020-05 C	1	149.00	149.00	A	1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-5
C-311-220-3	42 KGAL TANK #24-6	3020-05 C	1	149.00	149.00	A	1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-6
C-311-221-3	84 KGAL TANK #24-7	3020-05 D	1	203.00	203.00	A	2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-7
C-311-222-6	126,000 GALLON WASH TANK #24-9	3020-05 E	1	270.00	270.00	A	3000 BBL CONE BOTTOM WASH TANK #24-9
C-311-223-4	42,000 GAL STORAGE TANK #24-10	3020-05 C	1	149.00	149.00	A	1000 BBL FIXED ROOF PETROLEUM STORAGE TANK #24-10
C-311-227-3	1 Nozzle	3020-11 A	1	38.00	38.00	A	GASOLINE DISPENSING OPERATION WITH ONE 2,000 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROS EVR PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE(S) SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116-F)
C-311-232-2	42,000 gal	3020-05 C	1	149.00	149.00	A	1000 BBL FIXED ROOF PETROLEUM STORAGE TANK
C-311-233-2	42,000 gal	3020-05 C	1	149.00	149.00	A	1000 BBL FIXED ROOF PETROLEUM STORAGE TANK
C-311-234-2	42,000 gal	3020-05 C	1	149.00	149.00	A	1000 BBL FIXED ROOF PETROLEUM STORAGE TANK
C-311-235-2	600 bhp IC engine	3020-10 D	1	525.00	525.00	A	600 BHP CUMMINGS MODEL #KTA19C52 (SERIAL #31134968) DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR
C-311-236-8	214,200 GALLONS	3020-05 E	1	270.00	270.00	A	5,100 BBL FIXED ROOF CRUDE OIL STORAGE TANK # 13-19 SERVED BY SHARED VAPOR RECOVERY SYSTEM PTO C-311-267
C-311-238-3	532 bhp	3020-10 D	1	525.00	525.00	A	TRANSPORTABLE TIER 3 CERTIFIED DIESEL-FIRED IC ENGINE UP TO 532 HP FOR MECHANICAL PUMPING, COMPRESSION, OR POWERING AN ELECTRICAL GENERATOR
C-311-239-2	157 bhp	3020-10 B	1	129.00	129.00	A	157 BHP CATERPILLAR MODEL LC3034B S/N E5M02254 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR:
C-311-240-3	25,200 gallons	3020-05 C	1	149.00	149.00	A	600 BBL PRESSURE VESSEL VENTED TO TEOR OPERATION C-311-79
C-311-248-0	85 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR SG-13/25-XA WITH NORTH AMERICAN MODEL 4231-85 GLE LOW-NOX BURNER, OR EQUIVALENT, AND FLUE GAS RECIRCULATION
C-311-253-1	324 bhp	3020-10 C	1	264.00	264.00	A	324 BHP INTERMITTENT CUMMINS MODEL QSB7-G5NR3 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR. (13D WATER PLANT)
C-311-254-0	85 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR SG-6-36 WITH NORTH AMERICAN MODEL 4231-85 GLE LOW-NOX BURNER AND FLUE GAS RECIRCULATION

Detailed Facility Report

For Facility=311 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-311-265-1	42,000 gallons	3020-05 C	1	149.00	149.00	A	1000 BBL VESSEL SERVED BY VAPOR CONTROL SYSTEM LISTED ON C-311-111
C-311-266-1	10,500 gallons	3020-05 B	1	103.00	103.00	A	250 BBL CRUDE OIL DRAIN TANK CLAREMONT T-6
C-311-267-5	100 electric horsepower	3020-01 D	1	345.00	345.00	A	13D OIL CLEANING PLANT VAPOR RECOVERY SYSTEM, SERVING PERMIT UNITS C-311-146, '-147, '-150, '-196, '-197, '-198, '-236, AND '-271, INCLUDING TWO (2) 50 HP COMPRESSORS, REGULATOR, AND VAPOR PIPING TO DISTRICT APPROVED STEAM GENERATORS C-311-20, '-21, '-25, '-28, '-30, '-36, '-37, '-38, '-39, '-40 AND/OR '-41, OR DOGGR APPROVED VAPOR DISPOSAL WELLS
C-311-268-2	50 electric horsepower	3020-01 C	1	217.00	217.00	A	25D OIL CLEANING PLANT VAPOR RECOVERY SYSTEM, SERVING PERMIT UNITS C-311-163, '-164, '-165, '-166, '-167, '-168, '-169, '-170 AND '-177, INCLUDING 50 HP COMPRESSOR, TWO VERTICAL SCRUBBERS, FIN FAN COOLER, REGULATOR, AND VAPOR PIPING TO DISTRICT APPROVED STEAM GENERATORS C-311-20, '-21, '-25, '-28, '-30, '-36, '-37, '-38, '-39, '-40 AND/OR '-41, OR DOGGR APPROVED VAPOR DISPOSAL WELLS
C-311-269-0	10.6 KGAL STORAGE TANK CO-T-57	3020-05 B	1	103.00	103.00	A	TANK #CO-T-57: 10,584 GALLON FIXED ROOF CRUDE OIL STORAGE TANK, 15'D X 8'H, CAPACITY: 252 BBLS.
C-311-270-0	10.6 KGAL STORAGE TANK CO-T-58	3020-05 B	1	103.00	103.00	A	TANK #CO-T-58: 10,584 GALLON FIXED ROOF CRUDE OIL STORAGE TANK, 15'D X 8'H, CAPACITY: 252 BBLS.
C-311-271-1	84,000 gallons	3020-05 D	1	203.00	203.00	A	2,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK (OR DISTRICT APPROVED EQUIVALENT), #13-13A SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT UNIT C-311-267

Number of Facilities Reported: 1