



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

MAY 01 2019



Mr. Rene Soto
Bronco Wine Company
PO Box 789
Ceres, CA 95307

Re: Notice of Preliminary Decision – Title V Permit Renewal
Facility Number: N-1665
Project Number: N-1173371

Dear Mr. Soto:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Bronco Wine Company at 6342 Bystrum Road, Ceres, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Brian Clerico, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95358-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation Bronco Wine Company N-1665

TABLE OF CONTENTS

I.	PROPOSAL.....	1
II.	FACILITY LOCATION	1
III.	EQUIPMENT LISTING	1
IV.	GENERAL PERMIT TEMPLATE USAGE	2
V.	SCOPE OF EPA AND PUBLIC REVIEW	2
VI.	APPLICABLE REQUIREMENTS ADDRESSED BY GENERAL PERMIT TEMPLATES.....	2
VII.	APPLICABLE REQUIREMENTS NOT ADDRESSED BY GENERAL PERMIT TEMPLATES.....	3
VIII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE	4
IX.	PERMIT REQUIREMENTS.....	5
X.	PERMIT SHIELD	9
XI.	CALIFORNIA ENVIRONMENT QUALITY ACT	10
XII.	PERMIT CONDITIONS	10
XIII.	ATTACHMENTS	10
A.	Draft Renewed Title V Operating Permit	
B.	Previous Title V Operating Permit	
C.	Detailed Facility List	

TITLE V PERMIT RENEWAL EVALUATION

Winery Facility

Engineer: Kamaljit Sran

Date: April 25, 2019

Facility Number: N-1665

Facility Name: Bronco Wine Company

Mailing Address: P O Box 789
Ceres, CA 95307

Contact Name: Rene Soto

Phone: (209) 272-3259

Responsible Official: Rene Soto

Title: Maintenance Manager

Project #: N-1173371

Deemed Complete: November 27, 2017

I. PROPOSAL

Sutter Home Winery was issued a renewed Title V permit on April 17, 2014. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the last renewal Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

Bronco Wine Company is located at 6342 Bystrum Road, Ceres in Stanislaus County, CA

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit Templates:

A. Template SJV-UM-0-3 Facility Wide Umbrella

The applicant has requested to utilize general permit template SJV-UM-0-3, Facility Wide Umbrella. Based on the information submitted in the Template Qualification Form, the applicant qualifies for the use of this template.

Template SJV-UM-0-3 conditions have been added as conditions 1 through 40 for the facility wide requirements (N-1665-0-3).

V. SCOPE OF EPA AND PUBLIC REVIEW

Model general permit templates have been previously subject to EPA and public review. The terms and conditions from the model general permit templates as identified above are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The following permit conditions, including their underlying applicable requirements, originate from model general permit templates and are not subject to further EPA and Public review: conditions 1 through 40 for the facility wide requirements (N-1665-0-3).

VI. APPLICABLE REQUIREMENTS ADDRESSED BY GENERAL PERMIT TEMPLATES

- District Rule 1070, Inspections (amended December 17, 1992)
- District Rule 1100, Equipment Breakdown (amended December 17, 1992)
- District Rule 2010, Permits Required (amended December 17, 1992)
- District Rule 2031, Transfer of Permits (amended December 17, 1992)
- District Rule 2040, Applications (amended December 17, 1992)

- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080, Conditional Approval (amended December 17, 1992)
- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001), Sections 5.2, 9.1.1, 9.4, 9.5, 9.7, 9.8, 9.9, 9.13.1, 9.13.2, 9.16, and 10.0
- District Rule 4101, Visible Emissions (amended December 17, 2005)
- District Rule 4601, Architectural Coatings (amended December 17, 2009)
- District Rules 8021, 8031, 8041, 8051, and 8061, Fugitive Dust (PM₁₀) Emissions (amended August 19, 2004)
- District Rule 8071, Fugitive Dust (PM₁₀) Emissions (amended September 16, 2004)
- 40 CFR 61, Subpart M – Asbestos (amended September 18, 2003)

VII. APPLICABLE REQUIREMENTS NOT ADDRESSED BY GENERAL PERMIT TEMPLATES

A. Rules Updated or Evaluated

- District Rule 2020, Exemptions (amended August 18, 2011 ⇒ amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule (amended April 21, 2011 ⇒ amended February 18, 2016)
- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001)
- 40 CFR 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines (amended August 15, 2016)
- CFR 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (amended July 7, 2016)
- 40 CFR Part 64, Compliance Assurance Monitoring Program (adopted October 22, 1997)

- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners (amended June 25, 2013)
- 40 CFR Part 82, Subpart F, Recycling and Emission Reduction (amended December 27, 2017)¹

B. Rules Rescinded

There are no applicable rule that was rescinded since the initial Title V permit.

C. Rules Adopted

There are no applicable rule that was adopted since the initial Title V permit.

D. Rules Not Updated

- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)
- District Rule 4305, Boilers, Steam Generators, and Process Heaters - Phase 2 (amended August 21, 2003)
- District Rule 4306, Boilers, Steam Generators, and Process Heaters - Phase 3 (amended October 16, 2008)
- District Rule 4320, Advanced Emission Reduction Options For Boilers, Steam Generators, and Process Heaters Greater Than 5.0 MMBtu/hr (amended October 16, 2008)
- District Rule 4621, Gasoline Transfer Into Stationary Storage Containers, Delivery Vessels, And Bulk Plants (amended December 19, 2013)
- District Rule 4622, Gasoline Transfer Into Motor Vehicle Fuel Tanks (amended December 19, 2013)
- District Rule 4694, Wine Fermentation and Storage Tanks (amended December 15, 2005)

¹ This subpart was amended since last renewal TV permit was issued. However, the amendments to this subpart does not have any effect on existing permit requirements as addressed by condition 27 of permit unit N-1665-0-2 on the draft renewed permit.

- District Rule 4702, Internal Combustion Engines (amended November 14, 2013)
- District Rule 4801, Sulfur Compounds (amended December 17, 1992)

VIII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following rules are not federally enforceable and will not be discussed in further detail:

A. Rules Added (None)

B. Rules Not Updated

1. District Rule 4102, Nuisance (as amended December 17, 1992)

Condition 41 of the facility-wide requirements (N-1665-0-3) and condition 2 of the requirements for permit units N-1665-452-3 & -516-1 and -507-4 & -515-3 are based on District Rule 4102 and will therefore not be discussed any further.

2. District Rule 4694, Wine Fermentation and Storage Tanks (amended December 15, 2005)

The purpose of this rule is to reduce emissions of Volatile Organic Compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any facility with VOC emissions in excess of 10 tons per year. For those facilities to which the rule applies, the requirements of the rule are applicable to any fermentation or storage tank with capacity in excess of 5,000 gallons. The rule was adopted on December 15, 2005 and submitted to EPA for approval into the State Implementation Plan (SIP).

On November 29, 2012, the EPA approved an amended SIP submittal which excludes the fermentation provisions of the Rule 4694 while maintaining the storage provisions. Therefore, the fermentation provisions are not federally enforceable. All other provisions are considered to be federally enforceable.

Conditions 43 through 47 of the facility-wide requirements (N-1655-0-3) are based on District Rule 4694 fermentation requirements and are therefore not federally enforceable.

3. Title 17 CCR 93115, ATCM for Stationary Compression Ignition Engines (amended May 19, 2011)

All applicable requirements for this ATCM are satisfied via District Rule 4702 and 40 CFR 60 subpart IIII. No additional compliance discussion is needed.

IX. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the last Title V permit renewal or un-amended rules for which the original permit conditions have been revised.

A. District Rule 2020 - Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits and specifies recordkeeping requirements to verify such exemptions. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201 - New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since facility's Title V permit was last renewed. However the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into current Title V permit.

C. District Rule 2520 - Federally Mandated Operating Permits

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

D. 40 CFR 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

- a. N-1665-452-3 & -516-2: Emergency IC Engine

b. N-1665-507-4 & -515-3: Fire Pump Engine

These engines are subject to 40 CFR 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines because they were manufactured after April 1, 2006, as required by Section 60.4200(a)(2)(i).

Section 60.4205(b) requires the engine to comply with the standards in section 60.4202 for all pollutants for the same model year and maximum engine power. Section 60.4202(a)(ii) requires that engines over 50 bhp must meet the EPA standards in 40 CFR 89.112 and 40 CFR 89.113. According to the Manufacturer's Emission Data the engines will comply with the all standards.

Sections 60.4206 and 60.4211(a) require that the owner/operator operate and maintain the engine according to the manufacturer's written instructions or procedures developed by the owner or operator that are approved by the engine manufacturer, over the entire life of the engine. Condition 5 of the requirements for permit units N-1665-452-3 & -516-1 and -507-4 & -515-3 ensure compliance with this section.

Section 60.4207(a) requires that by October 1, 2007, the owner/operator must use fuel that complies with 40 CFR 80.510(a). This means that the fuel must have a sulfur content of 500 parts per million (ppm) maximum, a cetane index of 40 or a maximum aromatic content of 35 volume percent. This requirement is obsolete and been superseded by a requirement as described below.

Section 60.4207(b) requires that by October 1, 2010, the owner/operator must use fuel that complies with 40 CFR 80.510(b). This means that the fuel must have a sulfur content of 15 parts per million (ppm) maximum, and the same cetane index or aromatic content. Condition 3 of the requirements for permit units N-1665-452-3 & -516-1 and -507-4 & -515-3 ensure compliance with this section.

Section 60.4209(a) requires a non-resettable hour meter. This requirement is already in the standard permit conditions. Condition 4 of the requirements for permit units N-1665-452-3 & -516-1 and -507-4 & -515-3 ensure compliance with this section.

Section 60.4211(c) requires that owner or operator must comply with the emission standards specified in §60.4204(b) or §60.4205(b), or §60.4205(c) for fire pump engine by purchasing an engine certified to the emission standards in §60.4204(b), or §60.4205(b) or (c), as applicable. These engine will comply with the requirements of Section 60.4211(c) because these engines have been certified in accordance with 40 CFR Part 89.

Section 60.4211(f) requires that emergency stationary ICE operate for maintenance, testing, and required regulatory purposes for a maximum of 100 hours per calendar year. Condition 10 of the requirements for permit units N-1665-452-3 & -516-1 and -507-4 & -515-3 ensure compliance with this section.

The owner/operator is not required to perform tests in accordance with section 60.4212 or 60.4213.

Section 60.4214 states that owner/operators do not have to submit an initial notification to EPA for emergency engines.

Because the engines do not have a diesel particulate filter, it is not subject to section 60.4214(c).

E. 40 CFR Part 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

- a. N-1665-452-3 & -516-2: Emergency IC Engine
- b. N-1665-507-4 & -515-3: Fire Pump Engine

The requirements of 40 CFR Part 63, Subpart ZZZZ, National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines, are applicable to owners and operators of a stationary RICE located at a major or area source of HAP emissions. This facility is not a major source of HAP emissions and is therefore, by definition, and area source of HAP emissions. Therefore, the requirements of this subpart are applicable to these engines.

These engines comply with the NESHAPS by complying with NSPS, Subpart IIII, per Section 63.6590 (C) (1) of the NESHAPS 40 CFR 63, Subpart ZZZZ.

G. 40 CFR Part 64-CAM

§64.2 – Applicability

This section requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

This regulation was last amended on 10/22/1997; however, the Rule 2201 Major Source thresholds for NO_x and VOC were lowered from 50,000 to 20,000 lb/year via the 12/18/2008 amendment to Rule 2201 (the amended rule was not effective until 6/10/10). The facility's permits were evaluated for CAM purposes in the last renewal Title V using the 20,000 lb/year NO_x and VOC thresholds. Consequently, a CAM discussion is not required for these units. For the permit units that were installed since issuance of last TV renewal, CAM applicability and requirements are being addressed as following.

a. N-1665-514-2: 16.531 MMBtu/hr Boiler

As this boiler does not use any add-on control devices to achieve compliance with any emission limitation or standard for any applicable pollutant. Therefore CAM is not applicable to this boiler.

b. N-1665-515-3: Fire Pump Engine

c. N-1665-516-1 Emergency IC Engine

Per section, 40 CFR 64.2(b) permit units subject to New Source Performance Standards (NSPS) or National Emission Standard for Hazardous Air Pollutants (NESHAP) that were proposed after November 1990 are not subject to the CAM rule.

These engines are subject to 40 CFR 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines, therefore are exempt from CAM.

X. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

a. SJV-UM-0-3, Facility-Wide Umbrella General Permit Template

By submitting model general permit template SJV-UM-0-3, the applicant has requested that a permit shield be granted for all the applicable requirements identified by the template. Therefore, the permit shield, as

granted in the model general template is included as condition 39 and 40 of the facility wide requirements (N-1665-0-2).

B. Requirements not Addressed by Model General Permit Templates

The applicant is not requesting any permit shields.

XI. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XII. PERMIT CONDITIONS

See Attachment A – Draft Renewed Title V Operating Permit.

XIII. ATTACHMENTS

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Facility List

ATTACHMENT A

Draft Renewed Title V Operating Permits

San Joaquin Valley Air Pollution Control District

FACILITY: N-1665-0-3

EXPIRATION DATE: 04/30/2018

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: BRONCO WINE COMPANY

Location: 6342 BYSTRUM RD, CERES, CA 95307

N-1665-0-3 : May 1 2019 8:28AM -- SRANK

9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On April 30, 2008, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
44. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District every three years thereafter on or before December 1. [District Rule 4694]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

45. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District every three years on or before July 1. [District Rule 4694]
46. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of District Rule 4694 shall be submitted to the District by every year thereafter on or before March 1. [District Rule 4694]
47. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-1-6

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12.6 MMBTU/HR HURST MODEL 300 NATURAL GAS-FIRED BOILER WITH ST JOHNSON MODEL RX 300F ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 15 ppmv NO_x @ 3% O₂ or 0.018 lb-NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.005 lb-PM₁₀/MMBtu, 200 ppmv CO @ 3% O₂ or 0.148 lb-CO/MMBtu, 0.004 lb-VOC/MMBtu. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
5. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NO_x emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO_x emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
6. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
7. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
9. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
11. This unit shall be tested for compliance with the NO_x and CO emissions limits at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, and 4306] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
15. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
18. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit
19. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]
Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-5-6

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 5,200 CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I ENHANCED VAPOR RECOVERY (EVR) SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-F), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116-F)

PERMIT UNIT REQUIREMENTS

1. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
9. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
11. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
13. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
14. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

16. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
17. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
18. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
19. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
22. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
23. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
26. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-6-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

2,648 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 21) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-7-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 22) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-8-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 23) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-9-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

4,012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 40) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-10-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

4,012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 41) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-17-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

6,700 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 59) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-18-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

6,652 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 60) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-21-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

6,074 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 63) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-22-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 71) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-23-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 72) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-24-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 73) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-25-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 74 WITH PRESSURE/VACUUM VALVE)

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-26-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 75) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-27-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 76) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-28-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 77) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-29-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 78) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-30-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 83) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-31-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 84) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-32-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 85) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-33-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 89) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-34-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 90) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-38-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,093 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 104) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-39-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,500 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 105) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-40-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694]
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694]
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-41-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-42-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 110) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-43-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 111) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-44-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 112) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-45-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 113) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-46-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 114) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-47-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 115) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-48-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-49-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-50-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 118) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-51-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 119) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-52-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 120) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-53-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 121) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-54-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 122) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-55-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 123) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-56-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

11,888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 124) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-57-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

11,888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 125) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-58-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 126) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-59-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 130) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-60-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 131) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-61-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 132) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-62-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 133) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-63-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 134) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-64-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 135) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-65-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 141) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-66-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 142) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-67-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 143) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-68-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 144) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-69-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 150) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-70-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 151) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-71-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 152) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-72-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 153) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-73-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 154) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-74-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 155) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-75-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-76-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 157) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-77-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 158) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-78-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 159) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-79-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 160) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-80-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 161) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-81-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 162) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-82-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 163) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-83-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 164) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-84-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 165) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-85-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 166) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-86-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 167) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-87-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 168) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-88-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 169) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-89-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 170) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-90-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 171) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-91-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 172) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-92-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 173) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-93-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 174) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-94-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 175) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-95-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 176) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-96-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 177) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-97-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 178) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-98-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 179) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-99-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 180) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-100-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 181) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-101-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 182) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-102-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 183) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-103-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 184) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-104-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 185) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-105-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 186) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-106-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 220) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-107-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 221) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-108-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 222) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-109-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 223) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-110-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 224) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-111-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 225) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-112-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 226) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-113-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 227) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-117-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 251) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-118-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 252) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-119-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 253) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-120-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 254) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-121-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 255) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-122-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 256) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-123-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 301) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-124-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 302) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-125-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 303) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-126-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,033 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 501) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-127-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

54,971 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 502) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-128-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,017 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 503) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-129-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 504) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-130-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

54,881 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 505) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-131-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,141 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 506) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-132-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

54,930 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 507) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-133-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,030 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 508) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-134-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 511) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-135-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 512) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-136-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 513) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-137-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 514) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-138-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 515) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-139-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 516) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-140-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 517) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-141-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 518) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-142-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 519) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-143-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 520) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-144-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 521) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-145-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 522) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-146-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 523) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-147-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 524) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-148-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 525) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-149-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 526) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-150-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 527) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-151-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 528) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-152-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 529) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-153-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 530) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-154-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-155-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-156-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-157-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-158-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-159-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-160-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-161-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-162-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-163-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-164-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-165-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-166-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1017) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-167-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1018) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-168-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-169-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-170-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-171-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-172-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-173-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1036) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-174-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1037) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-175-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1038) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-176-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1039) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-177-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1040) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-178-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1041) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-179-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-180-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-181-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-182-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1045) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-183-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1046) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-184-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1047) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-185-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1048) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-186-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1049) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-187-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1050) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-188-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-189-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-190-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-191-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-192-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-193-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-194-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-195-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-196-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-197-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1063) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-198-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1064) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-199-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1065) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-200-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1066) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-201-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1067) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-202-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1071) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-203-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-204-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-205-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-206-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-207-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-208-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-209-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1081) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-210-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1082) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-211-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1083) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-212-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1084) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-213-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1085) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-214-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1086) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-215-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1087) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-216-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1101) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-217-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1102) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-218-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1103) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-219-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1104) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-220-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1105) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-221-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-222-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-223-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1111) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-224-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1112) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-225-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1113) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-226-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1114) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-227-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1115) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-228-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-229-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-230-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1301) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-231-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1302) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-232-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1303) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-233-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1304) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-234-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1501) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-235-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1502) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-236-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1503) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-237-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1504) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-238-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1505) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-239-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1506) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-240-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-241-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-242-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-243-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-244-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-245-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-246-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-247-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-248-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2017) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-249-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2018) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-250-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2019) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-251-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2020) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-252-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2021) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-253-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2022) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-254-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2023) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-255-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2024) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-256-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2025) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-257-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-258-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-259-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-260-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-261-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-262-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-263-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-264-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-265-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-266-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-267-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-268-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-269-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2058) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-270-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2059) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-271-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2060) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-272-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-273-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-275-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-276-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-277-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-278-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-279-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-280-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-281-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2078) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-282-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2079) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-283-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2080) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-284-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2081) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-285-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2082) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-286-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2121) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-287-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2122) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-288-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2123) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-289-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2124) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-290-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2125) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-291-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2131) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-292-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2132) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-293-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2133) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-294-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2134) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-295-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2135) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-296-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2141) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-297-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2142) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-298-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2143) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-299-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2144) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-300-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2145) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-301-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2146) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-302-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2151) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-303-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2152) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-304-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2153) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-305-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2154) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-306-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2155) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-307-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-308-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2401) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-309-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2402) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-310-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2403) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-311-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3021) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-312-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3022) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-313-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3023) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-314-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3024) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-315-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3025) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-316-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3026) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-317-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3027) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-318-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3028) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-319-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3029) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-320-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3030) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-321-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-322-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-323-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-324-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-325-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-326-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3036) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-327-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3037) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-328-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3038) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-329-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3039) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-330-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3040) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-332-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-333-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-334-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-335-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3045) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-336-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3046) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-337-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3047) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-338-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3048) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-339-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3049) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-340-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3050) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-341-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-342-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-343-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-344-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-345-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-346-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-347-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3058) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-348-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3059) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-349-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3060) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-350-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-351-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-352-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3063) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-353-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3064) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-354-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3065) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-355-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3066) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-356-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3067) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-357-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3068) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-358-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3069) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-359-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3070) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-360-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3071) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-361-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-362-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-363-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-364-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-365-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-366-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-367-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3078) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-368-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3079) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-369-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3080) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-370-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3086) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-371-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3087) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-372-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3088) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-373-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3089) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-374-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3090) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-375-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3096) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-376-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3097) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-377-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3098) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-378-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3099) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-379-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3100) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-380-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-381-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-382-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3108) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-383-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3109) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-384-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3110) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-385-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-386-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-387-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3118) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-388-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3119) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-389-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3120) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-390-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3126) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-391-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3127) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-392-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3128) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-393-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3129) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-394-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3130) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-395-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3136) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-396-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3137) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-397-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3138) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-398-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3139) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-399-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3140) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-400-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3146) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-401-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3147) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-402-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3148) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-403-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3149) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-404-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3150) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-405-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-406-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3157) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-407-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3158) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-408-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3159) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-409-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3160) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-410-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-411-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-412-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-413-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-414-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-415-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-416-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5007) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-417-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5008) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-418-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5009) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-419-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5010) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-420-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-421-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-422-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

625,878 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 6004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-423-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-424-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-425-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-426-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-427-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-428-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7007) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-429-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7008) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-430-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7009) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-431-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7010) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-432-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-433-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-434-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-435-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-436-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-437-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-438-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7041) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-439-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-440-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-441-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-442-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-443-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-444-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-445-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-446-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK A164) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-447-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C1) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-448-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C2) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-449-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C3) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-452-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

94.5 BHP CATERPILLAR MODEL C4.4 (2442/1800) TIER 2 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap, roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 & 480, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 4.95 g-NOx/bhp-hr, 0.60 g-CO/bhp-hr, or 0.35 g-VOC/bhp-hr. [District Rule 2201, 13 CCR 2423 & 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed 0.15 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 & 4102, 13 CCR 2423 & 17 CCR 93115 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for maintenance, testing, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-1665-496-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:
WINERY WASTEWATER TREATMENT OPERATION

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-497-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1410) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-498-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1411) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-499-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1412) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-500-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1413) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-501-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1414) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-502-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1415) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-503-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1416) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-504-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1417) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-505-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1418) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-506-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1419) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 425,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-507-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

150 BHP CUMMINS MODEL CFP5E-F50 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 & 4801, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII]
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 2.54 g-NOx/bhp-hr, 0.69 g-CO/bhp-hr, or 0.06 g-VOC/bhp-hr. [District Rule 2201, 13 CCR 2423 & 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed 0.088 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 & 4102, 13 CCR 2423 & 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-508-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

23,609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B231) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 23,609 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank, calculated on a 12 month rolling basis, shall not exceed 232,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-509-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

23,609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B232) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 23,609 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank, calculated on a 12 month rolling basis, shall not exceed 232,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-510-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B141) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 14,376 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank, calculated on a 12 month rolling basis, shall not exceed 232,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-511-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B142) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 14,376 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank, calculated on a 12 month rolling basis, shall not exceed 232,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-512-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B71) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 7,290 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank, calculated on a 12 month rolling basis, shall not exceed 232,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-513-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B72) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75°F. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75°F or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75°F or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine throughput in this tank shall not exceed 7,290 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine throughput in this tank, calculated on a 12 month rolling basis, shall not exceed 232,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
8. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine throughput rate (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-514-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15.75 MMBTU/HR NATURAL GAS FIRED CLAYTON SSEG-404-FMB-1 BOILER

PERMIT UNIT REQUIREMENTS

1. The economizer system shall be designed at maximum steam generator firing rate to either 1) reduce the temperature of the economizer flue gas outlet to a value no greater than 90 degrees F above the temperature of the boiler feed water or 2) heat the boiler feed water to a temperature which is no less than the saturation temperature of the steam at the pressure of the steam separator, or 3) reduce the final temperature of the boiler's flue gas to a temperature no greater than 300 degrees F. Feedwater temperature is defined as the temperature of the water stream delivered to the steam generator from the deaerator or feedwater tank. [CCR Title 14, Division 6, Chapter 3, § 15000-15387 (CEQA)]
2. Electric motors driving combustion air fans or induced draft fans shall have an efficiency meeting the standards of the National Electric Manufacturer's Association (NEMA) for "premium efficiency" motors and shall each be operated with a variable speed control or equivalent for control of flow through the fan. [CCR Title 14, Division 6, Chapter 3, § 15000-15387 (CEQA)]
3. The unit shall always operate at least 487 feet away from the nearest property boundary. [District Rule 4102]
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7 ppmv NO_x @ 3% O₂ or 0.008 lb-NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.0076 lb-PM₁₀/MMBtu, 50 ppmv CO @ 3% O₂ or 0.037 lb-CO/MMBtu, 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
16. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. Fuel sulfur content shall be determined using EPA Method 11 or Method 15. [District Rule 4320] Federally Enforceable Through Title V Permit
20. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
21. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
23. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-515-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

146 BHP CUMMINS MODEL CFP5E F50 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE
POWERING A FIRE PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 & 4801, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII]
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 2.52 g-NOx/bhp-hr, 0.746 g-CO/bhp-hr, or 0.092 g-VOC/bhp-hr. [District Rule 2201, 13 CCR 2423 & 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed 0.088 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 & 4102, 13 CCR 2423 & 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-516-1

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

389 BHP IVECO MODEL F2CE9685A-E DIESEL-FIRED EMERGENCY ENGINE (TIER 3 CERTIFIED)-POWERING AN ELECTRICAL GENERATOR.

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 & 4801, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 2.43 g-NOx/bhp-hr, 0.50 g-CO/bhp-hr, or 0.17 g-VOC/bhp-hr. [District Rule 2201, 17 CCR 93115, 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed 0.13 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 & 4102, 17 CCR 93115, 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required reed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT B

Previous Title V Operating Permits

San Joaquin Valley Air Pollution Control District

FACILITY: N-1665-0-2

EXPIRATION DATE: 04/30/2018

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1 and Stanislaus County Rule 110] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0 and Stanislaus County Rule 110] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: BRONCO WINE COMPANY

Location: 6342 BYSTRUM RD, CERES, CA 95307

N-1665-0-2 : May 1 2019 9:07AM -- SRANK

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101 and Stanislaus County Rule 401] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. On April 30, 2008, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin May 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
40. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
41. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
42. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District every three years thereafter on or before December 1. [District Rule 4694]
43. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District every three years on or before July 1. [District Rule 4694]
44. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of District Rule 4694 shall be submitted to the District by every year thereafter on or before March 1. [District Rule 4694]
45. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-1-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12.6 MMBTU/HR HURST MODEL 300 NATURAL GAS-FIRED BOILER WITH ST JOHNSON MODEL RX 300F ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 15 ppmv NO_x @ 3% O₂ or 0.018 lb-NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.005 lb-PM₁₀/MMBtu, 200 ppmv CO @ 3% O₂ or 0.148 lb-CO/MMBtu, 0.004 lb-VOC/MMBtu. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit
5. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NO_x emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NO_x emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
6. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
7. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
9. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
10. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
11. This unit shall be tested for compliance with the NO_x and CO emissions limits at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, and 4306] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
15. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
16. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
18. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit
19. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]
Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-5-5

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 5,200 CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I ENHANCED VAPOR RECOVERY (EVR) SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-F), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116-F)

PERMIT UNIT REQUIREMENTS

1. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
9. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
11. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
13. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
14. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

16. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
17. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
18. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
19. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
22. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
23. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
26. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-6-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

2,648 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 21) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-7-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 22) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-8-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 23) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-9-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

4,012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 40) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-10-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

4,012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 41) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-17-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

6,700 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 59) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-18-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

6,652 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 60) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-21-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

6,074 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 63) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-22-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 71) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-23-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 72) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-24-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 73) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-25-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 74 WITH PRESSURE/VACUUM VALVE)

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-26-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 75) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-27-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 76) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-28-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 77) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-29-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 78) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-30-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 83) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-31-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 84) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-32-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 85) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-33-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 89) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-34-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 90) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-38-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,093 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 104) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-39-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,500 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 105) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-40-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694]
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694]
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694]
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694]
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694]
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694]
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-41-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-42-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 110) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-43-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 111) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-44-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 112) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-45-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 113) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-46-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 114) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-47-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 115) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-48-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-49-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-50-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 118) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-51-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 119) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-52-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 120) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-53-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 121) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-54-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 122) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-55-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 123) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-56-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

11,888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 124) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-57-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

11,888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 125) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-58-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 126) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-59-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 130) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-60-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 131) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-61-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 132) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-62-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 133) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-63-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 134) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-64-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 135) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-65-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 141) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-66-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 142) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-67-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 143) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-68-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 144) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-69-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 150) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-70-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 151) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-71-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 152) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-72-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 153) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-73-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 154) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-74-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 155) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-75-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-76-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 157) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-77-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 158) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-78-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 159) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-79-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 160) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-80-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 161) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-81-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 162) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-82-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 163) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-83-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 164) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-84-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 165) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-85-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 166) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-86-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 167) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-87-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 168) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-88-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 169) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-89-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 170) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-90-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 171) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-91-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 172) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-92-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 173) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-93-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 174) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-94-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 175) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-95-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 176) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-96-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 177) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-97-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 178) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-98-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 179) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-99-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 180) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-100-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 181) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-101-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 182) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-102-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 183) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-103-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 184) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-104-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 185) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-105-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 186) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-106-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 220) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-107-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 221) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-108-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 222) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-109-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 223) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-110-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 224) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-111-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 225) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-112-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 226) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-113-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 227) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-117-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 251) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-118-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 252) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-119-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 253) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-120-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 254) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-121-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 255) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-122-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 256) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-123-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 301) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-124-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 302) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-125-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 303) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-126-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,033 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 501) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-127-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

54,971 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 502) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-128-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,017 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 503) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-129-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 504) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-130-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

54,881 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 505) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-131-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,141 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 506) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-132-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

54,930 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 507) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-133-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

55,030 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 508) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-134-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 511) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-135-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 512) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-136-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 513) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-137-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 514) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-138-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 515) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-139-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 516) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-140-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 517) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-141-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 518) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-142-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 519) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-143-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 520) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-144-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 521) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-145-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 522) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-146-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 523) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-147-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 524) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-148-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 525) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-149-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 526) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-150-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 527) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-151-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 528) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-152-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 529) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-153-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 530) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-154-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-155-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-156-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-157-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-158-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-159-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-160-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-161-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-162-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-163-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-164-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-165-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-166-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1017) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-167-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1018) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-168-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-169-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-170-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-171-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-172-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-173-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1036) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-174-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1037) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-175-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1038) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-176-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1039) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-177-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1040) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-178-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1041) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-179-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-180-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-181-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-182-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1045) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-183-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1046) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-184-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1047) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-185-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1048) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-186-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1049) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-187-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1050) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-188-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-189-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-190-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-191-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-192-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-193-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-194-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-195-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-196-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-197-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1063) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-198-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1064) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-199-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1065) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-200-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1066) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-201-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1067) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-202-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1071) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-203-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-204-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-205-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-206-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-207-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-208-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-209-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1081) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-210-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1082) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-211-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1083) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-212-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1084) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-213-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1085) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-214-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1086) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-215-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1087) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-216-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1101) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-217-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1102) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-218-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1103) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-219-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1104) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-220-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1105) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-221-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-222-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-223-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1111) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-224-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1112) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-225-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1113) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-226-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1114) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-227-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1115) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-228-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-229-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-230-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1301) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-231-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1302) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-232-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1303) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-233-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1304) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-234-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1501) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-235-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1502) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-236-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1503) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-237-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1504) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-238-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1505) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-239-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1506) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-240-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-241-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-242-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-243-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-244-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-245-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-246-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-247-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-248-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2017) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-249-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2018) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-250-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2019) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-251-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2020) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-252-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2021) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-253-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2022) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-254-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2023) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-255-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2024) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-256-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2025) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-257-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-258-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-259-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-260-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-261-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-262-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-263-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-264-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-265-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-266-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-267-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-268-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-269-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2058) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-270-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2059) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-271-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2060) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-272-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-273-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-275-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-276-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-277-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-278-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-279-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-280-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-281-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2078) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-282-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2079) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-283-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2080) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-284-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2081) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-285-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2082) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-286-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2121) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-287-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2122) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-288-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2123) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-289-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2124) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-290-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2125) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-291-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2131) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-292-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2132) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-293-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2133) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-294-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2134) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-295-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2135) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-296-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2141) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-297-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2142) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-298-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2143) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-299-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2144) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-300-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2145) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-301-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2146) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-302-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2151) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-303-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2152) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-304-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2153) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-305-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2154) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-306-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2155) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-307-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-308-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2401) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-309-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2402) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-310-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2403) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-311-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3021) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-312-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3022) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-313-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3023) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-314-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3024) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-315-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3025) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-316-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3026) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-317-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3027) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-318-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3028) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-319-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3029) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-320-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3030) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-321-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3031) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-322-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3032) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-323-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3033) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-324-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3034) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-325-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3035) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-326-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3036) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-327-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3037) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-328-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3038) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-329-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3039) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-330-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3040) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-332-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-333-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-334-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-335-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3045) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-336-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3046) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-337-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3047) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-338-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3048) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-339-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3049) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-340-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3050) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-341-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-342-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-343-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-344-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3055) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-345-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3056) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-346-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3057) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-347-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3058) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-348-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3059) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-349-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3060) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-350-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3061) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-351-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3062) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-352-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3063) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-353-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3064) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-354-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3065) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-355-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3066) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-356-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3067) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-357-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3068) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-358-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3069) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-359-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3070) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-360-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3071) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-361-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3072) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-362-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3073) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-363-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3074) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-364-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3075) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-365-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3076) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-366-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3077) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-367-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3078) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-368-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3079) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-369-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3080) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-370-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3086) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-371-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3087) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-372-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3088) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-373-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3089) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-374-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3090) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-375-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3096) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-376-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3097) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-377-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3098) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-378-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3099) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-379-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3100) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-380-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3106) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-381-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3107) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-382-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3108) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-383-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3109) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-384-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3110) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-385-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3116) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-386-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3117) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-387-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3118) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-388-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3119) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-389-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3120) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-390-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3126) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-391-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3127) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-392-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3128) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-393-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3129) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-394-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3130) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-395-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3136) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-396-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3137) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-397-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3138) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-398-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3139) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-399-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3140) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-400-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3146) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-401-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3147) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-402-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3148) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-403-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3149) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-404-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3150) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-405-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3156) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-406-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3157) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-407-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3158) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-408-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3159) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-409-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3160) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-410-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-411-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-412-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-413-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-414-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-415-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-416-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5007) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-417-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5008) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-418-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5009) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-419-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5010) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-420-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-421-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-422-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

625,878 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 6004) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-423-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7001) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-424-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7002) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-425-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7003) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-426-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7005) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-427-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7006) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-428-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7007) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-429-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7008) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-430-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7009) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-431-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7010) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-432-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7011) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-433-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7012) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-434-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7013) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-435-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7014) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-436-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7015) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-437-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7016) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-438-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7041) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-439-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7042) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-440-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7043) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-441-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7044) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-442-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7051) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-443-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7052) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-444-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7053) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-445-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7054) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-446-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK A164) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-447-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C1) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-448-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C2) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-449-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C3) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume processed or stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-452-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

94.5 BHP CATERPILLAR MODEL C4.4 (2442/1800) TIER 2 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap, roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 4.95 g-NOx/bhp-hr, 0.60 g-CO/bhp-hr, or 0.35 g-VOC/bhp-hr. [District Rule 2201, 13 CCR 2423, and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed 0.15 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 & 4102 and 13 CCR 2423 & 17 CCR 93115] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for maintenance, testing, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63.6603/66.6640 Table 2d, Row 1.a] Federally Enforceable Through Title V Permit
13. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 1.b] Federally Enforceable Through Title V Permit
14. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 1.c] Federally Enforceable Through Title V Permit
15. The permittee shall keep records of the maintenance conducted on the engine. [40 CFR 63.6655(e)] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
17. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-496-1

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

WINERY WASTEWATER TREATMENT OPERATION

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: BRONCO WINE COMPANY

Location: 6342 BYSTRUM RD, CERES, CA 95307

N-1665-496-1 : May 1 2019 9:11AM -- SRANK

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-497-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1410) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-498-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1411) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-499-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1412) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-500-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1413) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-501-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1414) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-502-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1415) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent, EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-503-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1416) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-504-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1417) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-505-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1418) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent, EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-506-4

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1419) WITH A PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 15,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent, EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-507-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

170 BHP (INTERMITTENT) CUMMINS MODEL CFP5E-F50 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801; 17 CCR 93115 and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
5. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 2.54 g-NOx/bhp-hr, 0.69 g-CO/bhp-hr, or 0.06 g-VOC/bhp-hr. [District Rule 2201, 13 CCR 2423, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed 0.088 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102; 13 CCR 2423, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems". Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4102 and 4702; and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-508-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

23,609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B231) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 23,609 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-509-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

23,609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B232) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 23,609 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-510-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B141) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 14,376 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-511-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

14,376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B142) WITH PRESSURE/VACUUM VALVE
LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 14,376 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-512-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B71) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 7,290 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent: EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-513-3

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

7,290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B72) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 14.0 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 7,290 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513, calculated on a twelve month rolling basis, shall not exceed 720 pounds per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Combined annual VOC emissions from wine storage operations under permit units N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than 8 volume percent, EF = 0.067 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 8 and less than 10 volume percent, EF = 0.088 lb-VOC/1,000 gallons of wine throughput; for wine with ethanol content equal to 10 and less than 12 volume percent, EF = 0.112 lb-VOC/1,000 gallons of wine throughput; and for wine with ethanol content equal to 12 and less than or equal to 14 volume percent, EF = 0.128 lb-VOC/1,000 gallons of wine throughput. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a daily basis, total gallons of wine contained in the tank. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
11. The operator shall maintain records of the calculated 12 month rolling total VOC emissions from the wine storage tanks under permits N-1665-497 through N-1665-506 and N-1665-508 through N-1665-513 (lb per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-514-1

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

16.531 MMBTU/HR NATURAL GAS FIRED CLAYTON SSEG-404-FMB-1 BOILER

PERMIT UNIT REQUIREMENTS

1. The economizer system shall be designed at maximum steam generator firing rate to either 1) reduce the temperature of the economizer flue gas outlet to a value no greater than 90 degrees F above the temperature of the boiler feed water or 2) heat the boiler feed water to a temperature which is no less than the saturation temperature of the steam at the pressure of the steam separator, or 3) reduce the final temperature of the boiler's flue gas to a temperature no greater than 300 degrees F. Feedwater temperature is defined as the temperature of the water stream delivered to the steam generator from the deaerator or feedwater tank. [CCR Title 14, Division 6, Chapter 3, § 15000-15387 (CEQA)]
2. Electric motors driving combustion air fans or induced draft fans shall have an efficiency meeting the standards of the National Electric Manufacturer's Association (NEMA) for "premium efficiency" motors and shall each be operated with a variable speed control or equivalent for control of flow through the fan. [CCR Title 14, Division 6, Chapter 3, § 15000-15387 (CEQA)]
3. The unit shall always operate at least 487 feet away from the nearest property boundary. [District Rule 4102]
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
7. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
8. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7 ppmv NO_x @ 3% O₂ or 0.008 lb-NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.0076 lb-PM₁₀/MMBtu, 50 ppmv CO @ 3% O₂ or 0.037 lb-CO/MMBtu, 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: BRONCO WINE COMPANY

Location: 6342 BYSTRUM RD, CERES, CA 95307

N-1665-514-1 : May 1 2019 9:11AM -- SRANK

11. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
16. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. Fuel sulfur content shall be determined using EPA Method 11 or Method 15. [District Rule 4320] Federally Enforceable Through Title V Permit
21. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
22. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
24. Permittee shall maintain monthly records of the amount of fuel used by this unit. [40 CFR 60.48(c)(g)] Federally Enforceable Through Title V Permit
25. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320 and 40 CFR 60.48(c)(i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-515-2

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

160 BHP (INTERMITTENT) CUMMINS MODEL CFP5E-F50 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801; 17 CCR 93115 and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
5. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 2.52 g-NOx/bhp-hr, 0.746 g-CO/bhp-hr, or 0.092 g-VOC/bhp-hr. [District Rule 2201, 13 CCR 2423, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed 0.098 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102; 13 CCR 2423, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems". Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4102 and 4702; and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1665-516-0

EXPIRATION DATE: 04/30/2018

EQUIPMENT DESCRIPTION:

389 BHP IVECO MODEL F2CE9685A-E DIESEL-FIRED EMERGENCY ENGINE (TIER 3 CERTIFIED) POWERING AN ELECTRICAL GENERATOR.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 2.43 g-NOx/bhp-hr, 0.50 g-CO/bhp-hr, or 0.17 g-VOC/bhp-hr. [District Rule 2201 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed 0.13 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102 and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
10. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
11. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
12. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
14. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
17. U.S. EPA administers the requirements of 40 CFR Part 60 Subpart IIII and 40 CFR Part 63 Subpart ZZZZ. The owner or operator shall comply with the emission and operating limitations, testing requirements, initial and continuous compliance requirements as specified in these subparts. The owner or operator shall submit all applicable notifications, reports, and records to the administrator by the required compliance dates. [District Rules 4001 and 4002] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT C

Detailed Facility List

Permit#	Equipment Description
N-1665-1-5	12.6 MMBTU/HR HURST MODEL 300 NATURAL GAS-FIRED BOILER WITH ST JOHNSON MODEL RX 300F ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION SYSTEM
N-1665-5-5	GASOLINE DISPENSING OPERATION WITH ONE 5,200 CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I ENHANCED VAPOR RECOVERY (EVR) SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-F), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116-F)
N-1665-6-2	2,648 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 21) WITH PRESSURE/VACUUM VALVE
N-1665-7-2	1,999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 22) WITH PRESSURE/VACUUM VALVE
N-1665-8-2	1,999 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 23) WITH PRESSURE/VACUUM VALVE
N-1665-9-2	4,012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 40) WITH PRESSURE/VACUUM VALVE
N-1665-10-2	4,012 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 41) WITH PRESSURE/VACUUM VALVE
N-1665-17-2	6,700 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 59) WITH PRESSURE/VACUUM VALVE
N-1665-18-2	6,652 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 60) WITH PRESSURE/VACUUM VALVE
N-1665-21-2	6,074 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 63) WITH PRESSURE/VACUUM VALVE
N-1665-22-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 71) WITH PRESSURE/VACUUM VALVE
N-1665-23-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 72) WITH PRESSURE/VACUUM VALVE
N-1665-24-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 73) WITH PRESSURE/VACUUM VALVE
N-1665-25-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 74) WITH PRESSURE/VACUUM VALVE
N-1665-26-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 75) WITH PRESSURE/VACUUM VALVE
N-1665-27-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 76) WITH PRESSURE/VACUUM VALVE
N-1665-28-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 77) WITH PRESSURE/VACUUM VALVE
N-1665-29-2	7,148 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 78) WITH PRESSURE/VACUUM VALVE
N-1665-30-2	7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 83) WITH PRESSURE/VACUUM VALVE
N-1665-31-2	7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 84) WITH PRESSURE/VACUUM VALVE
N-1665-32-2	7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 85) WITH PRESSURE/VACUUM VALVE
N-1665-33-2	7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 89) WITH PRESSURE/VACUUM VALVE
N-1665-34-2	7,850 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 90) WITH PRESSURE/VACUUM VALVE
N-1665-38-2	10,093 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 104) WITH PRESSURE/VACUUM VALVE
N-1665-39-2	10,500 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 105) WITH PRESSURE/VACUUM VALVE
N-1665-40-2	10,520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 106) WITH PRESSURE/VACUUM VALVE

Permit#	Equipment Description
N-1665-41-2	10,520 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 107) WITH PRESSURE/VACUUM VALVE
N-1665-42-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 110) WITH PRESSURE/VACUUM VALVE
N-1665-43-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 111) WITH PRESSURE/VACUUM VALVE
N-1665-44-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 112) WITH PRESSURE/VACUUM VALVE
N-1665-45-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 113) WITH PRESSURE/VACUUM VALVE
N-1665-46-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 114) WITH PRESSURE/VACUUM VALVE
N-1665-47-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 115) WITH PRESSURE/VACUUM VALVE
N-1665-48-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 116) WITH PRESSURE/VACUUM VALVE
N-1665-49-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 117) WITH PRESSURE/VACUUM VALVE
N-1665-50-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 118) WITH PRESSURE/VACUUM VALVE
N-1665-51-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 119) WITH PRESSURE/VACUUM VALVE
N-1665-52-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 120) WITH PRESSURE/VACUUM VALVE
N-1665-53-2	12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 121) WITH PRESSURE/VACUUM VALVE
N-1665-54-2	12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 122) WITH PRESSURE/VACUUM VALVE
N-1665-55-2	12,406 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 123) WITH PRESSURE/VACUUM VALVE
N-1665-56-2	11,888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 124) WITH PRESSURE/VACUUM VALVE
N-1665-57-2	11,888 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 125) WITH PRESSURE/VACUUM VALVE
N-1665-58-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 126) WITH PRESSURE/VACUUM VALVE
N-1665-59-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 130) WITH PRESSURE/VACUUM VALVE
N-1665-60-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 131) WITH PRESSURE/VACUUM VALVE
N-1665-61-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 132) WITH PRESSURE/VACUUM VALVE
N-1665-62-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 133) WITH PRESSURE/VACUUM VALVE
N-1665-63-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 134) WITH PRESSURE/VACUUM VALVE
N-1665-64-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 135) WITH PRESSURE/VACUUM VALVE
N-1665-65-2	14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 141) WITH PRESSURE/VACUUM VALVE
N-1665-66-2	14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 142) WITH PRESSURE/VACUUM VALVE
N-1665-67-2	14,771 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 143) WITH PRESSURE/VACUUM VALVE

[illegible]

Permit#	Equipment Description
N-1665-95-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 176) WITH PRESSURE/VACUUM VALVE
N-1665-96-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 177) WITH PRESSURE/VACUUM VALVE
N-1665-97-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 178) WITH PRESSURE/VACUUM VALVE
N-1665-98-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 179) WITH PRESSURE/VACUUM VALVE
N-1665-99-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 180) WITH PRESSURE/VACUUM VALVE
N-1665-100-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 181) WITH PRESSURE/VACUUM VALVE
N-1665-101-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 182) WITH PRESSURE/VACUUM VALVE
N-1665-102-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 183) WITH PRESSURE/VACUUM VALVE
N-1665-103-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 184) WITH PRESSURE/VACUUM VALVE
N-1665-104-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 185) WITH PRESSURE/VACUUM VALVE
N-1665-105-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 186) WITH PRESSURE/VACUUM VALVE
N-1665-106-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 220) WITH PRESSURE/VACUUM VALVE
N-1665-107-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 221) WITH PRESSURE/VACUUM VALVE
N-1665-108-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 222) WITH PRESSURE/VACUUM VALVE
N-1665-109-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 223) WITH PRESSURE/VACUUM VALVE
N-1665-110-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 224) WITH PRESSURE/VACUUM VALVE
N-1665-111-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 225) WITH PRESSURE/VACUUM VALVE
N-1665-112-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 226) WITH PRESSURE/VACUUM VALVE
N-1665-113-2	19,967 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 227) WITH PRESSURE/VACUUM VALVE
N-1665-117-2	24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 251) WITH PRESSURE/VACUUM VALVE
N-1665-118-2	24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 252) WITH PRESSURE/VACUUM VALVE
N-1665-119-2	24,693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 253) WITH PRESSURE/VACUUM VALVE
N-1665-120-2	24,693 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 254) WITH PRESSURE/VACUUM VALVE
N-1665-121-2	24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 255) WITH PRESSURE/VACUUM VALVE
N-1665-122-2	24,863 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 256) WITH PRESSURE/VACUUM VALVE
N-1665-123-2	31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 301) WITH PRESSURE/VACUUM VALVE
N-1665-124-2	31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 302) WITH PRESSURE/VACUUM VALVE

Permit#	Equipment Description
N-1665-125-2	31,562 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 303) WITH PRESSURE/VACUUM VALVE
N-1665-126-2	55,033 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 501) WITH PRESSURE/VACUUM VALVE
N-1665-127-2	54,971 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 502) WITH PRESSURE/VACUUM VALVE
N-1665-128-2	55,017 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 503) WITH PRESSURE/VACUUM VALVE
N-1665-129-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 504) WITH PRESSURE/VACUUM VALVE
N-1665-130-2	54,881 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 505) WITH PRESSURE/VACUUM VALVE
N-1665-131-2	55,141 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 506) WITH PRESSURE/VACUUM VALVE
N-1665-132-2	54,930 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 507) WITH PRESSURE/VACUUM VALVE
N-1665-133-2	55,030 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 508) WITH PRESSURE/VACUUM VALVE
N-1665-134-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 511) WITH PRESSURE/VACUUM VALVE
N-1665-135-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 512) WITH PRESSURE/VACUUM VALVE
N-1665-136-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 513) WITH PRESSURE/VACUUM VALVE
N-1665-137-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 514) WITH PRESSURE/VACUUM VALVE
N-1665-138-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 515) WITH PRESSURE/VACUUM VALVE
N-1665-139-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 516) WITH PRESSURE/VACUUM VALVE
N-1665-140-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 517) WITH PRESSURE/VACUUM VALVE
N-1665-141-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 518) WITH PRESSURE/VACUUM VALVE
N-1665-142-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 519) WITH PRESSURE/VACUUM VALVE
N-1665-143-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 520) WITH PRESSURE/VACUUM VALVE
N-1665-144-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 521) WITH PRESSURE/VACUUM VALVE
N-1665-145-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 522) WITH PRESSURE/VACUUM VALVE
N-1665-146-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 523) WITH PRESSURE/VACUUM VALVE
N-1665-147-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 524) WITH PRESSURE/VACUUM VALVE
N-1665-148-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 525) WITH PRESSURE/VACUUM VALVE
N-1665-149-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 526) WITH PRESSURE/VACUUM VALVE
N-1665-150-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 527) WITH PRESSURE/VACUUM VALVE
N-1665-151-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 528) WITH PRESSURE/VACUUM VALVE

Permit#	Equipment Description
N-1665-152-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 529) WITH PRESSURE/VACUUM VALVE
N-1665-153-2	52,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 530) WITH PRESSURE/VACUUM VALVE
N-1665-154-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1001) WITH PRESSURE/VACUUM VALVE
N-1665-155-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1002) WITH PRESSURE/VACUUM VALVE
N-1665-156-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1003) WITH PRESSURE/VACUUM VALVE
N-1665-157-2	106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1004) WITH PRESSURE/VACUUM VALVE
N-1665-158-2	106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1005) WITH PRESSURE/VACUUM VALVE
N-1665-159-2	106,274 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1006) WITH PRESSURE/VACUUM VALVE
N-1665-160-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1011) WITH PRESSURE/VACUUM VALVE
N-1665-161-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1012) WITH PRESSURE/VACUUM VALVE
N-1665-162-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1013) WITH PRESSURE/VACUUM VALVE
N-1665-163-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1014) WITH PRESSURE/VACUUM VALVE
N-1665-164-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1015) WITH PRESSURE/VACUUM VALVE
N-1665-165-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1016) WITH PRESSURE/VACUUM VALVE
N-1665-166-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1017) WITH PRESSURE/VACUUM VALVE
N-1665-167-2	105,690 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 1018) WITH PRESSURE/VACUUM VALVE
N-1665-168-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1031) WITH PRESSURE/VACUUM VALVE
N-1665-169-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1032) WITH PRESSURE/VACUUM VALVE
N-1665-170-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1033) WITH PRESSURE/VACUUM VALVE
N-1665-171-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1034) WITH PRESSURE/VACUUM VALVE
N-1665-172-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1035) WITH PRESSURE/VACUUM VALVE
N-1665-173-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1036) WITH PRESSURE/VACUUM VALVE
N-1665-174-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1037) WITH PRESSURE/VACUUM VALVE
N-1665-175-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1038) WITH PRESSURE/VACUUM VALVE
N-1665-176-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1039) WITH PRESSURE/VACUUM VALVE
N-1665-177-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1040) WITH PRESSURE/VACUUM VALVE
N-1665-178-2	106,989 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1041) WITH PRESSURE/VACUUM VALVE

[illegible]

[illegible]

Permit#	Equipment Description
N-1665-233-2	13,275 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1304) WITH PRESSURE/VACUUM VALVE
N-1665-234-2	15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1501) WITH PRESSURE/VACUUM VALVE
N-1665-235-2	15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1502) WITH PRESSURE/VACUUM VALVE
N-1665-236-2	15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1503) WITH PRESSURE/VACUUM VALVE
N-1665-237-2	15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1504) WITH PRESSURE/VACUUM VALVE
N-1665-238-2	15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1505) WITH PRESSURE/VACUUM VALVE
N-1665-239-2	15,069 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 1506) WITH PRESSURE/VACUUM VALVE
N-1665-240-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2001) WITH PRESSURE/VACUUM VALVE
N-1665-241-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2002) WITH PRESSURE/VACUUM VALVE
N-1665-242-2	215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2011) WITH PRESSURE/VACUUM VALVE
N-1665-243-2	215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2012) WITH PRESSURE/VACUUM VALVE
N-1665-244-2	215,054 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2013) WITH PRESSURE/VACUUM VALVE
N-1665-245-2	217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2014) WITH PRESSURE/VACUUM VALVE
N-1665-246-2	217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2015) WITH PRESSURE/VACUUM VALVE
N-1665-247-2	217,846 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2016) WITH PRESSURE/VACUUM VALVE
N-1665-248-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2017) WITH PRESSURE/VACUUM VALVE
N-1665-249-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2018) WITH PRESSURE/VACUUM VALVE
N-1665-250-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2019) WITH PRESSURE/VACUUM VALVE
N-1665-251-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2020) WITH PRESSURE/VACUUM VALVE
N-1665-252-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2021) WITH PRESSURE/VACUUM VALVE
N-1665-253-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2022) WITH PRESSURE/VACUUM VALVE
N-1665-254-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2023) WITH PRESSURE/VACUUM VALVE
N-1665-255-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2024) WITH PRESSURE/VACUUM VALVE
N-1665-256-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2025) WITH PRESSURE/VACUUM VALVE
N-1665-257-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2031) WITH PRESSURE/VACUUM VALVE
N-1665-258-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2032) WITH PRESSURE/VACUUM VALVE
N-1665-259-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2033) WITH PRESSURE/VACUUM VALVE

Permit#	Equipment Description
N-1665-260-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2034) WITH PRESSURE/VACUUM VALVE
N-1665-261-2	217,836 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2035) WITH PRESSURE/VACUUM VALVE
N-1665-262-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2051) WITH PRESSURE/VACUUM VALVE
N-1665-263-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2052) WITH PRESSURE/VACUUM VALVE
N-1665-264-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND RED WINE FERMENTATION TANK (TANK 2053) WITH PRESSURE/VACUUM VALVE
N-1665-265-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2054) WITH PRESSURE/VACUUM VALVE
N-1665-266-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2055) WITH PRESSURE/VACUUM VALVE
N-1665-267-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2056) WITH PRESSURE/VACUUM VALVE
N-1665-268-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2057) WITH PRESSURE/VACUUM VALVE
N-1665-269-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2058) WITH PRESSURE/VACUUM VALVE
N-1665-270-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2059) WITH PRESSURE/VACUUM VALVE
N-1665-271-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2060) WITH PRESSURE/VACUUM VALVE
N-1665-272-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2061) WITH PRESSURE/VACUUM VALVE
N-1665-273-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2062) WITH PRESSURE/VACUUM VALVE
N-1665-275-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2072) WITH PRESSURE/VACUUM VALVE
N-1665-276-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2073) WITH PRESSURE/VACUUM VALVE
N-1665-277-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2074) WITH PRESSURE/VACUUM VALVE
N-1665-278-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2075) WITH PRESSURE/VACUUM VALVE
N-1665-279-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2076) WITH PRESSURE/VACUUM VALVE
N-1665-280-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2077) WITH PRESSURE/VACUUM VALVE
N-1665-281-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2078) WITH PRESSURE/VACUUM VALVE
N-1665-282-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2079) WITH PRESSURE/VACUUM VALVE
N-1665-283-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2080) WITH PRESSURE/VACUUM VALVE
N-1665-284-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2081) WITH PRESSURE/VACUUM VALVE
N-1665-285-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2082) WITH PRESSURE/VACUUM VALVE
N-1665-286-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2121) WITH PRESSURE/VACUUM VALVE
N-1665-287-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2122) WITH PRESSURE/VACUUM VALVE

Permit#	Equipment Description
N-1665-288-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2123) WITH PRESSURE/VACUUM VALVE
N-1665-289-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2124) WITH PRESSURE/VACUUM VALVE
N-1665-290-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2125) WITH PRESSURE/VACUUM VALVE
N-1665-291-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2131) WITH PRESSURE/VACUUM VALVE
N-1665-292-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2132) WITH PRESSURE/VACUUM VALVE
N-1665-293-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2133) WITH PRESSURE/VACUUM VALVE
N-1665-294-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2134) WITH PRESSURE/VACUUM VALVE
N-1665-295-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2135) WITH PRESSURE/VACUUM VALVE
N-1665-296-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2141) WITH PRESSURE/VACUUM VALVE
N-1665-297-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2142) WITH PRESSURE/VACUUM VALVE
N-1665-298-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2143) WITH PRESSURE/VACUUM VALVE
N-1665-299-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2144) WITH PRESSURE/VACUUM VALVE
N-1665-300-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2145) WITH PRESSURE/VACUUM VALVE
N-1665-301-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2146) WITH PRESSURE/VACUUM VALVE
N-1665-302-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2151) WITH PRESSURE/VACUUM VALVE
N-1665-303-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2152) WITH PRESSURE/VACUUM VALVE
N-1665-304-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2153) WITH PRESSURE/VACUUM VALVE
N-1665-305-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2154) WITH PRESSURE/VACUUM VALVE
N-1665-306-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2155) WITH PRESSURE/VACUUM VALVE
N-1665-307-2	216,191 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2156) WITH PRESSURE/VACUUM VALVE
N-1665-308-2	24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2401) WITH PRESSURE/VACUUM VALVE
N-1665-309-2	24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2402) WITH PRESSURE/VACUUM VALVE
N-1665-310-2	24,665 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 2403) WITH PRESSURE/VACUUM VALVE
N-1665-311-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3021) WITH PRESSURE/VACUUM VALVE
N-1665-312-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3022) WITH PRESSURE/VACUUM VALVE
N-1665-313-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3023) WITH PRESSURE/VACUUM VALVE
N-1665-314-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3024) WITH PRESSURE/VACUUM VALVE

[illegible]

[illegible]

[illegible]

Permit#	Equipment Description
N-1665-397-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3138) WITH PRESSURE/VACUUM VALVE
N-1665-398-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3139) WITH PRESSURE/VACUUM VALVE
N-1665-399-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3140) WITH PRESSURE/VACUUM VALVE
N-1665-400-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3146) WITH PRESSURE/VACUUM VALVE
N-1665-401-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3147) WITH PRESSURE/VACUUM VALVE
N-1665-402-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3148) WITH PRESSURE/VACUUM VALVE
N-1665-403-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3149) WITH PRESSURE/VACUUM VALVE
N-1665-404-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3150) WITH PRESSURE/VACUUM VALVE
N-1665-405-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3156) WITH PRESSURE/VACUUM VALVE
N-1665-406-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3157) WITH PRESSURE/VACUUM VALVE
N-1665-407-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3158) WITH PRESSURE/VACUUM VALVE
N-1665-408-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3159) WITH PRESSURE/VACUUM VALVE
N-1665-409-2	350,450 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 3160) WITH PRESSURE/VACUUM VALVE
N-1665-410-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5001) WITH PRESSURE/VACUUM VALVE
N-1665-411-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5002) WITH PRESSURE/VACUUM VALVE
N-1665-412-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5003) WITH PRESSURE/VACUUM VALVE
N-1665-413-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5004) WITH PRESSURE/VACUUM VALVE
N-1665-414-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5005) WITH PRESSURE/VACUUM VALVE
N-1665-415-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5006) WITH PRESSURE/VACUUM VALVE
N-1665-416-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5007) WITH PRESSURE/VACUUM VALVE
N-1665-417-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5008) WITH PRESSURE/VACUUM VALVE
N-1665-418-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5009) WITH PRESSURE/VACUUM VALVE
N-1665-419-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5010) WITH PRESSURE/VACUUM VALVE
N-1665-420-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5011) WITH PRESSURE/VACUUM VALVE
N-1665-421-2	5,048 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 5012) WITH PRESSURE/VACUUM VALVE
N-1665-422-2	625,878 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 6004) WITH PRESSURE/VACUUM VALVE
N-1665-423-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7001) WITH PRESSURE/VACUUM VALVE

Permit#	Equipment Description
N-1665-424-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7002) WITH PRESSURE/VACUUM VALVE
N-1665-425-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7003) WITH PRESSURE/VACUUM VALVE
N-1665-426-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7005) WITH PRESSURE/VACUUM VALVE
N-1665-427-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7006) WITH PRESSURE/VACUUM VALVE
N-1665-428-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7007) WITH PRESSURE/VACUUM VALVE
N-1665-429-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7008) WITH PRESSURE/VACUUM VALVE
N-1665-430-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7009) WITH PRESSURE/VACUUM VALVE
N-1665-431-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7010) WITH PRESSURE/VACUUM VALVE
N-1665-432-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7011) WITH PRESSURE/VACUUM VALVE
N-1665-433-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7012) WITH PRESSURE/VACUUM VALVE
N-1665-434-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7013) WITH PRESSURE/VACUUM VALVE
N-1665-435-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7014) WITH PRESSURE/VACUUM VALVE
N-1665-436-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7015) WITH PRESSURE/VACUUM VALVE
N-1665-437-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7016) WITH PRESSURE/VACUUM VALVE
N-1665-438-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7041) WITH PRESSURE/VACUUM VALVE
N-1665-439-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7042) WITH PRESSURE/VACUUM VALVE
N-1665-440-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7043) WITH PRESSURE/VACUUM VALVE
N-1665-441-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7044) WITH PRESSURE/VACUUM VALVE
N-1665-442-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7051) WITH PRESSURE/VACUUM VALVE
N-1665-443-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7052) WITH PRESSURE/VACUUM VALVE
N-1665-444-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7053) WITH PRESSURE/VACUUM VALVE
N-1665-445-2	703,546 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK 7054) WITH PRESSURE/VACUUM VALVE
N-1665-446-2	10,040 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK A164) WITH PRESSURE/VACUUM VALVE
N-1665-447-2	1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C1) WITH PRESSURE/VACUUM VALVE
N-1665-448-2	1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C2) WITH PRESSURE/VACUUM VALVE
N-1665-449-2	1,948 GALLON STAINLESS STEEL WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK C3) WITH PRESSURE/VACUUM VALVE
N-1665-452-2	94.5 BHP CATERPILLAR MODEL C4.4 (2442/1800) TIER 2 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR
N-1665-496-1	WINERY WASTEWATER TREATMENT OPERATION

Permit#	Equipment Description
N-1665-497-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1410) WITH PRESSURE/VACUUM VALVE
N-1665-498-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1411) WITH PRESSURE/VACUUM VALVE
N-1665-499-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1412) WITH A PRESSURE/VACUUM VALVE
N-1665-500-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1413) WITH A PRESSURE/VACUUM VALVE
N-1665-501-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1414) WITH PRESSURE/VACUUM VALVE
N-1665-502-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1415) WITH PRESSURE/VACUUM VALVE
N-1665-503-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1416) WITH PRESSURE/VACUUM VALVE
N-1665-504-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1417) WITH A PRESSURE/VACUUM VALVE
N-1665-505-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1418) WITH A PRESSURE/VACUUM VALVE
N-1665-506-4	14,218 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 1419) WITH A PRESSURE/VACUUM VALVE
N-1665-507-3	170 BHP (INTERMITTENT) CUMMINS MODEL CFP5E-F50 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP
N-1665-508-3	23,609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B231) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING
N-1665-509-3	23,609 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B232) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING
N-1665-510-3	14,376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B141) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING
N-1665-511-3	14,376 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B142) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING
N-1665-512-3	7,290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B71) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING
N-1665-513-3	7,290 GALLON STAINLESS STEEL WINE STORAGE TANK (TANK B72) WITH PRESSURE/VACUUM VALVE LOCATED INSIDE A CLIMATE CONTROLLED BUILDING
N-1665-514-1	16.531 MMBTU/HR NATURAL GAS FIRED CLAYTON SSEG-404-FMB-1 BOILER
N-1665-515-2	160 BHP (INTERMITTENT) CUMMINS MODEL CFP5E-F50 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP
N-1665-516-0	389 BHP IVECO MODEL F2CE9685A-E DIESEL-FIRED EMERGENCY ENGINE (TIER 3 CERTIFIED) POWERING AN ELECTRICAL GENERATOR.